

Tabella di capacità

Sistema VRF Serie IV8-670WV2RN1E(PRO)

Tabella della capacità di raffreddamento

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
130%	-15	53,67	7,38	60,22	7,81	75,42	9,16	83,02	9,38	88,87	9,58	93,54	9,59	94,60	5,34
	-10	53,67	8,33	60,22	8,81	75,42	10,34	83,02	10,59	88,87	10,81	93,54	10,81	94,60	6,03
	-5	53,67	9,30	60,22	9,83	75,42	11,53	83,02	11,81	88,87	12,06	93,54	12,06	94,60	6,72
	-2	53,67	9,88	60,22	10,44	75,42	12,26	83,02	12,56	88,87	12,82	93,54	12,82	94,60	7,15
	0	53,67	10,28	60,22	10,86	75,42	12,75	83,02	13,05	88,87	13,33	93,54	13,33	94,60	7,43
	2	53,67	10,67	60,22	11,28	75,42	13,24	83,02	13,56	88,87	13,84	93,54	13,84	94,60	7,72
	4	53,67	11,07	60,22	11,70	75,42	13,73	83,02	14,06	88,87	14,36	93,54	14,37	94,60	8,01
	6	53,67	11,47	60,22	12,13	75,42	14,23	83,02	14,58	88,87	14,88	93,54	14,89	94,60	8,30
	8	53,67	11,87	60,22	12,55	75,42	14,73	83,02	15,09	88,87	15,40	93,54	15,41	94,60	8,59
	10	53,67	12,28	60,22	12,99	75,42	15,23	83,02	15,61	88,87	15,93	93,54	15,93	94,60	8,89
	12	53,67	12,69	60,22	13,42	75,42	15,74	83,02	16,13	88,87	16,46	93,54	16,47	94,60	9,18
	14	53,67	13,10	60,22	13,85	75,42	16,25	83,02	16,65	88,87	16,99	93,54	17,00	94,60	9,48
	16	53,67	13,52	60,22	14,29	75,42	16,77	83,02	17,18	88,87	17,53	93,54	17,54	94,60	9,78
	18	53,67	13,93	60,22	14,73	75,42	17,28	83,02	17,70	88,87	18,07	93,54	18,08	94,60	10,08
	20	53,67	14,35	60,22	15,17	75,42	17,80	83,02	18,24	88,87	18,62	93,54	18,62	94,60	10,39
	21	53,67	14,57	60,22	15,39	75,42	18,07	83,02	18,51	88,87	18,89	93,54	18,90	94,60	10,54
	23	53,67	14,99	60,22	15,85	75,42	18,59	83,02	19,04	88,87	19,44	93,54	19,45	94,60	10,85
	25	53,67	15,41	60,22	16,30	75,42	19,12	83,02	19,59	88,87	19,99	93,54	20,00	94,60	11,15
	27	53,67	15,85	60,22	16,75	75,42	19,65	83,02	20,14	88,87	20,55	93,54	20,56	94,60	11,47
	29	53,67	16,28	60,22	17,21	75,42	20,19	83,02	20,68	88,87	21,11	93,54	21,12	94,60	11,78
	31	53,67	16,71	60,22	17,66	75,42	20,73	83,02	21,23	88,30	21,54	93,54	21,69	94,60	12,09
	33	53,67	17,15	60,22	18,13	74,38	20,98	78,29	20,55	82,21	20,58	90,04	21,42	94,60	12,41
	35	53,67	17,59	60,22	18,59	69,93	20,23	72,49	19,52	76,12	19,54	83,37	20,34	90,62	12,19
	37	53,67	17,96	60,11	18,96	68,65	20,28	70,61	19,41	74,14	19,43	81,20	20,23	88,26	12,13
	39	52,62	17,98	60,11	19,35	66,65	20,10	69,38	19,47	72,85	19,50	79,79	20,29	86,73	12,16
	41	52,62	18,35	60,11	19,75	65,25	20,08	68,15	19,52	71,56	19,55	78,38	20,34	85,19	12,19
	43	52,73	18,76	58,35	19,56	63,58	19,96	66,92	19,56	70,27	19,58	76,96	20,38	83,66	12,22
	46	51,92	18,84	56,13	19,19	62,41	19,99	65,70	19,58	68,98	19,61	75,55	20,41	82,12	12,23
	48	47,01	17,56	51,15	18,00	57,16	18,85	60,17	18,47	63,18	18,49	69,20	19,25	75,22	11,54
	50	42,37	16,13	48,02	17,23	53,67	18,04	56,49	17,67	59,31	17,70	64,96	18,42	70,61	11,04
	52	39,61	15,38	44,89	16,42	50,17	17,19	52,81	16,84	55,45	16,86	60,73	17,55	66,01	10,52
	55	36,84	14,57	41,76	15,56	46,67	16,29	49,13	15,96	51,58	15,98	56,49	16,63	61,41	9,97
120%	-15	50,40	7,22	56,71	7,65	70,74	8,95	78,22	9,20	84,77	9,51	90,98	9,70	92,74	5,45
	-10	50,40	8,15	56,71	8,64	70,74	10,09	78,22	10,39	84,77	10,73	90,98	10,95	92,74	6,15
	-5	50,40	9,09	56,71	9,64	70,74	11,26	78,22	11,59	84,77	11,98	90,98	12,21	92,74	6,86
	-2	50,40	9,66	56,71	10,24	70,74	11,97	78,22	12,31	84,77	12,73	90,98	12,99	92,74	7,30
	0	50,40	10,04	56,71	10,65	70,74	12,45	78,22	12,81	84,77	13,24	90,98	13,50	92,74	7,59
	2	50,40	10,43	56,71	11,06	70,74	12,92	78,22	13,30	84,77	13,74	90,98	14,02	92,74	7,88
	4	50,40	10,82	56,71	11,47	70,74	13,41	78,22	13,79	84,77	14,26	90,98	14,54	92,74	8,17
	6	50,40	11,22	56,71	11,89	70,74	13,89	78,22	14,30	84,77	14,77	90,98	15,07	92,74	8,47
	8	50,40	11,60	56,71	12,31	70,74	14,38	78,22	14,80	84,77	15,29	90,98	15,60	92,74	8,77
	10	50,40	12,01	56,71	12,73	70,74	14,87	78,22	15,31	84,77	15,82	90,98	16,13	92,74	9,07
	12	50,40	12,41	56,71	13,15	70,74	15,37	78,22	15,81	84,77	16,35	90,98	16,67	92,74	9,37
	14	50,40	12,81	56,71	13,58	70,74	15,87	78,22	16,33	84,77	16,87	90,98	17,21	92,74	9,68
	16	50,40	13,21	56,71	14,01	70,74	16,37	78,22	16,85	84,77	17,41	90,98	17,76	92,74	9,98
	18	50,40	13,62	56,71	14,44	70,74	16,87	78,22	17,36	84,77	17,95	90,98	18,30	92,74	10,29
	20	50,40	14,03	56,71	14,87	70,74	17,38	78,22	17,89	84,77	18,49	90,98	18,86	92,74	10,60
	21	50,40	14,24	56,71	15,09	70,74	17,64	78,22	18,15	84,77	18,76	90,98	19,13	92,74	10,76
	23	50,40	14,65	56,71	15,53	70,74	18,15	78,22	18,68	84,77	19,31	90,98	19,69	92,74	11,07
	25	50,40	15,07	56,71	15,98	70,74	18,67	78,22	19,21	84,77	19,85	90,98	20,26	92,74	11,39
	27	50,40	15,49	56,71	16,42	70,74	19,19	78,22	19,75	84,77	20,41	90,98	20,81	92,74	11,70
	29	50,40	15,91	56,71	16,87	70,74	19,72	78,22	20,29	84,77	20,96	90,98	21,38	92,74	12,02
	31	50,40	16,33	56,71	17,32	70,74	20,24	78,22	20,83	84,77	21,52	90,98	21,96	92,74	12,35
	33	50,40	16,77	56,71	17,77	70,74	20,77	76,20	20,82	80,00	20,85	87,62	21,70	92,74	12,67
	35	50,40	17,19	56,71	18,23	68,65	20,68	70,55	19,77	74,08	19,80	81,13	20,61	88,19	12,35
	37	50,40	17,56	56,71	18,62	66,31	20,39	68,38	19,57	71,80	19,60	78,64	20,40	85,48	12,23
	39	50,40	17,93	56,71	19,01	65,60	20,59	67,19	19,63	70,55	19,65	77,27	20,46	83,99	12,26
	41	49,50	17,97	56,48	19,31	63,97	20,49	66,00	19,68	69,30	19,70	75,90	20,51	82,50	12,29
	43	49,46	18,32	56,48	19,70	61,87	20,22	64,81	19,72	68,05	19,74	74,53	20,55	81,01	12,32
	46	49,58	18,73	54,14	19,27	60,44	20,15	63,62	19,74	66,80	19,77	73,17	20,58	79,53	12,33
	48	46,18	17,97	49,53	18,15	55,36	19,01	58,27	18,62	61,19	18,64	67,01	19,40	72,84	11,63
	50	41,03	16,27	46,50	17,37	51,97	18,19	54,71	17,82	57,44	17,84	62,91	18,57	68,38	11,13
	52	38,36	15,50	43,47	16,55	48,58	17,33	51,14	16,97	53,70	16,99	58,81	17,69	63,93	10,61
	55	35,68	14,69	40,44	15,68	45,20	16,42	47,57	16,09	49,95	16,11	54,71	16,77	59,47	10,05

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
110%	-15	47,01	7,03	53,67	7,56	65,96	8,70	72,96	8,96	79,05	9,26	89,11	9,92	90,15	5,53
	-10	47,01	7,93	53,67	8,53	65,96	9,82	72,96	10,11	79,05	10,44	89,11	11,19	90,15	6,24
	-5	47,01	8,84	53,67	9,52	65,96	10,95	72,96	11,28	79,05	11,65	89,11	12,48	90,15	6,96
	-2	47,01	9,40	53,67	10,11	65,96	11,64	72,96	11,99	79,05	12,38	89,11	13,27	90,15	7,40
	0	47,01	9,78	53,67	10,51	65,96	12,11	72,96	12,46	79,05	12,88	89,11	13,80	90,15	7,70
	2	47,01	10,16	53,67	10,92	65,96	12,58	72,96	12,95	79,05	13,37	89,11	14,33	90,15	8,00
	4	47,01	10,53	53,67	11,33	65,96	13,04	72,96	13,43	79,05	13,88	89,11	14,87	90,15	8,29
	6	47,01	10,91	53,67	11,74	65,96	13,52	72,96	13,91	79,05	14,38	89,11	15,41	90,15	8,59
	8	47,01	11,30	53,67	12,15	65,96	13,99	72,96	14,41	79,05	14,89	89,11	15,95	90,15	8,90
	10	47,01	11,69	53,67	12,57	65,96	14,47	72,96	14,90	79,05	15,39	89,11	16,49	90,15	9,20
	12	47,01	12,08	53,67	12,99	65,96	14,95	72,96	15,39	79,05	15,91	89,11	17,04	90,15	9,51
	14	47,01	12,46	53,67	13,41	65,96	15,44	72,96	15,90	79,05	16,42	89,11	17,60	90,15	9,82
	16	47,01	12,86	53,67	13,83	65,96	15,93	72,96	16,40	79,05	16,94	89,11	18,15	90,15	10,12
	18	47,01	13,26	53,67	14,26	65,96	16,42	72,96	16,91	79,05	17,46	89,11	18,71	90,15	10,44
	20	47,01	13,66	53,67	14,69	65,96	16,91	72,96	17,41	79,05	17,99	89,11	19,28	90,15	10,75
	21	47,01	13,86	53,67	14,90	65,96	17,16	72,96	17,67	79,05	18,25	89,11	19,56	90,15	10,91
	23	47,01	14,26	53,67	15,34	65,96	17,66	72,96	18,19	79,05	18,79	89,11	20,13	90,15	11,23
	25	47,01	14,67	53,67	15,78	65,96	18,17	72,96	18,70	79,05	19,32	89,11	20,70	90,15	11,55
	27	47,01	15,07	53,67	16,22	65,96	18,67	72,96	19,22	79,05	19,86	89,11	21,28	90,15	11,87
	29	47,01	15,49	53,67	16,66	65,96	19,18	72,96	19,75	79,05	20,40	89,11	21,85	90,15	12,19
	31	47,01	15,90	53,67	17,11	65,96	19,69	72,96	20,27	79,05	20,95	89,11	22,44	90,15	12,52
	33	47,01	16,32	53,67	17,55	65,96	20,21	72,72	20,74	76,36	20,76	83,63	21,62	90,15	12,85
	35	47,01	16,74	53,67	18,00	65,83	20,69	68,75	20,11	70,70	19,72	77,44	20,53	84,17	12,31
	37	47,01	17,09	53,67	18,39	65,83	21,13	67,71	20,22	69,23	19,72	75,23	20,37	81,78	12,21
	39	47,01	17,45	53,67	18,77	64,43	21,11	66,42	20,25	67,50	19,62	73,93	20,43	80,35	12,24
	41	47,01	17,81	53,67	19,15	62,67	20,96	64,43	20,05	66,30	19,67	72,62	20,48	78,93	12,28
	43	47,01	18,17	53,67	19,54	60,69	20,71	62,20	19,75	65,11	19,71	71,31	20,52	77,51	12,30
	46	46,07	18,16	52,04	19,33	57,82	20,12	60,87	19,71	63,91	19,73	70,00	20,54	76,08	12,31
	48	42,91	17,42	47,39	18,12	52,96	18,98	55,75	18,59	58,54	18,61	64,11	19,38	69,69	11,61
	50	39,76	16,45	44,49	17,34	49,72	18,16	52,34	17,79	54,96	17,81	60,19	18,54	65,42	11,12
	52	36,70	15,48	41,59	16,52	46,48	17,30	48,93	16,95	51,37	16,97	56,27	17,66	61,16	10,59
	55	34,14	14,67	38,69	15,66	43,24	16,40	45,51	16,07	47,79	16,08	52,34	16,74	56,89	10,04
100%	-15	43,38	6,79	49,70	7,32	61,51	8,49	67,35	8,65	73,43	9,00	85,25	9,92	88,52	5,68
	-10	43,38	7,65	49,70	8,26	61,51	9,58	67,35	9,76	73,43	10,15	85,25	11,20	88,52	6,41
	-5	43,38	8,54	49,70	9,21	61,51	10,69	67,35	10,89	73,43	11,32	85,25	12,50	88,52	7,15
	-2	43,38	9,08	49,70	9,80	61,51	11,36	67,35	11,58	73,43	12,04	85,25	13,28	88,52	7,60
	0	43,38	9,44	49,70	10,19	61,51	11,81	67,35	12,04	73,43	12,51	85,25	13,81	88,52	7,91
	2	43,38	9,80	49,70	10,58	61,51	12,27	67,35	12,50	73,43	13,00	85,25	14,34	88,52	8,21
	4	43,38	10,17	49,70	10,98	61,51	12,73	67,35	12,97	73,43	13,48	85,25	14,88	88,52	8,52
	6	43,38	10,54	49,70	11,37	61,51	13,19	67,35	13,44	73,43	13,97	85,25	15,42	88,52	8,83
	8	43,38	10,91	49,70	11,77	61,51	13,65	67,35	13,91	73,43	14,47	85,25	15,96	88,52	9,14
	10	43,38	11,29	49,70	12,18	61,51	14,12	67,35	14,39	73,43	14,96	85,25	16,50	88,52	9,45
	12	43,38	11,66	49,70	12,58	61,51	14,59	67,35	14,87	73,43	15,46	85,25	17,06	88,52	9,77
	14	43,38	12,04	49,70	12,99	61,51	15,06	67,35	15,35	73,43	15,96	85,25	17,61	88,52	10,08
	16	43,38	12,41	49,70	13,40	61,51	15,54	67,35	15,84	73,43	16,47	85,25	18,17	88,52	10,40
	18	43,38	12,80	49,70	13,81	61,51	16,02	67,35	16,32	73,43	16,97	85,25	18,72	88,52	10,72
	20	43,38	13,19	49,70	14,23	61,51	16,50	67,35	16,82	73,43	17,48	85,25	19,29	88,52	11,05
	21	43,38	13,38	49,70	14,44	61,51	16,74	67,35	17,06	73,43	17,74	85,25	19,57	88,52	11,21
	23	43,38	13,77	49,70	14,86	61,51	17,23	67,35	17,56	73,43	18,25	85,25	20,14	88,52	11,54
	25	43,38	14,16	49,70	15,29	61,51	17,72	67,35	18,06	73,43	18,77	85,25	20,72	88,52	11,86
	27	43,38	14,55	49,70	15,71	61,51	18,22	67,35	18,56	73,43	19,30	85,25	21,30	88,52	12,19
	29	43,38	14,95	49,70	16,14	61,51	18,71	67,35	19,07	73,43	19,83	85,25	21,87	88,52	12,53
	31	43,38	15,35	49,70	16,57	61,51	19,21	67,35	19,58	73,43	20,36	85,25	22,46	88,52	12,86
	33	43,38	15,76	49,70	17,01	61,51	19,72	67,35	20,09	73,43	20,89	83,21	22,50	88,52	13,20
	35	43,38	16,16	49,70	17,44	61,51	20,22	67,00	20,50	70,35	20,53	77,05	21,37	83,75	12,81
	37	43,38	16,50	49,70	17,81	61,51	20,65	65,85	20,58	69,15	20,60	75,73	21,45	82,32	12,85
	39	43,38	16,84	49,70	18,18	61,51	21,08	64,71	20,64	67,94	20,66	74,41	21,51	80,89	12,90
	41	43,38	17,19	49,70	18,56	60,80	21,27	63,56	20,69	66,74	20,72	73,10	21,57	79,45	12,93
	43	43,38	17,54	49,70	18,93	59,30	21,16	62,42	20,73	65,54	20,76	71,78	21,60	78,02	12,95
	46	43,38	17,89	49,70	19,31	58,21	21,19	61,27	20,76	64,33	20,78	70,46	21,64	76,59	12,97
	48	42,09	17,87	47,70	19,08	53,31	19,98	56,12	19,58	58,93	19,60	64,54	20,40	70,15	12,23
	50	39,51	17,11	44,78	18,26	50,05	19,12	52,68	18,73	55,32	18,76	60,59	19,52	65,86	11,71
	52	36,94	16,30	41,86	17,40	46,79	18,22	49,25	17,85	51,71	17,87	56,64	18,60	61,56	11,15
	55	34,36	15,44	38,94	16,49	43,53	17,27	45,82	16,92	48,11	16,94	52,69	17,63	57,27	10,57

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
90%	-15	39,05	5,90	44,67	6,36	54,96	7,33	60,34	7,49	65,83	7,79	76,82	8,64	84,67	5,26
	-10	39,05	6,66	44,67	7,18	54,96	8,27	60,34	8,46	65,83	8,79	76,82	9,75	84,67	5,93
	-5	39,05	7,43	44,67	8,01	54,96	9,23	60,34	9,43	65,83	9,81	76,82	10,88	84,67	6,61
	-2	39,05	7,90	44,67	8,51	54,96	9,81	60,34	10,02	65,83	10,43	76,82	11,57	84,67	7,03
	0	39,05	8,21	44,67	8,85	54,96	10,20	60,34	10,43	65,83	10,85	76,82	12,03	84,67	7,31
	2	39,05	8,53	44,67	9,19	54,96	10,60	60,34	10,83	65,83	11,26	76,82	12,49	84,67	7,59
	4	39,05	8,84	44,67	9,53	54,96	10,99	60,34	11,23	65,83	11,68	76,82	12,96	84,67	7,88
	6	39,05	9,16	44,67	9,88	54,96	11,39	60,34	11,64	65,83	12,11	76,82	13,43	84,67	8,16
	8	39,05	9,49	44,67	10,23	54,96	11,79	60,34	12,04	65,83	12,53	76,82	13,90	84,67	8,45
	10	39,05	9,82	44,67	10,58	54,96	12,19	60,34	12,46	65,83	12,96	76,82	14,38	84,67	8,74
	12	39,05	10,14	44,67	10,93	54,96	12,60	60,34	12,87	65,83	13,39	76,82	14,85	84,67	9,03
	14	39,05	10,47	44,67	11,29	54,96	13,01	60,34	13,29	65,83	13,83	76,82	15,34	84,67	9,32
	16	39,05	10,80	44,67	11,64	54,96	13,42	60,34	13,71	65,83	14,26	76,82	15,82	84,67	9,62
	18	39,05	11,13	44,67	12,00	54,96	13,83	60,34	14,13	65,83	14,70	76,82	16,31	84,67	9,91
	20	39,05	11,47	44,67	12,36	54,96	14,25	60,34	14,56	65,83	15,15	76,82	16,80	84,67	10,21
	21	39,05	11,64	44,67	12,55	54,96	14,46	60,34	14,77	65,83	15,37	76,82	17,05	84,67	10,36
	23	39,05	11,98	44,67	12,91	54,96	14,88	60,34	15,21	65,83	15,82	76,82	17,55	84,67	10,66
	25	39,05	12,32	44,67	13,28	54,96	15,31	60,34	15,64	65,83	16,27	76,82	18,05	84,67	10,97
	27	39,05	12,67	44,67	13,65	54,96	15,73	60,34	16,07	65,83	16,72	76,82	18,55	84,67	11,27
	29	39,05	13,01	44,67	14,02	54,96	16,16	60,34	16,51	65,83	17,18	76,82	19,05	84,67	11,58
	31	39,05	13,36	44,67	14,40	54,96	16,59	60,34	16,96	65,83	17,64	76,82	19,57	84,67	11,89
	33	39,05	13,71	44,67	14,77	54,96	17,02	60,34	17,40	65,83	18,10	76,82	20,07	84,67	12,20
	35	39,05	14,06	44,67	15,16	54,96	17,46	60,34	17,85	65,83	18,56	76,82	20,59	83,75	12,38
	37	39,05	14,36	44,67	15,48	54,96	17,83	60,34	18,22	65,83	18,96	72,43	19,82	78,72	11,88
	39	39,05	14,65	44,67	15,80	54,96	18,20	60,34	18,61	63,85	18,77	67,81	18,94	73,71	11,36
	41	39,05	14,95	44,67	16,12	54,96	18,58	60,22	18,95	62,79	18,84	66,61	18,99	72,40	11,39
	43	39,05	15,26	44,67	16,45	54,73	18,88	58,59	18,81	60,92	18,65	65,41	19,03	71,10	11,41
	46	39,05	15,56	44,67	16,77	53,04	18,66	56,48	18,49	58,62	18,30	64,21	19,05	69,79	11,42
	48	38,36	15,75	43,47	16,81	48,58	17,60	51,14	17,24	53,70	17,26	58,81	17,97	63,92	10,77
	50	36,01	15,06	40,81	16,08	45,61	16,84	48,01	16,50	50,41	16,52	55,21	17,19	60,01	10,31
	52	33,66	14,35	38,15	15,32	42,64	16,05	44,88	15,72	47,12	15,74	51,61	16,38	56,10	9,82
	55	31,31	13,60	35,49	14,52	39,66	15,21	41,75	14,90	43,84	14,92	48,01	15,53	52,19	9,31
80%	-15	34,73	5,05	39,76	5,44	49,70	6,38	53,67	6,41	58,69	6,68	68,29	7,39	78,11	4,66
	-10	34,73	5,70	39,76	6,14	49,70	7,20	53,67	7,23	58,69	7,54	68,29	8,34	78,11	5,26
	-5	34,73	6,35	39,76	6,86	49,70	8,03	53,67	8,07	58,69	8,41	68,29	9,30	78,11	5,87
	-2	34,73	6,76	39,76	7,28	49,70	8,53	53,67	8,58	58,69	8,95	68,29	9,89	78,11	6,24
	0	34,73	7,03	39,76	7,58	49,70	8,87	53,67	8,91	58,69	9,30	68,29	10,28	78,11	6,49
	2	34,73	7,30	39,76	7,87	49,70	9,21	53,67	9,26	58,69	9,65	68,29	10,68	78,11	6,74
	4	34,73	7,57	39,76	8,16	49,70	9,56	53,67	9,60	58,69	10,02	68,29	11,08	78,11	6,99
	6	34,73	7,84	39,76	8,46	49,70	9,90	53,67	9,96	58,69	10,38	68,29	11,48	78,11	7,24
	8	34,73	8,12	39,76	8,76	49,70	10,25	53,67	10,31	58,69	10,75	68,29	11,88	78,11	7,50
	10	34,73	8,39	39,76	9,05	49,70	10,60	53,67	10,66	58,69	11,12	68,29	12,29	78,11	7,75
	12	34,73	8,68	39,76	9,36	49,70	10,96	53,67	11,02	58,69	11,49	68,29	12,70	78,11	8,01
	14	34,73	8,96	39,76	9,66	49,70	11,31	53,67	11,37	58,69	11,86	68,29	13,11	78,11	8,27
	16	34,73	9,24	39,76	9,97	49,70	11,67	53,67	11,73	58,69	12,23	68,29	13,52	78,11	8,53
	18	34,73	9,53	39,76	10,28	49,70	12,03	53,67	12,09	58,69	12,61	68,29	13,94	78,11	8,79
	20	34,73	9,81	39,76	10,58	49,70	12,40	53,67	12,46	58,69	12,99	68,29	14,37	78,11	9,06
	21	34,73	9,96	39,76	10,74	49,70	12,58	53,67	12,64	58,69	13,18	68,29	14,58	78,11	9,20
	23	34,73	10,25	39,76	11,05	49,70	12,94	53,67	13,01	58,69	13,56	68,29	15,00	78,11	9,46
	25	34,73	10,54	39,76	11,37	49,70	13,31	53,67	13,38	58,69	13,95	68,29	15,43	78,11	9,73
	27	34,73	10,83	39,76	11,68	49,70	13,68	53,67	13,75	58,69	14,34	68,29	15,86	78,11	10,01
	29	34,73	11,13	39,76	12,00	49,70	14,05	53,67	14,13	58,69	14,73	68,29	16,29	78,11	10,28
	31	34,73	11,42	39,76	12,32	49,70	14,43	53,67	14,50	58,69	15,12	68,29	16,72	78,11	10,55
	33	34,73	11,72	39,76	12,65	49,70	14,81	53,67	14,89	58,69	15,52	68,29	17,16	78,11	10,83
	35	34,73	12,03	39,76	12,97	49,70	15,19	53,67	15,27	58,69	15,92	68,29	17,60	78,11	11,10
	37	34,73	12,28	39,76	13,24	49,70	15,51	53,67	15,59	58,69	16,25	68,29	17,98	78,11	11,34
	39	34,73	12,54	39,76	13,52	49,70	15,83	53,67	15,91	58,69	16,59	67,80	18,22	73,70	10,92
	41	34,73	12,80	39,76	13,80	49,70	16,16	53,67	16,24	58,47	16,87	63,18	17,33	68,67	10,39
	43	34,73	13,05	39,76	14,08	48,64	16,13	53,56	16,54	58,47	17,21	61,51	17,21	63,98	9,87
	46	34,73	13,32	39,76	14,36	48,64	16,46	52,27	16,46	56,48	16,96	58,35	16,65	62,80	9,89
	48	34,51	13,62	39,12	14,55	45,72	15,93	47,71	15,47	48,32	14,94	52,92	15,55	57,52	9,32
	50	33,91	13,64	36,72	13,92	41,04	14,58	43,20	14,28	45,36	14,30	49,68	14,88	54,00	8,92
	52	30,99	12,71	34,33	13,26	38,37	13,89	40,39	13,61	42,40	13,62	46,44	14,18	50,48	8,50
	55	28,18	11,77	31,93	12,57	35,69	13,16	37,57	12,89	39,45	12,91	43,20	13,44	46,96	8,05

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
70%	-15	30,41	4,23	34,73	4,55	43,38	5,32	47,83	5,46	52,15	5,68	59,76	6,19	68,87	3,93
	-10	30,41	4,77	34,73	5,13	43,38	6,00	47,83	6,16	52,15	6,40	59,76	6,98	68,87	4,43
	-5	30,41	5,32	34,73	5,73	43,38	6,70	47,83	6,88	52,15	7,14	59,76	7,78	68,87	4,95
	-2	30,41	5,65	34,73	6,08	43,38	7,12	47,83	7,31	52,15	7,60	59,76	8,27	68,87	5,26
	0	30,41	5,88	34,73	6,33	43,38	7,40	47,83	7,60	52,15	7,90	59,76	8,60	68,87	5,47
	2	30,41	6,10	34,73	6,57	43,38	7,69	47,83	7,89	52,15	8,21	59,76	8,93	68,87	5,68
	4	30,41	6,34	34,73	6,82	43,38	7,98	47,83	8,19	52,15	8,51	59,76	9,27	68,87	5,89
	6	30,41	6,56	34,73	7,06	43,38	8,27	47,83	8,48	52,15	8,82	59,76	9,60	68,87	6,10
	8	30,41	6,79	34,73	7,31	43,38	8,56	47,83	8,78	52,15	9,13	59,76	9,94	68,87	6,32
	10	30,41	7,03	34,73	7,57	43,38	8,85	47,83	9,08	52,15	9,44	59,76	10,28	68,87	6,54
	12	30,41	7,26	34,73	7,82	43,38	9,15	47,83	9,38	52,15	9,75	59,76	10,63	68,87	6,76
	14	30,41	7,50	34,73	8,07	43,38	9,44	47,83	9,69	52,15	10,07	59,76	10,97	68,87	6,97
	16	30,41	7,73	34,73	8,32	43,38	9,74	47,83	9,99	52,15	10,39	59,76	11,32	68,87	7,20
	18	30,41	7,97	34,73	8,58	43,38	10,04	47,83	10,30	52,15	10,71	59,76	11,67	68,87	7,41
	20	30,41	8,21	34,73	8,84	43,38	10,34	47,83	10,61	52,15	11,03	59,76	12,02	68,87	7,64
	21	30,41	8,34	34,73	8,97	43,38	10,49	47,83	10,77	52,15	11,20	59,76	12,19	68,87	7,75
	23	30,41	8,58	34,73	9,23	43,38	10,80	47,83	11,08	52,15	11,52	59,76	12,55	68,87	7,97
	25	30,41	8,82	34,73	9,49	43,38	11,11	47,83	11,40	52,15	11,85	59,76	12,90	68,87	8,21
	27	30,41	9,06	34,73	9,75	43,38	11,42	47,83	11,71	52,15	12,18	59,76	13,27	68,87	8,43
	29	30,41	9,32	34,73	10,02	43,38	11,73	47,83	12,03	52,15	12,51	59,76	13,62	68,87	8,66
	31	30,41	9,56	34,73	10,29	43,38	12,04	47,83	12,36	52,15	12,85	59,76	13,99	68,87	8,90
	33	30,41	9,81	34,73	10,56	43,38	12,36	47,83	12,68	52,15	13,19	59,76	14,36	68,87	9,13
	35	30,41	10,07	34,73	10,83	43,38	12,68	47,83	13,00	52,15	13,52	59,76	14,73	68,87	9,36
	37	30,41	10,28	34,73	11,06	43,38	12,94	47,83	13,28	52,15	13,81	59,76	15,04	68,87	9,56
	39	30,41	10,49	34,73	11,29	43,38	13,21	47,83	13,56	52,15	14,10	59,76	15,35	68,87	9,76
	41	30,41	10,71	34,73	11,52	43,38	13,49	47,83	13,84	52,15	14,38	59,76	15,67	68,67	9,93
	43	30,41	10,93	34,73	11,76	43,38	13,76	47,83	14,11	52,15	14,68	58,59	15,67	63,65	9,39
	46	30,41	11,14	34,73	11,99	43,38	14,03	47,83	14,40	51,10	14,67	56,71	15,48	58,63	8,82
	48	30,41	11,47	34,73	12,35	41,63	13,86	43,96	13,63	47,83	14,14	48,41	13,60	51,09	7,92
	50	29,93	11,52	34,02	12,33	39,18	13,30	40,69	12,86	40,93	12,33	44,00	12,60	47,83	7,55
	52	26,89	10,54	31,22	11,53	33,98	11,76	35,77	11,52	37,56	11,53	41,13	12,01	44,71	7,20
	55	24,96	9,97	28,28	10,65	31,61	11,15	33,27	10,91	34,94	10,93	38,27	11,38	41,59	6,82
60%	-15	26,07	3,44	29,82	3,71	37,19	4,33	40,93	4,43	44,67	4,62	52,15	5,12	58,93	3,19
	-10	26,07	3,88	29,82	4,18	37,19	4,89	40,93	5,01	44,67	5,21	52,15	5,78	58,93	3,60
	-5	26,07	4,33	29,82	4,67	37,19	5,45	40,93	5,58	44,67	5,81	52,15	6,45	58,93	4,01
	-2	26,07	4,60	29,82	4,96	37,19	5,79	40,93	5,93	44,67	6,18	52,15	6,85	58,93	4,27
	0	26,07	4,79	29,82	5,16	37,19	6,02	40,93	6,17	44,67	6,42	52,15	7,13	58,93	4,44
	2	26,07	4,97	29,82	5,36	37,19	6,25	40,93	6,41	44,67	6,67	52,15	7,40	58,93	4,61
	4	26,07	5,16	29,82	5,56	37,19	6,49	40,93	6,65	44,67	6,92	52,15	7,68	58,93	4,79
	6	26,07	5,34	29,82	5,76	37,19	6,72	40,93	6,89	44,67	7,17	52,15	7,95	58,93	4,96
	8	26,07	5,53	29,82	5,96	37,19	6,96	40,93	7,13	44,67	7,42	52,15	8,24	58,93	5,13
	10	26,07	5,72	29,82	6,17	37,19	7,20	40,93	7,38	44,67	7,68	52,15	8,52	58,93	5,31
	12	26,07	3,44	29,82	3,71	37,19	4,33	40,93	4,44	44,67	4,62	52,15	5,13	58,93	5,48
	14	26,07	3,55	29,82	3,83	37,19	4,47	40,93	4,59	44,67	4,77	52,15	5,29	58,93	5,66
	16	26,07	3,66	29,82	3,95	37,19	4,62	40,93	4,73	44,67	4,92	52,15	5,46	58,93	5,84
	18	26,07	3,78	29,82	4,07	37,19	4,75	40,93	4,87	44,67	5,07	52,15	5,63	58,93	6,02
	20	26,07	3,90	29,82	4,20	37,19	4,90	40,93	5,02	44,67	5,23	52,15	5,80	58,93	6,20
	21	26,07	3,95	29,82	4,26	37,19	4,97	40,93	5,09	44,67	5,30	52,15	5,88	58,93	6,29
	23	26,07	4,06	29,82	4,38	37,19	5,12	40,93	5,24	44,67	5,46	52,15	6,05	58,93	6,48
	25	26,07	4,18	29,82	4,50	37,19	5,26	40,93	5,39	44,67	5,61	52,15	6,22	58,93	6,66
	27	26,07	4,30	29,82	4,63	37,19	5,41	40,93	5,54	44,67	5,76	52,15	6,40	58,93	6,85
	29	26,07	4,42	29,82	4,75	37,19	5,56	40,93	5,70	44,67	5,93	52,15	6,57	58,93	7,03
	31	26,07	4,54	29,82	4,89	37,19	5,71	40,93	5,85	44,67	6,08	52,15	6,75	58,93	7,22
	33	26,07	4,65	29,82	5,01	37,19	5,85	40,93	6,00	44,67	6,24	52,15	6,93	58,93	7,41
	35	26,07	4,77	29,82	5,14	37,19	6,00	40,93	6,15	44,67	6,40	52,15	7,11	58,93	7,60
	37	26,07	4,87	29,82	5,25	37,19	6,13	40,93	6,29	44,67	6,54	52,15	7,26	58,93	7,77
	39	26,07	4,97	29,82	5,36	37,19	6,26	40,93	6,41	44,67	6,67	52,15	7,41	58,93	7,92
	41	26,07	5,07	29,82	5,47	37,19	6,39	40,93	6,54	44,67	6,81	52,15	7,56	58,93	8,09
	43	26,07	5,18	29,82	5,58	37,19	6,52	40,93	6,68	44,67	6,95	52,15	7,71	58,93	8,25
	46	26,07	5,28	29,82	5,69	37,19	6,65	40,93	6,81	44,67	7,09	52,15	7,87	58,63	8,37
	48	26,07	5,44	29,82	5,86	37,19	6,84	40,93	7,01	42,91	7,01	47,93	7,45	51,09	7,51
	50	26,07	5,55	29,82	5,97	35,01	6,57	37,78	6,60	39,40	6,56	42,38	6,71	46,06	6,91
	52	25,61	5,55	27,91	5,70	31,45	6,02	32,98	5,87	34,47	5,85	37,75	6,09	41,04	6,27
	55	22,69	5,01	24,53	5,11	27,42	5,34	28,86	5,24	30,31	5,24	33,19	5,46	36,08	5,61

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
50%	-15	21,76	1,57	24,78	1,69	30,99	1,98	34,14	2,03	37,19	2,11	43,38	2,33	49,70	2,53
	-10	21,76	1,78	24,78	1,91	30,99	2,23	34,14	2,29	37,19	2,38	43,38	2,63	49,70	2,85
	-5	21,76	1,98	24,78	2,13	30,99	2,49	34,14	2,55	37,19	2,65	43,38	2,94	49,70	3,19
	-2	21,76	2,10	24,78	2,26	30,99	2,65	34,14	2,71	37,19	2,82	43,38	3,12	49,70	3,39
	0	21,76	2,19	24,78	2,35	30,99	2,75	34,14	2,82	37,19	2,93	43,38	3,25	49,70	3,53
	2	21,76	2,27	24,78	2,44	30,99	2,85	34,14	2,93	37,19	3,04	43,38	3,37	49,70	3,66
	4	21,76	2,36	24,78	2,53	30,99	2,96	34,14	3,04	37,19	3,16	43,38	3,50	49,70	3,80
	6	21,76	2,44	24,78	2,62	30,99	3,07	34,14	3,15	37,19	3,27	43,38	3,63	49,70	3,93
	8	21,76	2,53	24,78	2,72	30,99	3,18	34,14	3,26	37,19	3,39	43,38	3,75	49,70	4,07
	10	21,76	2,62	24,78	2,80	30,99	3,29	34,14	3,37	37,19	3,50	43,38	3,88	49,70	4,21
	12	21,76	2,70	24,78	2,90	30,99	3,40	34,14	3,48	37,19	3,62	43,38	4,01	49,70	4,35
	14	21,76	2,79	24,78	2,99	30,99	3,51	34,14	3,59	37,19	3,73	43,38	4,14	49,70	4,49
	16	21,76	2,88	24,78	3,09	30,99	3,62	34,14	3,71	37,19	3,85	43,38	4,27	49,70	4,64
	18	21,76	2,97	24,78	3,19	30,99	3,73	34,14	3,83	37,19	3,97	43,38	4,40	49,70	4,78
	20	21,76	3,05	24,78	3,28	30,99	3,84	34,14	3,94	37,19	4,09	43,38	4,54	49,70	4,92
	21	21,76	3,10	24,78	3,32	30,99	3,90	34,14	4,00	37,19	4,15	43,38	4,60	49,70	4,99
	23	21,76	3,19	24,78	3,43	30,99	4,01	34,14	4,12	37,19	4,27	43,38	4,74	49,70	5,14
	25	21,76	3,28	24,78	3,52	30,99	4,13	34,14	4,23	37,19	4,39	43,38	4,87	49,70	5,29
	27	21,76	3,37	24,78	3,62	30,99	4,24	34,14	4,35	37,19	4,52	43,38	5,01	49,70	5,43
	29	21,76	3,46	24,78	3,72	30,99	4,36	34,14	4,47	37,19	4,64	43,38	5,14	49,70	5,58
	31	21,76	3,56	24,78	3,82	30,99	4,47	34,14	4,59	37,19	4,76	43,38	5,28	49,70	5,73
	33	21,76	3,65	24,78	3,92	30,99	4,59	34,14	4,70	37,19	4,89	43,38	5,42	49,70	5,88
	35	21,76	3,74	24,78	4,02	30,99	4,71	34,14	4,83	37,19	5,01	43,38	5,56	49,70	6,03
	37	21,76	3,83	24,78	4,10	30,99	4,81	34,14	4,93	37,19	5,12	43,38	5,68	49,70	6,16
	39	21,76	3,90	24,78	4,19	30,99	4,91	34,14	5,03	37,19	5,23	43,38	5,80	49,70	6,29
	41	21,76	3,98	24,78	4,28	30,99	5,01	34,14	5,14	37,19	5,33	43,38	5,92	49,70	6,42
	43	21,76	4,06	24,78	4,36	30,99	5,11	34,14	5,24	37,19	5,44	43,38	6,03	49,70	6,55
	46	21,76	4,15	24,78	4,45	30,99	5,21	34,14	5,34	37,19	5,55	43,38	6,15	49,70	6,68
	48	21,76	4,27	24,78	4,58	30,99	5,37	34,14	5,50	37,19	5,71	43,38	6,34	49,70	6,88
	50	21,76	4,35	24,78	4,67	30,99	5,47	34,14	5,61	37,19	5,83	42,38	6,31	46,06	6,50
	52	21,76	4,43	24,78	4,76	30,99	5,58	32,83	5,50	34,47	5,51	37,75	5,73	41,04	5,90
	55	21,61	4,49	24,49	4,79	27,37	5,02	28,81	4,92	30,25	4,92	33,13	5,13	36,01	5,28

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

Tabella di capacità

Sistema VRF Serie IV8-670WV2RN1E(PRO)

Tabella della capacità di riscaldamento

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	-29.8	-30.0	47,19	12,96	46,28	13,41	45,38	13,86	44,93	14,07	44,47	14,32	43,57	14,76
	-25.0	-25.4	47,19	13,17	46,28	13,57	45,38	13,95	44,93	14,14	44,47	14,34	43,57	14,73
	-19.8	-20.0	47,19	13,39	46,28	13,73	45,38	14,05	44,93	14,21	44,47	14,37	43,57	14,71
	-18.8	-19.0	47,19	13,41	46,28	13,72	45,38	14,05	44,93	14,21	44,47	14,36	43,57	14,69
	-16.7	-17.0	47,19	13,39	46,28	13,71	45,38	14,00	44,93	14,17	44,47	14,32	43,92	14,75
	-13.7	-15.0	47,19	13,44	46,64	13,86	45,83	14,19	45,42	14,34	45,02	14,52	44,19	14,85
	-11.8	-13.0	47,77	13,55	46,94	13,84	46,86	14,40	46,48	14,56	46,10	14,75	45,35	15,10
	-9.8	-11.0	48,93	13,77	48,16	14,10	47,39	14,47	47,01	14,61	46,62	14,78	45,85	15,15
	-9.5	-10.0	49,20	13,73	48,43	14,07	47,65	14,39	47,26	14,57	46,87	14,73	46,09	15,06
	-8.5	-9.1	49,45	13,75	48,67	14,10	47,87	14,43	47,48	14,60	47,09	14,76	46,29	15,08
	-7.0	-7.6	49,84	13,79	49,04	14,11	48,24	14,43	47,84	14,58	47,44	14,74	46,63	15,09
	-5.0	-5.6	49,51	13,55	48,70	13,87	47,89	14,17	47,48	14,35	47,08	14,52	46,26	14,81
	-3.0	-3.7	51,30	13,75	50,46	14,06	49,62	14,38	49,20	14,54	48,78	14,68	47,93	15,01
	0.0	-0.7	55,65	14,39	54,74	14,71	53,83	15,06	53,38	15,22	52,92	15,38	52,00	15,72
	3.0	2.2	62,42	15,61	61,42	15,96	60,41	16,33	59,90	16,52	59,39	16,68	58,37	17,06
	5.0	4.1	67,92	16,61	66,84	17,01	65,76	17,39	65,22	17,56	64,68	17,78	63,58	18,17
	7.0	6.0	77,62	18,59	76,13	18,95	74,64	19,32	73,89	19,50	73,15	19,70	71,65	19,57
	9.0	7.9	80,11	18,79	78,57	19,17	77,02	19,54	76,25	19,72	75,49	19,92	72,59	18,90
	11.0	9.8	82,59	19,00	81,01	19,37	79,42	19,75	78,62	19,95	77,83	19,86	72,59	18,00
	13.0	11.8	85,07	19,15	83,44	19,56	81,80	19,95	80,99	20,01	79,84	19,37	72,59	16,84
	15.0	13.7	87,56	19,31	85,88	19,75	84,19	20,15	83,35	19,67	79,84	18,48	72,59	15,73
	18.0	16,6	91,28	19,81	89,53	20,23	87,10	19,08	83,49	17,57	79,84	16,13	72,59	13,40
	20.0	19,6	95,01	20,09	93,18	19,91	87,10	17,97	83,49	16,50	79,84	15,04	72,59	12,42
	23.0	22,4	98,74	20,37	94,36	19,06	87,10	16,49	83,49	15,07	79,84	13,76	72,59	11,48
	26.0	25,3	98,74	19,30	94,36	17,47	87,10	14,77	83,49	13,47	79,84	12,27	72,59	10,38
	30.0	28,1	101,77	18,85	94,36	16,02	87,10	13,22	83,49	12,03	79,84	10,94	72,59	9,38
120%	-29.8	-30.0	45,12	12,69	44,26	13,16	43,38	13,59	42,95	13,83	42,51	14,01	41,65	14,47
	-25.0	-25.4	45,12	12,91	44,26	13,30	43,38	13,67	42,95	13,88	42,51	14,05	41,65	14,44
	-19.8	-20.0	45,12	13,14	44,26	13,44	43,38	13,76	42,95	13,93	42,51	14,09	41,65	14,41
	-18.8	-19.0	45,12	13,13	44,26	13,44	43,38	13,75	42,95	13,90	42,51	14,05	41,65	14,38
	-16.7	-17.0	45,12	13,14	44,26	13,43	43,76	13,86	43,37	14,01	42,98	14,16	42,20	14,50
	-13.7	-15.0	45,61	13,33	44,82	13,65	44,69	14,18	44,34	14,33	43,98	14,52	43,27	14,89
	-11.8	-13.0	46,67	13,57	45,94	13,91	45,22	14,23	44,85	14,42	44,49	14,59	43,76	14,94
	-9.8	-11.0	47,21	13,63	46,46	13,97	45,72	14,28	45,35	14,45	44,97	14,62	44,22	14,96
	-9.5	-10.0	47,47	13,57	46,71	13,92	45,96	14,23	45,58	14,39	45,19	14,56	44,43	14,90
	-8.5	-9.1	47,70	13,61	46,94	13,94	46,17	14,25	45,78	14,42	45,40	14,58	44,63	14,92
	-7.0	-7.6	48,06	13,62	47,28	13,96	46,51	14,28	46,11	14,43	45,72	14,59	44,93	14,92
	-5.0	-5.6	47,70	13,42	46,92	13,72	46,13	14,03	45,74	14,19	45,35	14,35	44,55	14,66
	-3.0	-3.7	49,44	13,61	48,62	13,92	47,81	14,23	47,40	14,38	46,99	14,54	46,17	14,85
	0.0	-0.7	53,64	14,25	52,76	14,59	51,88	14,92	51,43	15,08	50,98	15,23	50,09	15,57
	3.0	2.2	60,18	15,50	59,21	15,88	58,24	16,21	57,75	16,39	57,25	16,56	55,86	16,40
	5.0	4.1	65,53	16,53	64,48	16,92	63,43	17,31	62,90	17,50	62,37	17,67	60,30	16,89
	7.0	6.0	74,21	18,36	72,78	18,73	71,90	19,25	71,26	19,42	70,47	19,26	67,00	17,89
	9.0	7.9	76,59	18,58	75,11	18,96	74,24	19,49	73,49	19,49	72,16	18,86	67,00	16,79
	11.0	9.8	78,96	18,79	77,44	19,18	76,56	19,67	75,17	19,01	73,71	18,39	67,00	15,71
	13.0	11.8	81,33	18,99	80,36	19,51	78,20	19,23	77,06	18,54	73,71	17,41	67,00	14,62
	15.0	13.7	83,71	19,21	82,75	19,75	80,40	18,84	77,06	17,65	73,71	16,27	67,00	13,59
	18.0	16,6	87,27	19,68	85,59	18,75	80,40	16,38	77,06	15,10	73,71	13,86	67,00	11,75
	20.0	19,6	90,83	19,40	87,10	18,04	80,40	15,31	77,06	14,02	73,71	12,86	67,00	10,83
	23.0	22,4	93,81	18,95	87,10	16,52	80,40	14,02	77,06	12,85	73,71	11,83	67,00	9,91
	26.0	25,3	93,81	17,31	87,10	14,82	80,40	12,48	77,06	11,55	73,71	10,70	67,00	8,97
	30.0	28,1	93,81	15,82	87,10	13,29	80,40	11,11	77,06	10,39	73,71	9,69	67,00	8,13

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
110%	-29.8	-30.0	42,62	12,33	41,80	12,79	40,98	13,19	40,57	13,44	40,16	13,61	39,34	14,03
	-25.0	-25.4	42,62	12,53	41,80	12,91	40,98	13,28	40,57	13,47	40,16	13,63	39,34	14,00
	-19.8	-20.0	42,62	12,74	41,80	13,05	40,98	13,37	40,57	13,50	40,49	13,76	39,76	14,11
	-18.8	-19.0	42,62	12,75	41,80	13,04	41,34	13,46	40,98	13,61	40,61	13,80	39,89	14,13
	-16.7	-17.0	43,09	12,88	42,35	13,21	42,25	13,72	41,92	13,89	41,58	14,08	40,92	14,44
	-13.7	-15.0	44,12	13,25	43,43	13,58	42,75	13,94	42,41	14,10	42,07	14,28	41,38	14,62
	-11.8	-13.0	44,64	13,32	43,93	13,66	43,23	14,00	42,88	14,15	42,52	14,33	41,82	14,67
	-9.8	-11.0	45,12	13,40	44,40	13,72	43,68	14,03	43,32	14,19	42,96	14,35	42,23	14,69
	-9.5	-10.0	45,35	13,36	44,63	13,66	43,90	13,97	43,53	14,14	43,17	14,29	42,42	14,63
	-8.5	-9.1	45,56	13,39	44,83	13,68	44,09	14,00	43,72	14,16	43,34	14,31	42,60	14,64
	-7.0	-7.6	45,89	13,41	45,14	13,70	44,39	14,03	44,01	14,17	43,64	14,33	42,88	14,64
	-5.0	-5.6	45,52	13,19	44,76	13,49	44,01	13,78	43,62	13,94	43,25	14,07	42,48	14,39
	-3.0	-3.7	47,17	13,39	46,38	13,69	45,60	13,99	45,20	14,13	44,81	14,28	44,01	14,57
	0.0	-0.7	51,16	14,08	50,32	14,37	49,47	14,69	49,04	14,85	48,62	15,00	47,27	14,81
	3.0	2.2	57,45	15,32	56,52	15,68	55,57	16,02	55,10	16,19	54,39	15,92	52,41	15,06
	5.0	4.1	62,60	16,40	61,60	16,74	60,58	17,14	59,85	16,95	58,78	16,39	56,53	15,24
	7.0	6.0	70,85	18,19	69,61	18,58	68,27	18,70	67,28	18,15	66,05	17,58	61,43	15,50
	9.0	7.9	73,15	18,43	71,87	18,86	70,14	18,31	68,87	17,72	67,56	17,11	61,43	14,48
	11.0	9.8	75,44	18,70	74,07	18,97	71,72	17,84	70,64	17,28	67,56	16,03	61,43	13,50
	13.0	11.8	77,76	18,92	75,99	18,59	73,71	17,45	70,64	16,18	67,56	14,90	61,43	12,50
	15.0	13.7	80,02	19,03	77,55	18,09	73,71	16,33	70,64	15,07	67,56	13,87	61,43	11,73
	18.0	16,6	82,44	17,86	79,84	16,18	73,71	13,89	70,64	12,78	67,56	11,93	61,43	10,30
	20.0	19,6	85,80	17,45	79,84	15,08	73,71	12,83	70,64	11,82	67,56	11,04	61,43	9,44
	23.0	22,4	85,99	16,08	79,84	13,86	73,71	11,87	70,64	10,89	67,56	10,15	61,43	8,51
	26.0	25,3	85,99	14,42	79,84	12,33	73,71	10,72	70,64	9,97	67,56	9,20	61,43	7,60
	30.0	28,1	85,99	12,92	79,84	10,97	73,71	9,67	70,64	9,13	67,56	8,35	61,43	6,78
100%	-29.8	-30.0	42,36	12,70	41,55	13,09	40,74	13,51	40,33	13,72	39,92	13,93	39,11	14,33
	-25.0	-25.4	42,36	12,86	41,55	13,22	40,74	13,58	40,33	13,77	39,92	13,96	39,11	14,31
	-19.8	-20.0	42,36	13,03	41,55	13,35	40,74	13,66	40,33	13,81	40,24	14,09	39,52	14,45
	-18.8	-19.0	42,36	13,05	41,55	13,35	41,09	13,78	40,74	13,97	40,37	14,12	39,65	14,47
	-16.7	-17.0	42,84	13,20	42,09	13,51	41,99	14,05	41,66	14,24	41,33	14,42	40,67	14,79
	-13.7	-15.0	43,84	13,57	43,17	13,92	42,50	14,27	42,16	14,44	41,82	14,63	41,14	14,99
	-11.8	-13.0	44,36	13,67	43,67	14,01	42,97	14,33	42,62	14,50	42,27	14,68	41,58	15,03
	-9.8	-11.0	44,85	13,75	44,14	14,07	43,42	14,40	43,06	14,57	42,70	14,74	41,99	15,07
	-9.5	-10.0	45,08	13,71	44,36	14,01	43,64	14,33	43,27	14,51	42,91	14,67	42,18	15,00
	-8.5	-9.1	45,28	13,74	44,56	14,05	43,83	14,38	43,45	14,53	43,09	14,70	42,35	15,02
	-7.0	-7.6	45,60	13,77	44,87	14,07	44,12	14,39	43,76	14,56	43,38	14,71	42,62	15,03
	-5.0	-5.6	45,22	13,58	44,48	13,87	43,73	14,19	43,35	14,34	42,98	14,48	41,90	14,34
	-3.0	-3.7	46,86	13,81	46,08	14,11	45,30	14,39	44,91	14,56	44,51	14,72	43,08	14,11
	0.0	-0.7	50,83	14,53	49,99	14,86	49,14	15,17	48,63	15,16	47,82	14,97	46,12	13,81
	3.0	2.2	57,08	15,87	56,15	16,20	54,90	16,07	53,97	15,92	53,01	15,28	50,99	13,82
	5.0	4.1	62,18	16,96	61,18	17,34	59,30	16,56	58,24	16,25	56,34	15,25	54,41	13,78
	7.0	6.0	70,38	18,88	68,94	18,69	67,00	17,85	64,21	16,79	61,43	15,56	55,84	13,20
	9.0	7.9	72,66	19,17	70,53	18,28	67,00	16,93	64,21	15,73	61,43	14,53	55,84	12,27
	11.0	9.8	74,71	18,84	72,59	17,94	67,00	15,83	64,21	14,68	61,43	13,55	55,84	11,60
	13.0	11.8	76,37	18,35	72,59	17,01	67,00	14,70	64,21	13,61	61,43	12,51	55,84	10,84
	15.0	13.7	78,18	17,92	72,59	15,89	67,00	13,69	64,21	12,66	61,43	11,77	55,84	10,12
	18.0	16,6	78,18	15,53	72,59	13,47	67,00	11,75	64,21	11,02	61,43	10,30	55,84	8,93
	20.0	19,6	78,18	14,51	72,59	12,42	67,00	10,85	64,21	10,12	61,43	9,39	55,84	8,03
	23.0	22,4	78,18	13,27	72,59	11,55	67,00	9,96	64,21	9,20	61,43	8,47	55,84	7,30
	26.0	25,3	78,18	11,84	72,59	10,42	67,00	9,05	64,21	8,29	61,43	7,57	55,84	6,63
	30.0	28,1	78,18	10,56	72,59	9,41	67,00	8,22	64,21	7,47	61,43	6,76	55,84	6,02

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
90%	-29.8	-30.0	38,13	11,80	37,39	12,18	36,66	12,58	36,30	12,75	35,93	12,99	35,20	13,36
	-25.0	-25.4	38,13	11,97	37,39	12,31	36,66	12,65	36,30	12,81	35,93	13,00	35,20	13,33
	-19.8	-20.0	38,69	12,33	38,65	12,87	38,06	13,22	37,77	13,40	37,48	13,58	36,89	13,94
	-18.8	-19.0	39,49	12,60	38,90	12,94	38,30	13,30	37,99	13,47	37,70	13,64	37,09	14,01
	-16.7	-17.0	39,97	12,74	39,35	13,08	38,73	13,42	38,42	13,59	38,11	13,77	37,48	14,11
	-13.7	-15.0	40,41	12,97	39,78	13,27	39,14	13,60	38,82	13,78	38,50	13,94	37,87	14,28
	-11.8	-13.0	40,84	13,04	40,18	13,36	39,53	13,67	39,20	13,83	38,88	13,98	38,22	14,33
	-9.8	-11.0	41,23	13,11	40,56	13,42	39,89	13,73	39,56	13,88	39,22	14,05	38,36	14,00
	-9.5	-10.0	41,41	13,07	40,74	13,36	40,06	13,69	39,72	13,84	39,38	13,99	38,36	13,61
	-8.5	-9.1	41,58	13,11	40,89	13,41	40,21	13,72	39,86	13,86	39,52	14,03	38,36	13,36
	-7.0	-7.6	41,83	13,15	41,14	13,44	40,44	13,75	40,09	13,91	39,70	13,94	38,36	12,92
	-5.0	-5.6	41,41	12,97	40,73	13,25	40,03	13,52	39,64	13,60	39,01	13,33	37,71	12,25
	-3.0	-3.7	42,91	13,20	42,18	13,47	41,42	13,68	40,79	13,42	40,13	13,11	38,77	12,00
	0.0	-0.7	46,57	13,92	45,78	14,22	44,48	13,94	43,77	13,41	43,04	12,84	41,51	11,69
	3.0	2.2	52,37	15,27	51,04	15,06	49,41	14,11	48,57	13,50	47,70	12,90	45,89	11,62
	5.0	4.1	56,97	16,08	55,21	15,56	53,37	14,30	52,41	13,62	50,71	12,78	48,97	11,64
	7.0	6.0	64,76	17,45	62,04	16,42	60,30	15,10	57,80	14,04	55,28	13,00	50,26	11,25
	9.0	7.9	65,50	16,87	63,47	15,75	60,30	14,11	57,80	13,07	55,28	12,14	50,26	10,52
	11.0	9.8	67,24	16,49	65,33	15,14	60,30	13,11	57,80	12,19	55,28	11,43	50,26	9,90
	13.0	11.8	68,73	15,70	65,33	14,05	60,30	12,19	57,80	11,43	55,28	10,75	50,26	9,20
	15.0	13.7	70,36	14,99	65,33	13,07	60,30	11,43	57,80	10,75	55,28	10,05	50,26	8,48
	18.0	16,6	70,36	12,64	65,33	11,28	60,30	10,00	57,80	9,39	55,28	8,80	50,26	7,74
	20.0	19,6	70,36	11,78	65,33	10,36	60,30	9,15	57,80	8,45	55,28	7,88	50,26	7,08
	23.0	22,4	70,36	10,89	65,33	9,46	60,30	8,25	57,80	7,60	55,28	7,20	50,26	6,44
	26.0	25,3	70,36	9,86	65,33	8,53	60,30	7,39	57,80	6,88	55,28	6,52	50,26	5,77
	30.0	28,1	70,36	8,94	65,33	7,70	60,30	6,62	57,80	6,22	55,28	5,90	50,26	5,17
80%	-29.8	-30.0	33,89	10,92	33,24	11,28	32,59	11,64	32,27	11,81	31,94	12,00	31,28	11,66
	-25.0	-25.4	34,30	11,22	33,72	11,56	33,71	12,10	33,46	12,30	33,21	12,50	32,30	12,38
	-19.8	-20.0	35,86	11,89	35,30	12,22	34,75	12,55	34,47	12,72	34,21	12,90	33,65	13,25
	-18.8	-19.0	36,06	11,97	35,49	12,29	34,93	12,62	34,65	12,78	34,38	12,94	33,81	13,30
	-16.7	-17.0	36,43	12,11	35,86	12,41	35,28	12,74	34,99	12,89	34,71	13,04	34,10	13,33
	-13.7	-15.0	36,78	12,30	36,19	12,61	35,60	12,92	35,30	13,08	35,00	13,23	34,10	13,09
	-11.8	-13.0	37,11	12,39	36,50	12,69	35,89	12,98	35,59	13,14	35,29	13,28	34,10	12,72
	-9.8	-11.0	37,41	12,47	36,80	12,75	36,17	13,03	35,87	13,19	35,29	12,95	34,10	12,26
	-9.5	-10.0	37,56	12,43	36,93	12,72	36,31	13,00	35,87	12,86	35,29	12,54	34,10	11,81
	-8.5	-9.1	37,68	12,47	37,06	12,76	36,42	13,03	35,87	12,60	35,29	12,22	34,10	11,46
	-7.0	-7.6	37,89	12,53	37,25	12,78	36,42	12,70	35,87	12,23	35,29	11,85	34,10	11,04
	-5.0	-5.6	37,47	12,33	36,82	12,61	35,78	12,10	35,23	11,65	34,68	11,23	33,52	10,41
	-3.0	-3.7	38,80	12,57	37,92	12,44	36,82	11,91	36,25	11,43	35,67	10,99	34,46	10,08
	0.0	-0.7	41,94	12,90	40,76	12,51	39,54	11,59	38,90	11,12	38,26	10,64	36,90	9,75
	3.0	2.2	46,74	13,64	45,36	12,66	43,93	11,61	43,17	11,11	42,41	10,59	40,79	9,88
	5.0	4.1	50,63	13,88	49,08	12,82	47,44	11,74	46,60	11,18	45,08	10,64	43,53	9,97
	7.0	6.0	57,56	14,78	55,15	13,44	53,60	12,32	51,38	11,62	49,13	10,89	44,67	9,57
	9.0	7.9	58,22	13,95	56,42	12,82	53,61	11,62	51,38	10,89	49,13	10,15	44,67	8,66
	11.0	9.8	59,77	13,38	58,07	12,26	53,61	10,89	51,38	10,25	49,13	9,57	44,67	8,11
	13.0	11.8	61,10	12,67	58,07	11,49	53,61	10,20	51,38	9,52	49,13	8,87	44,67	7,61
	15.0	13.7	62,53	12,06	58,07	10,82	53,61	9,49	51,38	8,80	49,13	8,16	44,67	7,24
	18.0	16,6	62,53	10,50	58,07	9,44	53,61	8,36	51,38	7,88	49,13	7,52	44,67	6,68
	20.0	19,6	62,53	9,66	58,07	8,51	53,61	7,57	51,38	7,22	49,13	6,88	44,67	6,16
	23.0	22,4	62,53	8,77	58,07	7,61	53,61	6,89	51,38	6,56	49,13	6,24	44,67	5,63
	26.0	25,3	62,53	7,84	58,07	6,88	53,61	6,22	51,38	5,92	49,13	5,60	44,67	4,88
	30.0	28,1	62,53	7,00	58,07	6,23	53,61	5,62	51,38	5,34	49,13	5,02	44,67	4,23

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
70%	-29.8	-30.0	30,02	10,15	29,96	10,63	29,53	11,07	29,24	11,11	28,20	10,53	27,37	10,13
	-25.0	-25.4	31,37	10,78	30,90	11,11	30,43	11,48	30,16	11,59	29,69	11,43	28,63	10,96
	-19.8	-20.0	32,24	11,26	31,73	11,57	31,22	11,86	30,96	12,03	30,71	12,19	29,84	11,80
	-18.8	-19.0	32,38	11,32	31,87	11,61	31,36	11,93	31,10	12,09	30,84	12,24	29,84	11,59
	-16.7	-17.0	32,67	11,47	32,13	11,73	31,61	12,04	31,35	12,20	30,88	11,98	29,84	11,27
	-13.7	-15.0	32,93	11,66	32,39	11,94	31,85	12,23	31,38	12,01	30,88	11,79	29,84	11,00
	-11.8	-13.0	33,18	11,73	32,63	12,00	31,87	11,91	31,38	11,69	30,88	11,43	29,84	10,61
	-9.8	-11.0	33,41	11,80	32,81	11,97	31,87	11,61	31,38	11,31	30,88	10,93	29,84	10,11
	-9.5	-10.0	33,53	11,77	32,81	11,66	31,87	11,22	31,38	10,92	30,88	10,53	29,84	9,70
	-8.5	-9.1	33,63	11,82	32,81	11,44	31,87	10,91	31,38	10,60	30,88	10,19	29,84	9,32
	-7.0	-7.6	33,73	11,72	32,81	11,13	31,87	10,57	31,38	10,23	30,88	9,80	29,84	8,94
	-5.0	-5.6	33,12	11,19	32,23	10,58	31,30	9,99	30,83	9,65	30,34	9,22	29,33	8,44
	-3.0	-3.7	34,11	11,04	33,18	10,39	32,22	9,69	31,72	9,31	31,21	8,94	30,15	8,21
	0.0	-0.7	36,70	10,86	35,67	10,12	34,60	9,36	34,04	9,00	33,47	8,74	32,29	8,17
	3.0	2.2	40,91	10,95	39,69	10,14	38,43	9,44	37,78	9,16	37,11	8,88	35,70	8,32
	5.0	4.1	44,31	11,06	42,94	10,21	41,51	9,60	40,76	9,34	39,44	8,85	38,09	8,27
	7.0	6.0	50,37	11,72	48,26	10,83	46,90	10,20	44,93	9,64	43,00	8,97	39,09	7,74
	9.0	7.9	50,95	11,09	49,37	10,41	46,90	9,37	44,93	8,73	43,00	8,19	39,09	7,28
	11.0	9.8	52,30	10,72	50,81	10,03	46,90	8,70	44,93	8,16	43,00	7,69	39,09	6,89
	13.0	11.8	53,46	10,26	50,81	9,32	46,90	8,08	44,93	7,67	43,00	7,27	39,09	6,49
	15.0	13.7	54,73	9,79	50,81	8,61	46,90	7,67	44,93	7,25	43,00	6,88	39,09	6,15
	18.0	16,6	54,73	8,56	50,81	7,74	46,90	7,10	44,93	6,71	43,00	6,33	39,09	5,63
	20.0	19,6	54,73	7,70	50,81	7,08	46,90	6,47	44,93	6,15	43,00	5,77	39,09	5,13
	23.0	22,4	54,73	6,98	50,81	6,42	46,90	5,88	44,93	5,63	43,00	5,24	39,09	4,60
	26.0	25,3	54,73	6,33	50,81	5,80	46,90	5,17	44,93	4,87	43,00	4,59	39,09	4,04
	30.0	28,1	54,73	5,74	50,81	5,22	46,90	4,55	44,93	4,21	43,00	4,01	39,09	3,54
60%	-29.8	-30.0	27,04	9,70	26,65	10,06	25,65	9,51	25,26	9,44	24,84	9,36	23,74	9,08
	-25.0	-25.4	27,76	10,16	27,32	10,49	26,55	10,19	26,14	10,02	25,72	9,83	24,84	9,44
	-19.8	-20.0	28,37	10,59	27,92	10,89	27,32	10,85	26,90	10,57	26,47	10,27	25,58	9,65
	-18.8	-19.0	28,48	10,66	28,02	10,95	27,32	10,67	26,90	10,36	26,47	10,08	25,58	9,45
	-16.7	-17.0	28,68	10,79	28,13	10,84	27,32	10,43	26,90	10,11	26,47	9,77	25,58	9,11
	-13.7	-15.0	28,88	10,98	28,13	10,66	27,32	10,22	26,90	9,88	26,47	9,52	25,58	8,82
	-11.8	-13.0	28,91	10,72	28,13	10,37	27,32	9,82	26,90	9,52	26,47	9,17	25,58	8,45
	-9.8	-11.0	28,91	10,44	28,13	9,99	27,32	9,37	26,90	9,06	26,47	8,73	25,58	8,12
	-9.5	-10.0	28,91	10,11	28,13	9,66	27,32	8,97	26,90	8,69	26,47	8,34	25,58	7,82
	-8.5	-9.1	28,91	9,83	28,13	9,33	27,32	8,64	26,90	8,35	26,47	8,06	25,58	7,66
	-7.0	-7.6	28,91	9,52	28,13	9,00	27,32	8,27	26,90	8,02	26,47	7,80	25,58	7,40
	-5.0	-5.6	28,39	9,02	27,62	8,49	26,84	7,79	26,42	7,58	26,00	7,35	25,14	6,96
	-3.0	-3.7	29,24	8,77	28,44	8,18	27,61	7,58	27,19	7,37	26,76	7,13	25,84	6,77
	0.0	-0.7	31,02	8,78	30,11	8,27	29,19	7,86	28,69	7,60	28,20	7,33	27,16	6,90
	3.0	2.2	34,49	8,87	33,43	8,42	32,33	7,98	31,75	7,74	31,16	7,47	29,54	6,96
	5.0	4.1	37,28	9,05	36,09	8,56	34,42	7,94	33,67	7,63	33,33	7,47	32,65	7,29
	7.0	6.0	41,81	9,56	41,00	9,10	39,48	8,17	37,81	7,80	36,15	7,45	35,23	7,23
	9.0	7.9	43,15	9,08	42,32	8,45	39,48	7,72	37,81	7,37	36,15	6,99	35,23	6,76
	11.0	9.8	44,49	8,71	42,32	7,91	39,48	7,30	40,66	7,48	36,15	6,63	35,23	6,39
	13.0	11.8	45,82	8,26	42,32	7,45	42,47	7,44	40,66	7,05	36,15	6,24	35,23	6,02
	15.0	13.7	45,82	7,77	42,32	7,10	42,47	6,97	40,66	6,63	36,15	5,88	35,23	5,69
	18.0	16,6	45,82	7,19	42,32	6,49	42,47	6,41	40,66	6,10	36,15	5,40	35,23	5,21
	20.0	19,6	45,82	6,56	42,32	5,96	42,47	5,85	40,66	5,59	36,15	4,88	35,23	4,71
	23.0	22,4	49,72	6,46	42,32	5,43	42,47	5,33	40,66	5,00	36,15	4,39	35,23	4,19
	26.0	25,3	49,72	5,67	42,32	4,70	42,47	4,62	40,66	4,38	36,15	3,86	35,23	3,70
	30.0	28,1	49,72	4,99	42,32	4,07	42,47	3,99	40,66	3,83	36,15	3,40	35,23	3,27

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
50%	-29.8	-30.0	22,82	9,15	22,19	8,99	21,55	8,80	21,21	8,71	20,86	8,56	20,15	8,27
	-25.0	-25.4	23,33	9,47	22,68	9,16	22,02	8,84	21,66	8,67	21,31	8,47	20,57	8,10
	-19.8	-20.0	23,80	9,77	23,13	9,33	22,44	8,86	22,08	8,61	21,72	8,36	20,96	7,91
	-18.8	-19.0	23,80	9,61	23,13	9,15	22,44	8,68	22,08	8,43	21,72	8,17	20,96	7,80
	-16.7	-17.0	23,80	9,38	23,13	8,92	22,44	8,41	22,08	8,10	21,72	7,85	20,96	7,55
	-13.7	-15.0	23,80	9,21	23,13	8,70	22,44	8,14	22,08	7,83	21,72	7,63	20,96	7,32
	-11.8	-13.0	23,80	8,86	23,13	8,37	22,44	7,78	22,08	7,55	21,72	7,33	20,96	7,03
	-9.8	-11.0	23,80	8,43	23,13	7,93	22,44	7,49	22,08	7,25	21,72	7,03	20,96	6,71
	-9.5	-10.0	23,80	8,08	23,13	7,56	22,44	7,20	22,08	7,02	21,72	6,85	20,96	6,52
	-8.5	-9.1	23,80	7,77	23,13	7,31	22,44	7,02	22,08	6,87	21,72	6,71	20,96	6,40
	-7.0	-7.6	23,80	7,44	23,13	7,08	22,44	6,80	22,08	6,64	21,72	6,49	20,96	6,20
	-5.0	-5.6	23,37	7,02	22,73	6,66	22,06	6,37	21,71	6,22	21,35	6,10	20,61	5,88
	-3.0	-3.7	24,06	6,83	23,38	6,47	22,68	6,19	22,32	6,05	21,95	5,95	21,17	5,77
	0.0	-0.7	25,84	6,85	25,09	6,46	24,32	6,13	23,91	6,02	23,49	5,92	22,63	5,73
	3.0	2.2	28,74	6,99	27,86	6,61	26,94	6,31	26,46	6,18	25,97	6,06	24,62	5,78
	5.0	4.1	31,07	7,05	30,07	6,68	28,68	6,33	28,27	6,27	27,77	6,17	25,69	5,57
	7.0	6.0	34,84	7,10	33,38	6,80	30,83	6,27	29,53	5,99	28,26	5,73	25,69	5,23
	9.0	7.9	35,96	6,92	33,38	6,38	30,83	5,84	29,53	5,60	28,26	5,33	25,69	4,82
	11.0	9.8	35,97	6,53	33,38	6,03	30,83	5,54	29,53	5,28	28,26	5,04	25,69	4,58
	13.0	11.8	35,97	6,15	33,38	5,69	30,83	5,21	29,53	4,97	28,26	4,76	25,69	4,31
	15.0	13.7	35,97	5,83	33,38	5,35	30,83	4,92	29,53	4,71	28,26	4,52	25,69	4,10
	18.0	16.6	35,97	5,31	33,38	4,90	30,83	4,49	29,53	4,28	28,26	4,09	25,69	3,73
	20.0	19.6	35,97	4,84	33,38	4,43	30,83	4,05	29,53	3,86	28,26	3,68	25,69	3,34
	23.0	22.4	35,97	4,36	33,38	3,96	30,83	3,61	29,53	3,43	28,26	3,25	25,69	2,94
	26.0	25.3	35,97	3,80	33,38	3,49	30,83	3,17	29,53	3,00	28,26	2,85	25,69	2,58
	30.0	28,1	35,97	3,32	33,38	3,07	30,83	2,79	29,53	2,62	28,26	2,50	25,69	2,27

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

Tabella di capacità

Sistema VRF Serie IV8-670WV2RN1E(PRO)

Tabella della capacità di riscaldamento

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	-29.8	-30.0	52,83	17,62	51,81	18,23	50,80	18,84	50,29	19,13	49,78	19,47	48,77	20,07
	-25.0	-25.4	52,83	17,91	51,81	18,45	50,80	18,97	50,29	19,23	49,78	19,50	48,77	20,03
	-19.8	-20.0	52,83	18,21	51,81	18,67	50,80	19,11	50,29	19,32	49,78	19,54	48,77	20,00
	-18.8	-19.0	52,83	18,23	51,81	18,65	50,80	19,10	50,29	19,32	49,78	19,53	48,77	19,97
	-16.7	-17.0	52,83	18,21	51,81	18,64	50,80	19,04	50,29	19,27	49,78	19,47	49,16	20,06
	-13.7	-15.0	52,83	18,28	52,21	18,85	51,30	19,29	50,84	19,50	50,39	19,74	49,47	20,19
	-11.8	-13.0	53,47	18,42	52,55	18,82	52,45	19,58	52,03	19,80	51,61	20,05	50,77	20,53
	-9.8	-11.0	54,77	18,72	53,91	19,17	53,05	19,67	52,62	19,87	52,19	20,10	51,32	20,60
	-9.5	-10.0	55,08	18,67	54,21	19,13	53,34	19,56	52,90	19,81	52,47	20,03	51,59	20,48
	-8.5	-9.1	55,36	18,70	54,48	19,17	53,59	19,62	53,15	19,85	52,71	20,07	51,82	20,51
	-7.0	-7.6	55,79	18,75	54,90	19,18	54,00	19,62	53,55	19,83	53,10	20,04	52,20	20,52
	-5.0	-5.6	55,42	18,43	54,51	18,86	53,61	19,27	53,15	19,51	52,70	19,74	51,78	20,14
	-3.0	-3.7	57,43	18,69	56,49	19,12	55,55	19,55	55,08	19,77	54,60	19,96	53,65	20,41
	0.0	-0.7	62,30	19,56	61,28	20,00	60,26	20,47	59,75	20,70	59,24	20,91	58,21	21,37
	3.0	2.2	69,87	21,22	68,75	21,70	67,62	22,21	67,05	22,46	66,48	22,68	65,34	23,19
	5.0	4.1	76,03	22,58	74,82	23,13	73,61	23,64	73,01	23,88	72,40	24,17	71,17	24,70
	7.0	6.0	86,89	25,27	85,22	25,77	83,55	26,27	82,71	26,51	81,88	26,78	80,21	26,61
	9.0	7.9	89,67	25,55	87,95	26,07	86,22	26,57	85,36	26,81	84,50	27,08	81,26	25,70
	11.0	9.8	92,45	25,83	90,68	26,33	88,90	26,85	88,01	27,13	87,12	27,00	81,26	24,47
	13.0	11.8	95,23	26,04	93,40	26,60	91,57	27,13	90,66	27,21	89,37	26,34	81,26	22,90
	15.0	13.7	98,01	26,26	96,13	26,86	94,24	27,40	93,30	26,75	89,37	25,13	81,26	21,39
	18.0	16,6	102,18	26,93	100,22	27,50	97,50	25,94	93,46	23,89	89,37	21,93	81,26	18,22
	20.0	19,6	106,36	27,31	104,31	27,07	97,50	24,43	93,46	22,43	89,37	20,45	81,26	16,89
	23.0	22,4	110,53	27,70	105,63	25,91	97,50	22,42	93,46	20,49	89,37	18,71	81,26	15,61
	26.0	25,3	110,53	26,24	105,63	23,76	97,50	20,08	93,46	18,31	89,37	16,68	81,26	14,11
	30.0	28,1	113,92	25,63	105,63	21,78	97,50	17,98	93,46	16,36	89,37	14,87	81,26	12,76
120%	-29.8	-30.0	50,51	17,26	49,54	17,89	48,56	18,48	48,08	18,81	47,59	19,05	46,62	19,67
	-25.0	-25.4	50,51	17,56	49,54	18,08	48,56	18,59	48,08	18,87	47,59	19,10	46,62	19,63
	-19.8	-20.0	50,51	17,86	49,54	18,28	48,56	18,71	48,08	18,94	47,59	19,16	46,62	19,59
	-18.8	-19.0	50,51	17,85	49,54	18,28	48,56	18,69	48,08	18,90	47,59	19,11	46,62	19,55
	-16.7	-17.0	50,51	17,86	49,54	18,26	48,98	18,84	48,55	19,05	48,11	19,25	47,24	19,71
	-13.7	-15.0	51,06	18,13	50,17	18,56	50,03	19,28	49,63	19,48	49,23	19,74	48,44	20,25
	-11.8	-13.0	52,24	18,45	51,43	18,91	50,62	19,35	50,21	19,61	49,80	19,84	48,98	20,31
	-9.8	-11.0	52,85	18,53	52,01	18,99	51,18	19,42	50,76	19,65	50,34	19,88	49,50	20,34
	-9.5	-10.0	53,14	18,45	52,29	18,93	51,45	19,35	51,02	19,57	50,59	19,80	49,74	20,26
	-8.5	-9.1	53,39	18,50	52,54	18,96	51,68	19,38	51,25	19,60	50,82	19,82	49,96	20,28
	-7.0	-7.6	53,80	18,52	52,93	18,98	52,06	19,41	51,62	19,62	51,18	19,84	50,30	20,29
	-5.0	-5.6	53,40	18,24	52,52	18,66	51,64	19,07	51,20	19,30	50,76	19,51	49,87	19,93
	-3.0	-3.7	55,34	18,51	54,43	18,93	53,52	19,35	53,06	19,55	52,60	19,77	51,68	20,19
	0.0	-0.7	60,04	19,38	59,06	19,84	58,07	20,28	57,57	20,51	57,07	20,71	56,07	21,17
	3.0	2.2	67,37	21,08	66,28	21,59	65,19	22,04	64,64	22,28	64,09	22,52	62,53	22,30
	5.0	4.1	73,35	22,48	72,18	23,00	71,00	23,53	70,41	23,79	69,82	24,03	67,50	22,97
	7.0	6.0	83,07	24,96	81,47	25,46	80,49	26,17	79,77	26,41	78,88	26,19	75,00	24,33
	9.0	7.9	85,73	25,26	84,08	25,78	83,11	26,50	82,27	26,50	80,78	25,65	75,00	22,83
	11.0	9.8	88,39	25,55	86,69	26,08	85,70	26,75	84,14	25,85	82,51	25,00	75,00	21,36
	13.0	11.8	91,04	25,82	89,96	26,53	87,54	26,15	86,26	25,21	82,51	23,67	75,00	19,88
	15.0	13.7	93,70	26,12	92,63	26,85	90,00	25,61	86,26	24,00	82,51	22,12	75,00	18,48
	18.0	16,6	97,69	26,76	95,81	25,49	90,00	22,27	86,26	20,53	82,51	18,85	75,00	15,98
	20.0	19,6	101,68	26,38	97,50	24,53	90,00	20,82	86,26	19,06	82,51	17,49	75,00	14,73
	23.0	22,4	105,01	25,77	97,50	22,46	90,00	19,06	86,26	17,47	82,51	16,08	75,00	13,47
	26.0	25,3	105,01	23,54	97,50	20,15	90,00	16,97	86,26	15,71	82,51	14,55	75,00	12,20
	30.0	28,1	105,01	21,51	97,50	18,07	90,00	15,10	86,26	14,13	82,51	13,17	75,00	11,05

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
110%	-29.8	-30.0	47,71	16,77	46,79	17,39	45,87	17,94	45,41	18,27	44,96	18,50	44,04	19,08
	-25.0	-25.4	47,71	17,04	46,79	17,56	45,87	18,06	45,41	18,31	44,96	18,53	44,04	19,03
	-19.8	-20.0	47,71	17,32	46,79	17,74	45,87	18,18	45,41	18,35	45,32	18,71	44,51	19,18
	-18.8	-19.0	47,71	17,34	46,79	17,73	46,28	18,30	45,87	18,51	45,46	18,76	44,65	19,21
	-16.7	-17.0	48,24	17,51	47,41	17,96	47,29	18,66	46,92	18,89	46,55	19,14	45,81	19,63
	-13.7	-15.0	49,39	18,02	48,62	18,47	47,86	18,95	47,47	19,17	47,09	19,41	46,32	19,88
	-11.8	-13.0	49,97	18,11	49,18	18,57	48,39	19,03	48,00	19,24	47,60	19,49	46,81	19,94
	-9.8	-11.0	50,51	18,22	49,70	18,65	48,90	19,08	48,49	19,30	48,09	19,51	47,27	19,97
	-9.5	-10.0	50,77	18,16	49,96	18,57	49,14	19,00	48,73	19,22	48,32	19,43	47,49	19,89
	-8.5	-9.1	51,00	18,20	50,18	18,60	49,35	19,03	48,94	19,25	48,52	19,46	47,69	19,91
	-7.0	-7.6	51,37	18,23	50,53	18,63	49,69	19,07	49,27	19,27	48,85	19,48	48,00	19,90
	-5.0	-5.6	50,95	17,94	50,10	18,34	49,26	18,73	48,83	18,95	48,41	19,13	47,55	19,56
	-3.0	-3.7	52,80	18,21	51,92	18,61	51,04	19,02	50,60	19,21	50,16	19,41	49,27	19,81
	0.0	-0.7	57,27	19,14	56,33	19,54	55,38	19,97	54,90	20,19	54,42	20,40	52,91	20,13
	3.0	2.2	64,31	20,83	63,27	21,32	62,21	21,78	61,68	22,01	60,88	21,64	58,67	20,48
	5.0	4.1	70,08	22,30	68,95	22,76	67,81	23,30	67,00	23,05	65,80	22,28	63,28	20,72
	7.0	6.0	79,31	24,73	77,92	25,26	76,42	25,43	75,31	24,68	73,94	23,90	68,76	21,08
	9.0	7.9	81,88	25,06	80,45	25,64	78,52	24,89	77,09	24,10	75,63	23,26	68,76	19,69
	11.0	9.8	84,45	25,42	82,91	25,79	80,28	24,25	79,07	23,50	75,63	21,79	68,76	18,35
	13.0	11.8	87,05	25,73	85,06	25,27	82,51	23,72	79,07	22,00	75,63	20,26	68,76	16,99
	15.0	13.7	89,58	25,88	86,81	24,60	82,51	22,20	79,07	20,49	75,63	18,86	68,76	15,95
	18.0	16,6	92,28	24,29	89,37	22,00	82,51	18,88	79,07	17,37	75,63	16,22	68,76	14,00
	20.0	19,6	96,04	23,73	89,37	20,50	82,51	17,45	79,07	16,07	75,63	15,01	68,76	12,83
	23.0	22,4	96,26	21,87	89,37	18,84	82,51	16,14	79,07	14,81	75,63	13,80	68,76	11,57
	26.0	25,3	96,26	19,61	89,37	16,77	82,51	14,57	79,07	13,56	75,63	12,51	68,76	10,33
	30.0	28,1	96,26	17,57	89,37	14,92	82,51	13,15	79,07	12,41	75,63	11,35	68,76	9,22
100%	-29.8	-30.0	47,42	17,27	46,51	17,80	45,60	18,37	45,14	18,65	44,69	18,94	43,78	19,48
	-25.0	-25.4	47,42	17,49	46,51	17,97	45,60	18,47	45,14	18,72	44,69	18,98	43,78	19,46
	-19.8	-20.0	47,42	17,72	46,51	18,15	45,60	18,57	45,14	18,78	45,04	19,16	44,24	19,65
	-18.8	-19.0	47,42	17,74	46,51	18,15	46,00	18,74	45,60	18,99	45,19	19,20	44,38	19,68
	-16.7	-17.0	47,95	17,95	47,12	18,37	47,00	19,10	46,63	19,36	46,27	19,61	45,53	20,11
	-13.7	-15.0	49,08	18,45	48,33	18,93	47,57	19,40	47,19	19,64	46,81	19,89	46,05	20,38
	-11.8	-13.0	49,66	18,59	48,88	19,05	48,10	19,49	47,71	19,71	47,32	19,96	46,54	20,44
	-9.8	-11.0	50,21	18,69	49,41	19,13	48,60	19,58	48,20	19,81	47,80	20,04	47,00	20,49
	-9.5	-10.0	50,46	18,64	49,66	19,05	48,85	19,48	48,44	19,73	48,03	19,95	47,22	20,40
	-8.5	-9.1	50,69	18,68	49,88	19,10	49,06	19,55	48,64	19,76	48,23	19,99	47,41	20,42
	-7.0	-7.6	51,05	18,72	50,23	19,13	49,39	19,57	48,98	19,79	48,56	20,00	47,71	20,43
	-5.0	-5.6	50,62	18,46	49,79	18,86	48,95	19,29	48,53	19,50	48,11	19,69	46,90	19,50
	-3.0	-3.7	52,45	18,78	51,58	19,18	50,71	19,57	50,27	19,79	49,83	20,02	48,22	19,18
	0.0	-0.7	56,90	19,75	55,96	20,20	55,01	20,63	54,44	20,61	53,53	20,35	51,63	18,78
	3.0	2.2	63,89	21,58	62,85	22,03	61,46	21,85	60,41	21,65	59,34	20,77	57,08	18,79
	5.0	4.1	69,60	23,06	68,48	23,58	66,38	22,52	65,19	22,09	63,07	20,73	60,91	18,74
	7.0	6.0	78,78	25,67	77,17	25,41	75,00	24,27	71,88	22,83	68,76	21,15	62,51	17,95
	9.0	7.9	81,34	26,07	78,95	24,86	75,00	23,02	71,88	21,39	68,76	19,76	62,51	16,68
	11.0	9.8	83,63	25,61	81,26	24,39	75,00	21,52	71,88	19,96	68,76	18,42	62,51	15,77
	13.0	11.8	85,49	24,95	81,26	23,13	75,00	19,99	71,88	18,51	68,76	17,01	62,51	14,74
	15.0	13.7	87,51	24,36	81,26	21,60	75,00	18,62	71,88	17,21	68,76	16,00	62,51	13,76
	18.0	16,6	87,51	21,12	81,26	18,31	75,00	15,98	71,88	14,98	68,76	14,00	62,51	12,14
	20.0	19,6	87,51	19,73	81,26	16,89	75,00	14,75	71,88	13,76	68,76	12,77	62,51	10,92
	23.0	22,4	87,51	18,04	81,26	15,70	75,00	13,54	71,88	12,51	68,76	11,52	62,51	9,93
	26.0	25,3	87,51	16,10	81,26	14,17	75,00	12,30	71,88	11,27	68,76	10,29	62,51	9,02
	30.0	28,1	87,51	14,36	81,26	12,79	75,00	11,17	71,88	10,15	68,76	9,19	62,51	8,19

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
90%	-29.8	-30.0	42,68	16,05	41,86	16,56	41,04	17,10	40,63	17,34	40,22	17,66	39,40	18,16
	-25.0	-25.4	42,68	16,28	41,86	16,74	41,04	17,20	40,63	17,42	40,22	17,68	39,40	18,12
	-19.8	-20.0	43,31	16,76	43,27	17,50	42,61	17,97	42,28	18,22	41,95	18,46	41,29	18,95
	-18.8	-19.0	44,21	17,13	43,54	17,59	42,87	18,08	42,53	18,31	42,20	18,55	41,52	19,05
	-16.7	-17.0	44,74	17,32	44,05	17,78	43,35	18,24	43,01	18,48	42,66	18,72	41,96	19,18
	-13.7	-15.0	45,24	17,63	44,53	18,04	43,81	18,49	43,46	18,73	43,10	18,95	42,39	19,41
	-11.8	-13.0	45,72	17,73	44,98	18,16	44,25	18,58	43,88	18,80	43,52	19,01	42,78	19,48
	-9.8	-11.0	46,15	17,83	45,40	18,25	44,65	18,67	44,28	18,87	43,90	19,10	42,94	19,03
	-9.5	-10.0	46,36	17,77	45,60	18,17	44,84	18,61	44,46	18,82	44,08	19,02	42,94	18,50
	-8.5	-9.1	46,54	17,83	45,77	18,23	45,01	18,65	44,62	18,85	44,24	19,07	42,94	18,16
	-7.0	-7.6	46,82	17,88	46,05	18,28	45,27	18,69	44,88	18,91	44,44	18,96	42,94	17,57
	-5.0	-5.6	46,36	17,63	45,59	18,02	44,81	18,38	44,37	18,49	43,67	18,13	42,21	16,66
	-3.0	-3.7	48,03	17,95	47,22	18,31	46,37	18,60	45,66	18,24	44,92	17,83	43,40	16,31
	0.0	-0.7	52,13	18,92	51,25	19,34	49,79	18,95	49,00	18,23	48,18	17,46	46,47	15,90
	3.0	2.2	58,62	20,76	57,13	20,47	55,31	19,19	54,37	18,36	53,40	17,54	51,37	15,80
	5.0	4.1	63,77	21,86	61,80	21,16	59,74	19,44	58,67	18,52	56,77	17,38	54,82	15,82
	7.0	6.0	72,49	23,73	69,45	22,32	67,50	20,53	64,70	19,09	61,88	17,67	56,26	15,30
	9.0	7.9	73,32	22,94	71,05	21,41	67,50	19,19	64,70	17,77	61,88	16,51	56,26	14,30
	11.0	9.8	75,27	22,42	73,13	20,58	67,50	17,82	64,70	16,57	61,88	15,54	56,26	13,46
	13.0	11.8	76,94	21,34	73,13	19,11	67,50	16,57	64,70	15,54	61,88	14,61	56,26	12,51
	15.0	13.7	78,76	20,38	73,13	17,77	67,50	15,54	64,70	14,61	61,88	13,66	56,26	11,53
	18.0	16,6	78,76	17,19	73,13	15,34	67,50	13,60	64,70	12,77	61,88	11,96	56,26	10,52
	20.0	19,6	78,76	16,02	73,13	14,08	67,50	12,44	64,70	11,49	61,88	10,72	56,26	9,62
	23.0	22,4	78,76	14,81	73,13	12,86	67,50	11,22	64,70	10,33	61,88	9,79	56,26	8,76
	26.0	25,3	78,76	13,41	73,13	11,60	67,50	10,05	64,70	9,35	61,88	8,86	56,26	7,85
	30.0	28,1	78,76	12,15	73,13	10,47	67,50	9,00	64,70	8,46	61,88	8,02	56,26	7,03
80%	-29.8	-30.0	37,94	14,85	37,21	15,34	36,48	15,82	36,12	16,06	35,75	16,32	35,02	15,86
	-25.0	-25.4	38,40	15,25	37,75	15,72	37,73	16,45	37,45	16,72	37,17	17,00	36,16	16,83
	-19.8	-20.0	40,14	16,17	39,52	16,62	38,90	17,06	38,59	17,30	38,29	17,54	37,67	18,01
	-18.8	-19.0	40,37	16,28	39,73	16,71	39,10	17,16	38,79	17,37	38,48	17,60	37,85	18,09
	-16.7	-17.0	40,78	16,46	40,14	16,88	39,49	17,32	39,17	17,52	38,85	17,73	38,17	18,13
	-13.7	-15.0	41,17	16,73	40,51	17,15	39,85	17,57	39,51	17,78	39,18	17,99	38,17	17,80
	-11.8	-13.0	41,54	16,85	40,86	17,25	40,18	17,65	39,84	17,87	39,50	18,06	38,17	17,30
	-9.8	-11.0	41,88	16,95	41,19	17,33	40,49	17,72	40,15	17,94	39,50	17,61	38,17	16,67
	-9.5	-10.0	42,04	16,90	41,34	17,29	40,64	17,68	40,15	17,48	39,50	17,05	38,17	16,06
	-8.5	-9.1	42,18	16,96	41,48	17,35	40,77	17,71	40,15	17,13	39,50	16,61	38,17	15,58
	-7.0	-7.6	42,41	17,03	41,70	17,38	40,77	17,27	40,15	16,63	39,50	16,11	38,17	15,01
	-5.0	-5.6	41,94	16,77	41,22	17,14	40,05	16,45	39,44	15,84	38,82	15,27	37,52	14,16
	-3.0	-3.7	43,43	17,09	42,45	16,92	41,22	16,19	40,58	15,54	39,93	14,94	38,57	13,70
	0.0	-0.7	46,95	17,54	45,63	17,01	44,26	15,76	43,55	15,12	42,83	14,47	41,31	13,25
	3.0	2.2	52,32	18,55	50,78	17,21	49,17	15,79	48,33	15,11	47,47	14,40	45,66	13,43
	5.0	4.1	56,68	18,87	54,94	17,43	53,11	15,96	52,16	15,20	50,46	14,47	48,73	13,55
	7.0	6.0	64,43	20,10	61,74	18,27	60,00	16,75	57,51	15,80	55,00	14,81	50,00	13,01
	9.0	7.9	65,17	18,97	63,16	17,43	60,01	15,80	57,51	14,81	55,00	13,80	50,00	11,77
	11.0	9.8	66,91	18,19	65,00	16,67	60,01	14,81	57,51	13,93	55,00	13,01	50,00	11,03
	13.0	11.8	68,39	17,23	65,00	15,62	60,01	13,87	57,51	12,94	55,00	12,06	50,00	10,35
	15.0	13.7	70,00	16,40	65,00	14,71	60,01	12,90	57,51	11,97	55,00	11,09	50,00	9,85
	18.0	16,6	70,00	14,28	65,00	12,83	60,01	11,36	57,51	10,72	55,00	10,22	50,00	9,08
	20.0	19,6	70,00	13,14	65,00	11,57	60,01	10,29	57,51	9,82	55,00	9,35	50,00	8,38
	23.0	22,4	70,00	11,93	65,00	10,35	60,01	9,37	57,51	8,92	55,00	8,48	50,00	7,66
	26.0	25,3	70,00	10,66	65,00	9,36	60,01	8,46	57,51	8,05	55,00	7,61	50,00	6,64
	30.0	28,1	70,00	9,52	65,00	8,47	60,01	7,64	57,51	7,26	55,00	6,82	50,00	5,75

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
70%	-29.8	-30.0	33,60	13,80	33,54	14,45	33,06	15,05	32,73	15,11	31,57	14,32	30,64	13,77
	-25.0	-25.4	35,12	14,66	34,59	15,11	34,06	15,61	33,76	15,76	33,23	15,54	32,05	14,90
	-19.8	-20.0	36,09	15,31	35,52	15,73	34,95	16,13	34,66	16,36	34,38	16,57	33,40	16,05
	-18.8	-19.0	36,25	15,39	35,68	15,79	35,10	16,22	34,81	16,44	34,52	16,64	33,40	15,76
	-16.7	-17.0	36,57	15,59	35,97	15,95	35,38	16,37	35,09	16,59	34,57	16,29	33,40	15,32
	-13.7	-15.0	36,86	15,85	36,26	16,23	35,65	16,63	35,13	16,33	34,57	16,03	33,40	14,96
	-11.8	-13.0	37,14	15,95	36,53	16,31	35,67	16,19	35,13	15,90	34,57	15,54	33,40	14,43
	-9.8	-11.0	37,40	16,04	36,73	16,27	35,67	15,78	35,13	15,38	34,57	14,86	33,40	13,75
	-9.5	-10.0	37,53	16,00	36,73	15,86	35,67	15,26	35,13	14,85	34,57	14,32	33,40	13,19
	-8.5	-9.1	37,64	16,07	36,73	15,55	35,67	14,84	35,13	14,41	34,57	13,85	33,40	12,67
	-7.0	-7.6	37,76	15,94	36,73	15,13	35,67	14,37	35,13	13,91	34,57	13,32	33,40	12,16
	-5.0	-5.6	37,08	15,22	36,08	14,39	35,04	13,58	34,51	13,12	33,96	12,54	32,83	11,48
	-3.0	-3.7	38,18	15,01	37,14	14,13	36,07	13,18	35,51	12,66	34,94	12,15	33,75	11,16
	0.0	-0.7	41,08	14,77	39,93	13,76	38,73	12,72	38,11	12,24	37,47	11,88	36,14	11,11
	3.0	2.2	45,79	14,89	44,43	13,79	43,02	12,84	42,29	12,45	41,54	12,08	39,96	11,31
	5.0	4.1	49,60	15,04	48,07	13,88	46,47	13,05	45,63	12,70	44,15	12,03	42,64	11,25
	7.0	6.0	56,38	15,93	54,02	14,73	52,50	13,87	50,30	13,11	48,13	12,19	43,76	10,52
	9.0	7.9	57,03	15,08	55,26	14,15	52,50	12,74	50,30	11,87	48,13	11,13	43,76	9,90
	11.0	9.8	58,54	14,58	56,88	13,64	52,50	11,83	50,30	11,09	48,13	10,46	43,76	9,37
	13.0	11.8	59,84	13,95	56,88	12,67	52,50	10,99	50,30	10,43	48,13	9,89	43,76	8,83
	15.0	13.7	61,26	13,31	56,88	11,70	52,50	10,43	50,30	9,86	48,13	9,35	43,76	8,36
	18.0	16,6	61,26	11,64	56,88	10,53	52,50	9,65	50,30	9,12	48,13	8,60	43,76	7,66
	20.0	19,6	61,26	10,47	56,88	9,62	52,50	8,80	50,30	8,36	48,13	7,85	43,76	6,98
	23.0	22,4	61,26	9,49	56,88	8,73	52,50	7,99	50,30	7,65	48,13	7,13	43,76	6,26
	26.0	25,3	61,26	8,60	56,88	7,88	52,50	7,03	50,30	6,62	48,13	6,24	43,76	5,49
	30.0	28,1	61,26	7,80	56,88	7,10	52,50	6,19	50,30	5,73	48,13	5,45	43,76	4,82
60%	-29.8	-30.0	30,27	13,19	29,83	13,68	28,71	12,93	28,28	12,84	27,81	12,73	26,57	12,35
	-25.0	-25.4	31,07	13,81	30,58	14,26	29,72	13,85	29,26	13,62	28,79	13,37	27,81	12,84
	-19.8	-20.0	31,76	14,40	31,25	14,81	30,58	14,75	30,11	14,37	29,63	13,97	28,63	13,12
	-18.8	-19.0	31,88	14,49	31,37	14,89	30,58	14,51	30,11	14,09	29,63	13,70	28,63	12,85
	-16.7	-17.0	32,11	14,67	31,49	14,74	30,58	14,18	30,11	13,75	29,63	13,29	28,63	12,39
	-13.7	-15.0	32,33	14,93	31,49	14,49	30,58	13,90	30,11	13,44	29,63	12,95	28,63	11,99
	-11.8	-13.0	32,36	14,58	31,49	14,10	30,58	13,35	30,11	12,94	29,63	12,47	28,63	11,49
	-9.8	-11.0	32,36	14,20	31,49	13,58	30,58	12,74	30,11	12,32	29,63	11,87	28,63	11,04
	-9.5	-10.0	32,36	13,74	31,49	13,13	30,58	12,19	30,11	11,82	29,63	11,34	28,63	10,63
	-8.5	-9.1	32,36	13,36	31,49	12,69	30,58	11,75	30,11	11,35	29,63	10,96	28,63	10,41
	-7.0	-7.6	32,36	12,94	31,49	12,24	30,58	11,25	30,11	10,91	29,63	10,60	28,63	10,06
	-5.0	-5.6	31,78	12,26	30,92	11,54	30,04	10,59	29,58	10,30	29,11	10,00	28,14	9,47
	-3.0	-3.7	32,73	11,92	31,84	11,12	30,91	10,31	30,44	10,02	29,95	9,69	28,93	9,20
	0.0	-0.7	34,72	11,94	33,71	11,25	32,67	10,69	32,12	10,34	31,57	9,97	30,40	9,38
	3.0	2.2	38,61	12,06	37,42	11,45	36,19	10,85	35,54	10,53	34,88	10,15	33,07	9,47
	5.0	4.1	41,73	12,31	40,40	11,64	38,53	10,79	37,69	10,37	37,31	10,16	36,55	9,91
	7.0	6.0	46,80	13,00	45,90	12,37	44,19	11,11	42,32	10,61	40,47	10,13	39,44	9,83
	9.0	7.9	48,30	12,34	47,37	11,49	44,19	10,49	42,32	10,02	40,47	9,51	39,44	9,19
	11.0	9.8	49,80	11,84	47,37	10,76	44,19	9,93	45,51	10,17	40,47	9,01	39,44	8,69
	13.0	11.8	51,29	11,23	47,37	10,13	47,54	10,12	45,51	9,58	40,47	8,48	39,44	8,18
	15.0	13.7	51,29	10,57	47,37	9,65	47,54	9,48	45,51	9,02	40,47	8,00	39,44	7,73
	18.0	16,6	51,29	9,78	47,37	8,83	47,54	8,72	45,51	8,29	40,47	7,34	39,44	7,09
	20.0	19,6	51,29	8,92	47,37	8,10	47,54	7,96	45,51	7,60	40,47	6,64	39,44	6,40
	23.0	22,4	55,66	8,78	47,37	7,38	47,54	7,25	45,51	6,80	40,47	5,97	39,44	5,70
	26.0	25,3	55,66	7,71	47,37	6,39	47,54	6,28	45,51	5,95	40,47	5,25	39,44	5,03
	30.0	28,1	55,66	6,78	47,37	5,53	47,54	5,43	45,51	5,21	40,47	4,62	39,44	4,45

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
50%	-29.8	-30.0	25,54	12,44	24,84	12,22	24,12	11,97	23,74	11,84	23,35	11,64	22,56	11,24
	-25.0	-25.4	26,12	12,87	25,39	12,46	24,65	12,02	24,25	11,79	23,85	11,51	23,03	11,01
	-19.8	-20.0	26,64	13,29	25,89	12,68	25,12	12,04	24,72	11,70	24,31	11,36	23,46	10,76
	-18.8	-19.0	26,64	13,06	25,89	12,44	25,12	11,80	24,72	11,46	24,31	11,11	23,46	10,61
	-16.7	-17.0	26,64	12,76	25,89	12,13	25,12	11,43	24,72	11,01	24,31	10,68	23,46	10,26
	-13.7	-15.0	26,64	12,52	25,89	11,83	25,12	11,07	24,72	10,65	24,31	10,37	23,46	9,95
	-11.8	-13.0	26,64	12,04	25,89	11,38	25,12	10,58	24,72	10,26	24,31	9,97	23,46	9,56
	-9.8	-11.0	26,64	11,46	25,89	10,78	25,12	10,19	24,72	9,86	24,31	9,56	23,46	9,13
	-9.5	-10.0	26,64	10,99	25,89	10,28	25,12	9,79	24,72	9,54	24,31	9,31	23,46	8,87
	-8.5	-9.1	26,64	10,57	25,89	9,94	25,12	9,55	24,72	9,34	24,31	9,13	23,46	8,70
	-7.0	-7.6	26,64	10,11	25,89	9,63	25,12	9,24	24,72	9,03	24,31	8,83	23,46	8,43
	-5.0	-5.6	26,16	9,54	25,44	9,05	24,69	8,66	24,30	8,46	23,90	8,29	23,07	8,00
	-3.0	-3.7	26,93	9,29	26,17	8,80	25,39	8,42	24,98	8,22	24,57	8,09	23,70	7,85
	0.0	-0.7	28,93	9,31	28,09	8,78	27,22	8,33	26,77	8,19	26,30	8,05	25,33	7,79
	3.0	2.2	32,17	9,50	31,19	8,99	30,16	8,58	29,62	8,40	29,07	8,24	27,56	7,86
	5.0	4.1	34,78	9,59	33,66	9,08	32,11	8,60	31,64	8,52	31,09	8,39	28,76	7,58
	7.0	6.0	39,00	9,66	37,37	9,24	34,51	8,52	33,06	8,14	31,63	7,79	28,76	7,11
	9.0	7.9	40,25	9,41	37,37	8,67	34,51	7,94	33,06	7,61	31,63	7,25	28,76	6,56
	11.0	9.8	40,26	8,88	37,37	8,20	34,51	7,53	33,06	7,18	31,63	6,85	28,76	6,23
	13.0	11.8	40,26	8,36	37,37	7,74	34,51	7,08	33,06	6,76	31,63	6,47	28,76	5,86
	15.0	13.7	40,26	7,93	37,37	7,28	34,51	6,69	33,06	6,40	31,63	6,14	28,76	5,58
	18.0	16.6	40,26	7,22	37,37	6,66	34,51	6,10	33,06	5,82	31,63	5,56	28,76	5,07
	20.0	19.6	40,26	6,58	37,37	6,02	34,51	5,50	33,06	5,25	31,63	5,00	28,76	4,54
	23.0	22.4	40,26	5,93	37,37	5,38	34,51	4,91	33,06	4,67	31,63	4,42	28,76	4,00
	26.0	25.3	40,26	5,17	37,37	4,74	34,51	4,31	33,06	4,08	31,63	3,88	28,76	3,51
	30.0	28,1	40,26	4,52	37,37	4,17	34,51	3,79	33,06	3,56	31,63	3,40	28,76	3,08

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)