

Tabella di capacità

Sistema VRF Serie IV8-730WV2RN1E(PRO)

Tabella della capacità di raffreddamento

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
130%	-15	59,95	8,77	68,37	9,42	85,33	11,01	94,08	11,30	97,76	11,19	101,87	11,09	104,29	5,92
	-10	59,95	9,80	68,37	10,53	85,33	12,31	94,08	12,63	97,76	12,52	101,87	12,40	104,29	6,62
	-5	59,95	10,85	68,37	11,66	85,33	13,63	94,08	13,99	97,76	13,86	101,87	13,73	104,29	7,32
	-2	59,95	11,49	68,37	12,34	85,33	14,43	94,08	14,81	97,76	14,68	101,87	14,53	104,29	7,75
	0	59,95	11,92	68,37	12,81	85,33	14,98	94,08	15,36	97,76	15,22	101,87	15,08	104,29	8,05
	2	59,95	12,35	68,37	13,27	85,33	15,52	94,08	15,92	97,76	15,78	101,87	15,62	104,29	8,34
	4	59,95	12,79	68,37	13,74	85,33	16,07	94,08	16,48	97,76	16,34	101,87	16,18	104,29	8,63
	6	59,95	13,23	68,37	14,21	85,33	16,61	94,08	17,05	97,76	16,90	101,87	16,73	104,29	8,93
	8	59,95	13,66	68,37	14,68	85,33	17,17	94,08	17,62	97,76	17,45	101,87	17,29	104,29	9,22
	10	59,95	14,11	68,37	15,16	85,33	17,73	94,08	18,19	97,76	18,03	101,87	17,85	104,29	9,53
	12	59,95	14,56	68,37	15,64	85,33	18,28	94,08	18,77	97,76	18,60	101,87	18,41	104,29	9,83
	14	59,95	15,01	68,37	16,12	85,33	18,85	94,08	19,34	97,76	19,17	101,87	18,99	104,29	10,13
	16	59,95	15,46	68,37	16,61	85,33	19,42	94,08	19,93	97,76	19,74	101,87	19,56	104,29	10,44
	18	59,95	15,91	68,37	17,10	85,33	19,99	94,08	20,52	97,76	20,33	101,87	20,13	104,29	10,74
	20	59,95	16,37	68,37	17,60	85,33	20,57	94,08	21,10	97,76	20,92	101,87	20,72	104,29	11,05
	21	59,95	16,60	68,37	17,84	85,33	20,86	94,08	21,41	97,76	21,21	101,87	21,00	104,29	11,21
	23	59,95	17,07	68,37	18,34	85,33	21,44	94,08	22,00	97,76	21,80	101,87	21,59	104,29	11,52
	25	59,95	17,53	68,37	18,84	85,33	22,02	94,08	22,60	97,76	22,39	101,87	22,18	104,29	11,83
	27	59,95	18,00	68,37	19,34	85,33	22,62	94,08	23,21	97,76	22,99	101,87	22,78	104,29	12,15
	29	59,95	18,47	68,37	19,85	85,33	23,21	94,08	23,81	97,76	23,59	101,87	23,37	104,29	12,47
	31	59,95	18,95	68,37	20,36	85,33	23,81	91,62	23,79	96,20	23,82	101,87	23,97	104,29	12,79
	33	59,95	19,43	68,37	20,88	81,04	23,18	85,30	22,71	89,57	22,74	98,10	23,67	104,29	13,12
	35	59,73	19,84	68,26	21,36	75,85	22,24	78,99	21,55	82,94	21,58	90,83	22,46	98,73	12,72
	37	59,73	20,27	68,26	21,83	74,80	22,41	76,94	21,45	80,78	21,48	88,48	22,36	96,17	12,67
	39	59,73	20,72	68,26	22,31	72,06	22,06	75,60	21,54	79,38	21,57	86,94	22,45	94,50	12,72
	41	59,84	21,20	65,42	21,84	70,55	22,06	74,26	21,62	77,98	21,65	85,40	22,53	92,83	12,76
	43	57,41	20,78	62,58	21,34	69,28	22,13	72,93	21,68	76,57	21,71	83,87	22,59	91,16	12,80
	46	54,46	20,12	60,85	21,18	68,01	22,18	71,59	21,73	75,17	21,75	82,33	22,65	89,49	12,83
	48	49,19	18,74	55,75	20,01	62,31	20,95	65,59	20,52	68,87	20,55	75,43	21,39	81,99	12,12
	50	46,19	17,95	52,35	19,17	58,51	20,07	61,59	19,66	64,67	19,69	70,83	20,49	76,98	11,61
	52	43,19	17,12	48,95	18,28	54,71	19,14	57,59	18,75	60,47	18,77	66,22	19,54	71,98	11,07
	55	40,19	16,24	45,55	17,34	50,91	18,16	53,59	17,79	56,26	17,81	61,62	18,54	66,98	10,50
120%	-15	56,25	8,54	64,37	9,21	80,17	10,75	88,38	11,03	95,34	11,34	100,08	11,31	101,97	6,01
	-10	56,25	9,55	64,37	10,30	80,17	12,02	88,38	12,33	95,34	12,68	100,08	12,65	101,97	6,72
	-5	56,25	10,58	64,37	11,40	80,17	13,30	88,38	13,65	95,34	14,05	100,08	14,01	101,97	7,44
	-2	56,25	11,20	64,37	12,07	80,17	14,09	88,38	14,46	95,34	14,87	100,08	14,84	101,97	7,88
	0	56,25	11,62	64,37	12,53	80,17	14,62	88,38	15,00	95,34	15,43	100,08	15,39	101,97	8,18
	2	56,25	12,04	64,37	12,98	80,17	15,15	88,38	15,54	95,34	15,99	100,08	15,95	101,97	8,47
	4	56,25	12,47	64,37	13,44	80,17	15,68	88,38	16,09	95,34	16,55	100,08	16,51	101,97	8,77
	6	56,25	12,89	64,37	13,90	80,17	16,22	88,38	16,64	95,34	17,12	100,08	17,08	101,97	9,07
	8	56,25	13,32	64,37	14,36	80,17	16,76	88,38	17,20	95,34	17,69	100,08	17,65	101,97	9,37
	10	56,25	13,76	64,37	14,83	80,17	17,31	88,38	17,76	95,34	18,26	100,08	18,22	101,97	9,68
	12	56,25	14,19	64,37	15,30	80,17	17,86	88,38	18,32	95,34	18,84	100,08	18,80	101,97	9,98
	14	56,25	14,63	64,37	15,77	80,17	18,40	88,38	18,89	95,34	19,42	100,08	19,38	101,97	10,29
	16	56,25	15,07	64,37	16,25	80,17	18,96	88,38	19,46	95,34	20,01	100,08	19,96	101,97	10,60
	18	56,25	15,52	64,37	16,72	80,17	19,52	88,38	20,03	95,34	20,60	100,08	20,55	101,97	10,91
	20	56,25	15,97	64,37	17,21	80,17	20,08	88,38	20,60	95,34	21,19	100,08	21,15	101,97	11,23
	21	56,25	16,19	64,37	17,45	80,17	20,36	88,38	20,89	95,34	21,49	100,08	21,44	101,97	11,39
	23	56,25	16,64	64,37	17,94	80,17	20,93	88,38	21,48	95,34	22,09	100,08	22,04	101,97	11,70
	25	56,25	17,10	64,37	18,43	80,17	21,51	88,38	22,06	95,34	22,69	100,08	22,64	101,97	12,03
	27	56,25	17,55	64,37	18,92	80,17	22,08	88,38	22,65	95,34	23,30	100,08	23,25	101,97	12,34
	29	56,25	18,01	64,37	19,42	80,17	22,66	88,38	23,25	95,34	23,91	100,08	23,86	101,97	12,67
	31	56,25	18,47	64,37	19,92	80,17	23,24	88,38	23,84	93,63	24,08	100,08	24,47	101,97	13,00
	33	56,25	18,94	64,37	20,42	78,87	23,44	83,02	22,97	87,17	22,99	95,47	23,93	101,97	13,32
	35	56,25	19,41	64,37	20,93	74,58	22,71	76,87	21,79	80,71	21,82	88,40	22,71	96,09	12,86
	37	56,15	19,80	64,15	21,32	73,53	22,89	75,12	21,76	78,23	21,62	85,68	22,50	93,13	12,75
	39	56,15	20,24	64,15	21,78	71,43	22,72	73,21	21,68	76,87	21,71	84,20	22,59	91,52	12,80
	41	56,15	20,68	64,05	22,22	68,68	22,32	71,92	21,75	75,52	21,78	82,71	22,67	89,90	12,85
	43	56,15	21,11	61,31	21,72	67,09	22,27	70,63	21,82	74,16	21,84	81,22	22,74	88,28	12,88
	46	52,99	20,34	58,93	21,31	65,86	22,32	69,33	21,86	72,80	21,89	79,73	22,79	86,66	12,91
	48	47,64	18,86	53,99	20,13	60,34	21,08	63,52	20,65	66,69	20,68	73,05	21,52	79,40	12,19
	50	44,73	18,06	50,70	19,29	56,66	20,19	59,64	19,78	62,63	19,81	68,59	20,62	74,55	11,68
	52	41,83	17,23	47,40	18,39	52,98	19,26	55,77	18,87	58,56	18,89	64,13	19,66	69,71	11,14
	55	38,92	16,34	44,11	17,45	49,30	18,27	51,89	17,90	54,49	17,92	59,68	18,66	64,87	10,57

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
110%	-15	52,46	8,30	59,95	8,94	74,90	10,46	82,28	10,69	89,76	11,12	97,54	11,49	99,55	6,11
	-10	52,46	9,28	59,95	9,99	74,90	11,69	82,28	11,96	89,76	12,43	97,54	12,85	99,55	6,83
	-5	52,46	10,27	59,95	11,06	74,90	12,95	82,28	13,24	89,76	13,77	97,54	14,22	99,55	7,56
	-2	52,46	10,88	59,95	11,72	74,90	13,71	82,28	14,02	89,76	14,58	97,54	15,06	99,55	8,01
	0	52,46	11,29	59,95	12,15	74,90	14,22	82,28	14,54	89,76	15,13	97,54	15,62	99,55	8,31
	2	52,46	11,70	59,95	12,59	74,90	14,74	82,28	15,07	89,76	15,68	97,54	16,19	99,55	8,61
	4	52,46	12,11	59,95	13,04	74,90	15,26	82,28	15,60	89,76	16,23	97,54	16,76	99,55	8,92
	6	52,46	12,52	59,95	13,48	74,90	15,78	82,28	16,14	89,76	16,78	97,54	17,34	99,55	9,22
	8	52,46	12,94	59,95	13,93	74,90	16,31	82,28	16,67	89,76	17,34	97,54	17,91	99,55	9,53
	10	52,46	13,36	59,95	14,39	74,90	16,84	82,28	17,21	89,76	17,91	97,54	18,50	99,55	9,84
	12	52,46	13,79	59,95	14,84	74,90	17,37	82,28	17,76	89,76	18,47	97,54	19,08	99,55	10,15
	14	52,46	14,21	59,95	15,30	74,90	17,91	82,28	18,31	89,76	19,04	97,54	19,67	99,55	10,47
	16	52,46	14,64	59,95	15,76	74,90	18,45	82,28	18,86	89,76	19,62	97,54	20,26	99,55	10,78
	18	52,46	15,07	59,95	16,22	74,90	18,99	82,28	19,42	89,76	20,20	97,54	20,86	99,55	11,10
	20	52,46	15,51	59,95	16,70	74,90	19,54	82,28	19,97	89,76	20,78	97,54	21,46	99,55	11,41
	21	52,46	15,72	59,95	16,93	74,90	19,82	82,28	20,26	89,76	21,07	97,54	21,76	99,55	11,58
	23	52,46	16,16	59,95	17,40	74,90	20,36	82,28	20,82	89,76	21,66	97,54	22,37	99,55	11,90
	25	52,46	16,60	59,95	17,87	74,90	20,92	82,28	21,39	89,76	22,25	97,54	22,98	99,55	12,23
	27	52,46	17,05	59,95	18,36	74,90	21,48	82,28	21,96	89,76	22,85	97,54	23,59	99,55	12,55
	29	52,46	17,50	59,95	18,83	74,90	22,05	82,28	22,54	89,76	23,45	97,54	24,22	99,55	12,88
	31	52,46	17,94	59,95	19,32	74,90	22,61	82,28	23,12	89,36	23,94	97,54	24,84	99,55	13,22
	33	52,46	18,40	59,95	19,81	74,90	23,18	79,23	22,82	83,20	22,85	91,12	23,79	99,04	13,48
	35	52,46	18,86	59,95	20,30	73,11	23,19	74,80	22,08	77,03	21,69	84,37	22,57	91,71	12,79
	37	52,46	19,27	59,95	20,75	72,06	23,37	73,84	22,28	75,32	21,68	81,97	22,42	89,10	12,70
	39	52,46	19,69	59,84	21,16	70,79	23,45	71,32	21,99	73,55	21,63	80,55	22,51	87,55	12,76
	41	52,35	20,07	59,73	21,58	68,16	23,07	68,81	21,68	72,25	21,70	79,13	22,59	86,01	12,80
	43	52,35	20,50	57,63	21,26	64,19	22,19	67,57	21,73	70,95	21,76	77,70	22,65	84,46	12,83
	46	50,45	20,17	56,38	21,24	63,01	22,24	66,33	21,79	69,65	21,81	76,28	22,71	82,91	12,86
	48	45,58	18,79	51,65	20,06	57,73	21,00	60,77	20,57	63,81	20,60	69,88	21,45	75,96	12,15
	50	42,80	18,00	48,50	19,22	54,21	20,12	57,06	19,71	59,91	19,73	65,62	20,55	71,33	11,64
	52	40,02	17,16	45,35	18,33	50,69	19,19	53,35	18,80	56,02	18,82	61,36	19,59	66,69	11,10
	55	37,24	16,28	42,20	17,39	47,16	18,21	49,65	17,84	52,13	17,86	57,09	18,59	62,06	10,53
100%	-15	48,56	8,02	55,41	8,62	69,32	10,10	76,06	10,32	83,01	10,74	94,08	11,57	96,81	6,20
	-10	48,56	8,97	55,41	9,64	69,32	11,30	76,06	11,54	83,01	12,01	94,08	12,93	96,81	6,93
	-5	48,56	9,93	55,41	10,67	69,32	12,51	76,06	12,77	83,01	13,30	94,08	14,32	96,81	7,68
	-2	48,56	10,51	55,41	11,30	69,32	13,25	76,06	13,53	83,01	14,08	94,08	15,16	96,81	8,14
	0	48,56	10,91	55,41	11,73	69,32	13,75	76,06	14,03	83,01	14,61	94,08	15,73	96,81	8,44
	2	48,56	11,30	55,41	12,15	69,32	14,24	76,06	14,55	83,01	15,14	94,08	16,30	96,81	8,74
	4	48,56	11,70	55,41	12,58	69,32	14,74	76,06	15,06	83,01	15,67	94,08	16,88	96,81	9,05
	6	48,56	12,10	55,41	13,01	69,32	15,25	76,06	15,57	83,01	16,21	94,08	17,45	96,81	9,36
	8	48,56	12,50	55,41	13,45	69,32	15,76	76,06	16,09	83,01	16,75	94,08	18,04	96,81	9,68
	10	48,56	12,91	55,41	13,88	69,32	16,27	76,06	16,61	83,01	17,29	94,08	18,63	96,81	9,99
	12	48,56	13,32	55,41	14,32	69,32	16,78	76,06	17,14	83,01	17,84	94,08	19,22	96,81	10,31
	14	48,56	13,73	55,41	14,76	69,32	17,30	76,06	17,67	83,01	18,39	94,08	19,81	96,81	10,63
	16	48,56	14,15	55,41	15,21	69,32	17,83	76,06	18,20	83,01	18,94	94,08	20,40	96,81	10,94
	18	48,56	14,56	55,41	15,66	69,32	18,35	76,06	18,74	83,01	19,50	94,08	21,00	96,81	11,27
	20	48,56	14,98	55,41	16,11	69,32	18,88	76,06	19,28	83,01	20,06	94,08	21,61	96,81	11,59
	21	48,56	15,19	55,41	16,34	69,32	19,14	76,06	19,55	83,01	20,35	94,08	21,92	96,81	11,76
	23	48,56	15,62	55,41	16,79	69,32	19,68	76,06	20,10	83,01	20,92	94,08	22,53	96,81	12,08
	25	48,56	16,04	55,41	17,25	69,32	20,22	76,06	20,65	83,01	21,49	94,08	23,14	96,81	12,42
	27	48,56	16,47	55,41	17,71	69,32	20,76	76,06	21,20	83,01	22,06	94,08	23,76	96,81	12,75
	29	48,56	16,91	55,41	18,17	69,32	21,30	76,06	21,75	83,01	22,64	94,08	24,38	96,81	13,08
	31	48,56	17,34	55,41	18,64	69,32	21,85	76,06	22,31	83,01	23,22	94,08	25,01	96,81	13,42
	33	48,56	17,78	55,41	19,11	69,32	22,40	76,06	22,88	82,78	23,74	90,67	24,71	96,81	13,75
	35	48,56	18,22	55,41	19,59	69,32	22,95	73,00	22,50	76,65	22,53	83,95	23,45	91,25	13,29
	37	48,56	18,63	55,41	20,02	69,11	23,39	71,95	22,67	75,34	22,64	82,52	23,56	89,69	13,35
	39	48,56	19,03	55,41	20,46	69,11	23,91	70,79	22,79	74,03	22,73	81,08	23,66	88,13	13,40
	41	48,56	19,44	55,41	20,90	66,58	23,53	69,26	22,78	72,72	22,81	79,65	23,74	86,58	13,45
	43	48,56	19,85	55,41	21,35	64,61	23,32	68,01	22,85	71,42	22,87	78,22	23,81	85,02	13,49
	46	48,56	20,27	55,41	21,79	63,43	23,37	66,77	22,89	70,11	22,92	76,78	23,86	83,46	13,52
	48	45,88	19,74	52,00	21,08	58,11	22,08	61,17	21,62	64,23	21,65	70,35	22,54	76,46	12,77
	50	43,08	18,91	48,82	20,20	54,57	21,15	57,44	20,72	60,31	20,74	66,06	21,59	71,80	12,23
	52	40,28	18,04	45,65	19,26	51,02	20,17	53,71	19,76	56,39	19,78	61,76	20,59	67,13	11,67
	55	37,48	17,11	42,48	18,27	47,48	19,13	49,98	18,74	52,47	18,77	57,47	19,54	62,47	11,07

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
90%	-15	44,36	7,10	49,94	7,53	62,25	8,80	68,58	9,02	74,69	9,36	87,22	10,39	93,02	5,78
	-10	44,36	7,94	49,94	8,42	62,25	9,83	68,58	10,08	74,69	10,47	87,22	11,62	93,02	6,46
	-5	44,36	8,79	49,94	9,32	62,25	10,89	68,58	11,16	74,69	11,59	87,22	12,87	93,02	7,15
	-2	44,36	9,31	49,94	9,87	62,25	11,53	68,58	11,82	74,69	12,27	87,22	13,63	93,02	7,58
	0	44,36	9,65	49,94	10,24	62,25	11,96	68,58	12,26	74,69	12,73	87,22	14,13	93,02	7,86
	2	44,36	10,01	49,94	10,61	62,25	12,40	68,58	12,71	74,69	13,20	87,22	14,65	93,02	8,14
	4	44,36	10,36	49,94	10,99	62,25	12,83	68,58	13,16	74,69	13,66	87,22	15,16	93,02	8,43
	6	44,36	10,71	49,94	11,36	62,25	13,27	68,58	13,60	74,69	14,13	87,22	15,68	93,02	8,72
	8	44,36	11,07	49,94	11,74	62,25	13,72	68,58	14,06	74,69	14,60	87,22	16,21	93,02	9,01
	10	44,36	11,43	49,94	12,12	62,25	14,16	68,58	14,52	74,69	15,08	87,22	16,73	93,02	9,30
	12	44,36	11,79	49,94	12,51	62,25	14,61	68,58	14,98	74,69	15,55	87,22	17,26	93,02	9,60
	14	44,36	12,16	49,94	12,89	62,25	15,06	68,58	15,44	74,69	16,04	87,22	17,80	93,02	9,89
	16	44,36	12,52	49,94	13,28	62,25	15,51	68,58	15,91	74,69	16,52	87,22	18,33	93,02	10,19
	18	44,36	12,89	49,94	13,68	62,25	15,97	68,58	16,37	74,69	17,00	87,22	18,87	93,02	10,49
	20	44,36	13,26	49,94	14,07	62,25	16,43	68,58	16,85	74,69	17,50	87,22	19,42	93,02	10,80
	21	44,36	13,45	49,94	14,26	62,25	16,66	68,58	17,08	74,69	17,74	87,22	19,69	93,02	10,94
	23	44,36	13,82	49,94	14,66	62,25	17,13	68,58	17,56	74,69	18,23	87,22	20,24	93,02	11,25
	25	44,36	14,21	49,94	15,06	62,25	17,60	68,58	18,04	74,69	18,73	87,22	20,79	93,02	11,56
	27	44,36	14,58	49,94	15,47	62,25	18,07	68,58	18,52	74,69	19,23	87,22	21,35	93,02	11,87
	29	44,36	14,96	49,94	15,87	62,25	18,54	68,58	19,01	74,69	19,74	87,22	21,91	93,02	12,18
	31	44,36	15,35	49,94	16,28	62,25	19,01	68,58	19,50	74,69	20,25	87,22	22,47	93,02	12,49
	33	44,36	15,74	49,94	16,70	62,25	19,50	68,58	19,99	74,69	20,76	87,22	23,04	93,02	12,81
	35	44,36	16,13	49,94	17,11	62,25	19,98	68,58	20,48	74,69	21,27	83,95	22,72	91,25	12,87
	37	44,36	16,48	49,94	17,48	62,25	20,42	68,58	20,94	72,05	20,98	78,91	21,83	85,77	12,37
	39	44,36	16,85	49,94	17,87	62,15	20,83	68,48	21,36	70,27	20,90	73,89	20,89	80,31	11,84
	41	44,36	17,21	49,94	18,26	62,15	21,29	65,84	20,98	67,94	20,65	72,58	20,96	78,89	11,88
	43	44,36	17,57	49,94	18,64	59,62	20,85	62,68	20,40	65,08	20,20	71,28	21,02	77,47	11,91
	46	44,36	17,94	49,94	19,03	57,80	20,63	60,84	20,22	63,89	20,24	69,97	21,07	76,05	11,94
	48	41,81	17,44	47,38	18,61	52,95	19,49	55,74	19,10	58,53	19,12	64,10	19,90	69,68	11,27
	50	39,26	16,70	44,49	17,83	49,72	18,67	52,34	18,29	54,96	18,31	60,19	19,07	65,43	10,80
	52	36,71	15,93	41,60	17,01	46,49	17,81	48,94	17,44	51,39	17,47	56,28	18,18	61,18	10,30
	55	34,16	15,11	38,71	16,14	43,26	16,90	45,54	16,55	47,82	16,57	52,37	17,25	56,93	9,77
80%	-15	39,40	6,08	45,09	6,56	55,41	7,55	60,99	7,74	66,47	8,04	77,53	8,91	87,86	5,26
	-10	39,40	6,80	45,09	7,34	55,41	8,44	60,99	8,65	66,47	8,99	77,53	9,97	87,86	5,89
	-5	39,40	7,53	45,09	8,12	55,41	9,35	60,99	9,58	66,47	9,95	77,53	11,03	87,86	6,52
	-2	39,40	7,98	45,09	8,60	55,41	9,90	60,99	10,14	66,47	10,54	77,53	11,69	87,86	6,90
	0	39,40	8,27	45,09	8,92	55,41	10,27	60,99	10,52	66,47	10,93	77,53	12,12	87,86	7,16
	2	39,40	8,57	45,09	9,24	55,41	10,64	60,99	10,90	66,47	11,33	77,53	12,56	87,86	7,42
	4	39,40	8,88	45,09	9,57	55,41	11,02	60,99	11,29	66,47	11,73	77,53	13,00	87,86	7,68
	6	39,40	9,18	45,09	9,90	55,41	11,40	60,99	11,67	66,47	12,13	77,53	13,45	87,86	7,94
	8	39,40	9,48	45,09	10,23	55,41	11,77	60,99	12,06	66,47	12,54	77,53	13,90	87,86	8,21
	10	39,40	9,80	45,09	10,56	55,41	12,16	60,99	12,46	66,47	12,95	77,53	14,35	87,86	8,48
	12	39,40	10,10	45,09	10,90	55,41	12,55	60,99	12,85	66,47	13,35	77,53	14,81	87,86	8,74
	14	39,40	10,42	45,09	11,23	55,41	12,93	60,99	13,25	66,47	13,76	77,53	15,26	87,86	9,01
	16	39,40	10,73	45,09	11,57	55,41	13,32	60,99	13,65	66,47	14,18	77,53	15,72	87,86	9,28
	18	39,40	11,05	45,09	11,91	55,41	13,71	60,99	14,05	66,47	14,60	77,53	16,18	87,86	9,56
	20	39,40	11,37	45,09	12,26	55,41	14,11	60,99	14,45	66,47	15,02	77,53	16,65	87,86	9,84
	21	39,40	11,53	45,09	12,43	55,41	14,31	60,99	14,66	66,47	15,23	77,53	16,88	87,86	9,97
	23	39,40	11,84	45,09	12,77	55,41	14,71	60,99	15,06	66,47	15,66	77,53	17,35	87,86	10,25
	25	39,40	12,17	45,09	13,12	55,41	15,11	60,99	15,48	66,47	16,08	77,53	17,83	87,86	10,53
	27	39,40	12,50	45,09	13,48	55,41	15,51	60,99	15,89	66,47	16,51	77,53	18,31	87,86	10,81
	29	39,40	12,82	45,09	13,83	55,41	15,92	60,99	16,31	66,47	16,95	77,53	18,79	87,86	11,10
	31	39,40	13,15	45,09	14,18	55,41	16,33	60,99	16,72	66,47	17,38	77,53	19,27	87,86	11,38
	33	39,40	13,49	45,09	14,54	55,41	16,74	60,99	17,15	66,47	17,82	77,53	19,76	87,86	11,67
	35	39,40	13,82	45,09	14,90	55,41	17,15	60,99	17,57	66,47	18,26	77,53	20,25	87,86	11,96
	37	39,40	14,13	45,09	15,23	55,41	17,54	60,99	17,97	66,47	18,67	77,53	20,69	85,77	11,93
	39	39,40	14,43	45,09	15,57	55,41	17,92	60,99	18,36	66,47	19,08	73,88	20,15	80,30	11,41
	41	39,40	14,75	45,09	15,90	55,41	18,30	60,78	18,69	64,15	18,81	68,84	19,18	74,82	10,87
	43	39,40	15,06	45,09	16,24	55,30	18,66	58,25	18,29	61,95	18,54	64,14	18,25	69,72	10,34
	46	39,40	15,38	45,09	16,58	52,56	18,10	55,73	17,87	57,49	17,57	62,96	18,29	68,44	10,36
	48	38,56	15,51	42,64	16,16	47,65	16,92	50,16	16,58	52,67	16,60	57,68	17,28	62,70	9,79
	50	36,66	15,05	40,04	15,48	44,75	16,21	47,10	15,88	49,46	15,90	54,17	16,55	58,88	9,38
	52	33,03	13,83	37,43	14,76	41,84	15,46	44,04	15,15	46,24	15,16	50,65	15,78	55,05	8,94
	55	30,73	13,12	34,83	14,01	38,93	14,67	40,98	14,37	43,03	14,39	47,13	14,98	51,22	8,48

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
70%	-15	34,55	5,12	39,40	5,50	48,46	6,33	53,30	6,49	58,14	6,75	67,94	7,49	77,01	4,43
	-10	34,55	5,72	39,40	6,15	48,46	7,09	53,30	7,25	58,14	7,54	67,94	8,38	77,01	4,95
	-5	34,55	6,34	39,40	6,81	48,46	7,85	53,30	8,03	58,14	8,35	67,94	9,28	77,01	5,48
	-2	34,55	6,71	39,40	7,21	48,46	8,31	53,30	8,51	58,14	8,85	67,94	9,83	77,01	5,80
	0	34,55	6,96	39,40	7,48	48,46	8,62	53,30	8,82	58,14	9,18	67,94	10,19	77,01	6,02
	2	34,55	7,22	39,40	7,75	48,46	8,93	53,30	9,14	58,14	9,51	67,94	10,56	77,01	6,24
	4	34,55	7,47	39,40	8,02	48,46	9,25	53,30	9,47	58,14	9,84	67,94	10,93	77,01	6,46
	6	34,55	7,72	39,40	8,30	48,46	9,56	53,30	9,79	58,14	10,18	67,94	11,31	77,01	6,68
	8	34,55	7,98	39,40	8,58	48,46	9,88	53,30	10,12	58,14	10,52	67,94	11,69	77,01	6,91
	10	34,55	8,24	39,40	8,85	48,46	10,20	53,30	10,44	58,14	10,86	67,94	12,07	77,01	7,13
	12	34,55	8,50	39,40	9,14	48,46	10,53	53,30	10,77	58,14	11,21	67,94	12,45	77,01	7,35
	14	34,55	8,77	39,40	9,42	48,46	10,85	53,30	11,11	58,14	11,56	67,94	12,83	77,01	7,58
	16	34,55	9,03	39,40	9,70	48,46	11,18	53,30	11,44	58,14	11,90	67,94	13,22	77,01	7,81
	18	34,55	9,30	39,40	9,99	48,46	11,51	53,30	11,78	58,14	12,25	67,94	13,61	77,01	8,04
	20	34,55	9,57	39,40	10,27	48,46	11,84	53,30	12,12	58,14	12,60	67,94	14,00	77,01	8,27
	21	34,55	9,70	39,40	10,42	48,46	12,00	53,30	12,29	58,14	12,79	67,94	14,20	77,01	8,39
	23	34,55	9,97	39,40	10,71	48,46	12,34	53,30	12,63	58,14	13,14	67,94	14,59	77,01	8,62
	25	34,55	10,24	39,40	11,00	48,46	12,67	53,30	12,98	58,14	13,50	67,94	14,99	77,01	8,86
	27	34,55	10,51	39,40	11,30	48,46	13,02	53,30	13,33	58,14	13,86	67,94	15,39	77,01	9,10
	29	34,55	10,79	39,40	11,59	48,46	13,36	53,30	13,68	58,14	14,22	67,94	15,80	77,01	9,33
	31	34,55	11,07	39,40	11,89	48,46	13,70	53,30	14,03	58,14	14,59	67,94	16,21	77,01	9,57
	33	34,55	11,35	39,40	12,19	48,46	14,05	53,30	14,38	58,14	14,96	67,94	16,61	77,01	9,81
	35	34,55	11,63	39,40	12,49	48,46	14,39	53,30	14,74	58,14	15,33	67,94	17,03	77,01	10,06
	37	34,55	11,89	39,40	12,77	48,46	14,72	53,30	15,06	58,14	15,67	67,94	17,40	77,01	10,28
	39	34,55	12,15	39,40	13,05	48,46	15,04	53,30	15,39	58,14	16,01	67,94	17,78	77,01	10,51
	41	34,55	12,41	39,40	13,33	48,46	15,36	53,30	15,72	58,14	16,35	67,94	18,17	74,82	10,43
	43	34,55	12,67	39,40	13,62	48,46	15,69	53,30	16,06	58,14	16,70	63,80	17,42	69,35	9,87
	46	34,55	12,94	39,40	13,90	48,46	16,01	51,10	15,72	55,20	16,19	58,76	16,38	63,88	9,28
	48	33,93	13,10	38,77	14,11	45,19	15,40	46,25	14,67	46,76	14,14	51,21	14,72	55,66	8,34
	50	32,03	12,62	35,50	13,17	39,63	13,78	41,72	13,50	43,80	13,51	47,97	14,06	52,14	7,97
	52	30,23	12,14	33,15	12,55	37,05	13,14	39,00	12,87	40,96	12,89	44,86	13,42	48,76	7,60
	55	27,22	11,15	30,85	11,90	34,48	12,46	36,29	12,21	38,11	12,23	41,74	12,73	45,37	7,21
60%	-15	29,60	4,18	33,82	4,50	42,24	5,27	46,46	5,39	49,83	5,52	58,14	6,12	65,84	3,61
	-10	29,60	4,67	33,82	5,03	42,24	5,89	46,46	6,03	49,83	6,16	58,14	6,83	65,84	4,03
	-5	29,60	5,17	33,82	5,57	42,24	6,52	46,46	6,68	49,83	6,83	58,14	7,57	65,84	4,47
	-2	29,60	5,48	33,82	5,90	42,24	6,91	46,46	7,07	49,83	7,23	58,14	8,02	65,84	4,73
	0	29,60	5,69	33,82	6,12	42,24	7,16	46,46	7,34	49,83	7,50	58,14	8,32	65,84	4,91
	2	29,60	5,89	33,82	6,35	42,24	7,42	46,46	7,60	49,83	7,77	58,14	8,62	65,84	5,09
	4	29,60	6,10	33,82	6,56	42,24	7,68	46,46	7,86	49,83	8,04	58,14	8,92	65,84	5,26
	6	29,60	6,31	33,82	6,79	42,24	7,95	46,46	8,14	49,83	8,32	58,14	9,22	65,84	5,45
	8	29,60	6,52	33,82	7,02	42,24	8,21	46,46	8,41	49,83	8,59	58,14	9,54	65,84	5,63
	10	29,60	6,73	33,82	7,25	42,24	8,48	46,46	8,68	49,83	8,88	58,14	9,84	65,84	5,81
	12	29,60	3,82	33,82	4,11	42,24	4,82	46,46	4,93	49,83	5,04	58,14	5,59	65,84	5,99
	14	29,60	3,94	33,82	4,24	42,24	4,96	46,46	5,08	49,83	5,20	58,14	5,76	65,84	6,18
	16	29,60	4,06	33,82	4,37	42,24	5,12	46,46	5,23	49,83	5,35	58,14	5,93	65,84	6,36
	18	29,60	4,18	33,82	4,50	42,24	5,26	46,46	5,39	49,83	5,51	58,14	6,11	65,84	6,55
	20	29,60	4,30	33,82	4,63	42,24	5,42	46,46	5,55	49,83	5,67	58,14	6,29	65,84	6,74
	21	29,60	4,36	33,82	4,69	42,24	5,49	46,46	5,62	49,83	5,75	58,14	6,38	65,84	6,83
	23	29,60	4,48	33,82	4,82	42,24	5,65	46,46	5,78	49,83	5,91	58,14	6,55	65,84	7,03
	25	29,60	4,60	33,82	4,96	42,24	5,80	46,46	5,93	49,83	6,07	58,14	6,73	65,84	7,22
	27	29,60	4,73	33,82	5,09	42,24	5,95	46,46	6,09	49,83	6,23	58,14	6,91	65,84	7,41
	29	29,60	4,85	33,82	5,22	42,24	6,11	46,46	6,26	49,83	6,40	58,14	7,09	65,84	7,61
	31	29,60	4,97	33,82	5,36	42,24	6,27	46,46	6,42	49,83	6,56	58,14	7,28	65,84	7,81
	33	29,60	5,10	33,82	5,49	42,24	6,43	46,46	6,58	49,83	6,73	58,14	7,46	65,84	8,00
	35	29,60	5,23	33,82	5,63	42,24	6,59	46,46	6,74	49,83	6,89	58,14	7,65	65,84	8,20
	37	29,60	5,35	33,82	5,75	42,24	6,73	46,46	6,89	49,83	7,05	58,14	7,82	65,84	8,38
	39	29,60	5,46	33,82	5,88	42,24	6,88	46,46	7,04	49,83	7,20	58,14	7,99	65,84	8,57
	41	29,60	5,58	33,82	6,00	42,24	7,03	46,46	7,19	49,83	7,36	58,14	8,16	65,84	8,75
	43	29,60	5,70	33,82	6,13	42,24	7,18	46,46	7,35	49,83	7,51	58,14	8,33	65,84	8,94
	46	29,60	5,82	33,82	6,26	42,24	7,33	46,46	7,50	49,83	7,67	58,14	8,51	63,88	8,85
	48	29,60	6,00	33,82	6,45	42,24	7,55	44,53	7,41	46,76	7,42	51,21	7,72	55,66	7,95
	50	29,60	6,12	33,82	6,59	38,14	6,96	40,15	6,82	42,16	6,82	46,17	7,11	50,19	7,31
	52	27,07	5,71	30,40	6,04	33,98	6,32	35,77	6,19	37,56	6,20	41,14	6,46	44,71	6,65
	55	23,61	5,07	26,76	5,42	29,91	5,68	31,48	5,56	33,06	5,57	36,21	5,79	39,36	5,96

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna (°C BS)	Temperatura interna (°C BS/BU)													
		22/15		23.3/16		25.8/18		27/19		28.2/20		30.7/22		32/24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW	KW
50%	-15	24,65	1,81	28,13	1,95	35,18	2,28	38,77	2,34	42,24	2,43	48,46	2,66	54,99	2,85
	-10	24,65	2,03	28,13	2,18	35,18	2,55	38,77	2,62	42,24	2,72	48,46	2,97	54,99	3,19
	-5	24,65	2,24	28,13	2,41	35,18	2,83	38,77	2,90	42,24	3,01	48,46	3,28	54,99	3,53
	-2	24,65	2,38	28,13	2,55	35,18	3,00	38,77	3,07	42,24	3,19	48,46	3,48	54,99	3,74
	0	24,65	2,47	28,13	2,65	35,18	3,11	38,77	3,18	42,24	3,31	48,46	3,61	54,99	3,88
	2	24,65	2,55	28,13	2,75	35,18	3,22	38,77	3,30	42,24	3,43	48,46	3,74	54,99	4,02
	4	24,65	2,64	28,13	2,84	35,18	3,33	38,77	3,42	42,24	3,55	48,46	3,87	54,99	4,16
	6	24,65	2,74	28,13	2,94	35,18	3,44	38,77	3,54	42,24	3,67	48,46	4,00	54,99	4,30
	8	24,65	2,83	28,13	3,04	35,18	3,56	38,77	3,66	42,24	3,80	48,46	4,14	54,99	4,44
	10	24,65	2,92	28,13	3,14	35,18	3,68	38,77	3,77	42,24	3,92	48,46	4,27	54,99	4,59
	12	24,65	3,01	28,13	3,24	35,18	3,79	38,77	3,89	42,24	4,04	48,46	4,41	54,99	4,74
	14	24,65	3,10	28,13	3,34	35,18	3,91	38,77	4,01	42,24	4,17	48,46	4,54	54,99	4,88
	16	24,65	3,20	28,13	3,44	35,18	4,03	38,77	4,13	42,24	4,29	48,46	4,68	54,99	5,03
	18	24,65	3,29	28,13	3,54	35,18	4,15	38,77	4,26	42,24	4,42	48,46	4,82	54,99	5,18
	20	24,65	3,39	28,13	3,64	35,18	4,27	38,77	4,38	42,24	4,54	48,46	4,96	54,99	5,33
	21	24,65	3,44	28,13	3,69	35,18	4,33	38,77	4,44	42,24	4,61	48,46	5,03	54,99	5,40
	23	24,65	3,53	28,13	3,80	35,18	4,45	38,77	4,56	42,24	4,74	48,46	5,17	54,99	5,55
	25	24,65	3,63	28,13	3,90	35,18	4,57	38,77	4,69	42,24	4,87	48,46	5,31	54,99	5,70
	27	24,65	3,73	28,13	4,00	35,18	4,69	38,77	4,81	42,24	5,00	48,46	5,45	54,99	5,86
	29	24,65	3,82	28,13	4,11	35,18	4,82	38,77	4,94	42,24	5,13	48,46	5,59	54,99	6,01
	31	24,65	3,92	28,13	4,22	35,18	4,94	38,77	5,06	42,24	5,26	48,46	5,74	54,99	6,16
	33	24,65	4,02	28,13	4,32	35,18	5,06	38,77	5,19	42,24	5,39	48,46	5,88	54,99	6,32
	35	24,65	4,12	28,13	4,43	35,18	5,19	38,77	5,32	42,24	5,53	48,46	6,03	54,99	6,48
	37	24,65	4,21	28,13	4,53	35,18	5,30	38,77	5,44	42,24	5,65	48,46	6,16	54,99	6,62
	39	24,65	4,30	28,13	4,63	35,18	5,42	38,77	5,56	42,24	5,78	48,46	6,30	54,99	6,76
	41	24,65	4,40	28,13	4,73	35,18	5,53	38,77	5,68	42,24	5,90	48,46	6,43	54,99	6,91
	43	24,65	4,49	28,13	4,83	35,18	5,65	38,77	5,80	42,24	6,02	48,46	6,57	54,99	7,06
	46	24,65	4,58	28,13	4,93	35,18	5,78	38,77	5,92	42,24	6,15	48,46	6,71	54,99	7,21
	48	24,65	4,73	28,13	5,08	35,18	5,95	38,77	6,10	42,24	6,34	48,46	6,91	54,99	7,43
	50	24,65	4,82	28,13	5,18	35,18	6,07	38,77	6,23	42,16	6,46	46,17	6,72	50,19	6,92
	52	24,65	4,92	28,13	5,29	33,98	5,98	35,77	5,86	37,56	5,87	41,14	6,10	44,71	6,29
	55	23,54	4,79	26,68	5,11	29,82	5,35	31,39	5,25	32,96	5,25	36,10	5,46	39,24	5,63

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

Tabella di capacità

Sistema VRF Serie IV8-730WV2RN1E(PRO)

Tabella della capacità di riscaldamento

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	-29.8	-30.0	51,42	14,37	50,43	14,81	49,44	15,20	48,95	15,49	48,46	15,68	47,46	16,09
	-25.0	-25.4	51,42	14,48	50,43	14,87	49,44	15,24	48,95	15,45	48,46	15,62	47,46	15,98
	-19.8	-20.0	51,42	14,61	50,43	14,93	49,44	15,27	48,95	15,41	48,46	15,56	47,46	15,88
	-18.8	-19.0	51,42	14,59	50,43	14,92	49,44	15,21	48,95	15,38	48,46	15,53	47,46	15,81
	-16.7	-17.0	51,42	14,55	50,43	14,85	49,44	15,15	48,95	15,31	48,46	15,44	47,46	15,73
	-13.7	-15.0	51,42	14,58	50,43	14,87	49,44	15,16	48,95	15,30	48,84	15,57	47,96	15,89
	-11.8	-13.0	51,82	14,57	50,93	14,89	50,04	15,21	49,60	15,37	49,15	15,53	49,05	16,09
	-9.8	-11.0	52,15	14,53	52,07	15,07	51,25	15,43	50,85	15,60	50,44	15,77	49,61	16,11
	-9.5	-10.0	53,20	14,70	52,38	15,03	51,55	15,37	51,14	15,53	50,71	15,69	49,88	16,04
	-8.5	-9.1	53,47	14,72	52,64	15,06	51,80	15,39	51,39	15,54	50,97	15,72	50,11	16,05
	-7.0	-7.6	53,92	14,73	53,07	15,06	52,22	15,38	51,79	15,55	51,36	15,71	50,50	16,04
	-5.0	-5.6	53,59	14,50	52,73	14,80	51,86	15,12	51,43	15,28	50,99	15,44	50,12	15,75
	-3.0	-3.7	55,55	14,68	54,66	15,00	53,76	15,30	53,30	15,47	52,86	15,62	51,94	15,94
	0.0	-0.7	60,26	15,34	59,30	15,68	58,32	16,00	57,83	16,18	57,33	16,33	56,35	16,67
	3.0	2.2	67,56	16,60	66,50	16,97	65,41	17,34	64,88	17,52	64,33	17,71	63,24	18,06
	5.0	4.1	72,52	17,43	72,35	18,05	71,19	18,46	70,61	18,65	70,04	18,84	68,86	19,24
	7.0	6.0	84,57	19,89	82,95	20,27	81,32	20,64	80,51	20,82	79,70	21,00	78,07	21,19
	9.0	7.9	87,28	20,10	85,60	20,50	83,93	20,86	83,09	21,05	82,24	21,24	78,07	20,02
	11.0	9.8	89,99	20,31	88,25	20,70	86,53	21,08	85,67	21,26	84,80	21,45	78,07	18,93
	13.0	11.8	92,70	20,47	90,91	20,87	89,13	21,27	88,24	21,46	84,80	20,48	79,14	18,07
	15.0	13.7	95,40	20,66	93,57	21,06	91,73	21,49	90,82	21,30	84,80	19,34	79,14	17,01
	18.0	16,6	99,46	20,95	97,55	21,39	94,94	20,99	90,82	19,49	84,80	17,68	79,14	15,53
	20.0	19,6	103,52	21,21	101,53	21,66	94,94	19,19	90,97	17,85	84,80	16,14	79,14	14,17
	23.0	22,4	107,58	21,52	102,79	20,10	94,94	17,51	90,97	16,26	84,80	14,64	79,14	12,96
	26.0	25,3	111,64	21,11	102,79	18,36	94,94	15,92	90,97	14,72	84,80	13,36	79,14	11,77
	30.0	28,1	113,32	20,25	102,79	16,77	94,94	14,48	90,97	13,34	87,11	12,52	79,14	10,69
120%	-29.8	-30.0	49,16	14,08	48,22	14,52	47,27	14,95	46,80	15,17	46,33	15,38	45,38	15,77
	-25.0	-25.4	49,16	14,19	48,22	14,56	47,27	14,94	46,80	15,12	46,33	15,30	45,38	15,66
	-19.8	-20.0	49,16	14,31	48,22	14,60	47,27	14,93	46,80	15,07	46,33	15,23	45,38	15,54
	-18.8	-19.0	49,16	14,29	48,22	14,61	47,27	14,90	46,80	15,06	46,33	15,20	45,38	15,49
	-16.7	-17.0	49,16	14,26	48,22	14,55	47,27	14,83	46,80	14,98	46,33	15,12	45,80	15,54
	-13.7	-15.0	49,16	14,29	48,63	14,68	47,78	14,99	47,36	15,16	46,93	15,31	46,79	15,88
	-11.8	-13.0	49,79	14,33	49,67	14,87	48,90	15,21	48,50	15,38	48,12	15,55	47,34	15,90
	-9.8	-11.0	51,05	14,59	50,26	14,94	49,46	15,26	49,06	15,43	48,66	15,59	47,86	15,92
	-9.5	-10.0	51,34	14,55	50,54	14,86	49,73	15,19	49,33	15,36	48,92	15,52	48,11	15,83
	-8.5	-9.1	51,60	14,57	50,79	14,87	49,97	15,21	49,56	15,38	49,15	15,53	48,33	15,85
	-7.0	-7.6	52,01	14,57	51,18	14,89	50,36	15,22	49,94	15,37	49,51	15,53	48,68	15,85
	-5.0	-5.6	51,66	14,34	50,82	14,63	49,98	14,94	49,56	15,09	49,14	15,25	48,29	15,57
	-3.0	-3.7	53,55	14,53	52,68	14,83	51,80	15,14	51,36	15,29	50,92	15,44	50,04	15,77
	0.0	-0.7	58,10	15,21	57,15	15,53	56,21	15,87	55,73	16,01	55,26	16,18	54,30	16,49
	3.0	2.2	65,17	16,51	64,13	16,86	63,08	17,21	62,56	17,39	62,04	17,57	60,86	17,77
	5.0	4.1	70,92	17,58	69,81	17,97	68,68	18,36	68,12	18,54	67,55	18,75	65,69	18,16
	7.0	6.0	80,86	19,66	79,30	20,01	77,75	20,37	76,97	20,55	76,19	20,71	73,20	19,13
	9.0	7.9	83,44	19,86	81,84	20,24	80,24	20,61	79,43	20,80	78,63	20,43	73,20	18,09
	11.0	9.8	86,03	20,09	84,38	20,47	82,72	20,85	81,89	20,63	78,63	19,32	73,20	17,06
	13.0	11.8	88,62	20,30	86,91	20,68	85,21	20,74	81,89	19,43	78,63	18,19	73,20	16,01
	15.0	13.7	91,20	20,49	89,45	20,91	87,70	20,16	81,89	18,34	78,63	17,14	73,20	15,06
	18.0	16,6	95,09	20,82	93,26	20,65	87,70	18,45	83,98	17,18	78,63	15,64	73,20	13,81
	20.0	19,6	98,97	21,11	93,26	18,89	87,70	16,81	83,98	15,66	78,63	14,22	73,20	12,63
	23.0	22,4	102,25	19,95	93,26	17,23	87,70	15,27	83,98	14,24	78,63	13,02	73,20	11,49
	26.0	25,3	102,25	18,21	94,90	15,94	87,70	13,91	83,98	12,98	78,63	11,84	73,20	10,38
	30.0	28,1	102,25	16,62	94,90	14,50	87,72	12,67	83,98	11,83	80,45	11,02	73,20	9,39

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
110%	-29.8	-30.0	46,43	13,68	45,55	14,11	44,65	14,51	44,20	14,70	43,76	14,91	42,87	15,28
	-25.0	-25.4	46,43	13,77	45,55	14,13	44,65	14,48	44,20	14,66	43,76	14,83	42,87	15,17
	-19.8	-20.0	46,43	13,87	45,55	14,15	44,65	14,46	44,20	14,60	43,76	14,76	42,87	15,06
	-18.8	-19.0	46,43	13,86	45,55	14,15	44,65	14,44	44,20	14,58	43,76	14,72	43,28	15,16
	-16.7	-17.0	46,43	13,83	45,94	14,22	45,14	14,54	44,75	14,70	44,36	14,85	44,24	15,40
	-13.7	-15.0	47,05	14,03	46,94	14,55	46,22	14,90	45,86	15,07	45,49	15,24	44,77	15,59
	-11.8	-13.0	48,26	14,29	47,52	14,60	46,76	14,94	46,39	15,11	46,02	15,28	45,27	15,61
	-9.8	-11.0	48,82	14,35	48,05	14,66	47,28	14,98	46,89	15,13	46,51	15,30	45,73	15,64
	-9.5	-10.0	49,08	14,29	48,30	14,60	47,52	14,92	47,13	15,08	46,74	15,23	45,95	15,55
	-8.5	-9.1	49,31	14,31	48,52	14,61	47,73	14,93	47,34	15,09	46,94	15,24	46,16	15,56
	-7.0	-7.6	49,68	14,32	48,88	14,63	48,08	14,93	47,68	15,08	47,28	15,24	46,47	15,56
	-5.0	-5.6	49,31	14,09	48,49	14,38	47,69	14,68	47,28	14,83	46,87	14,97	46,06	15,27
	-3.0	-3.7	51,10	14,28	50,27	14,59	49,43	14,87	49,00	15,02	48,57	15,16	47,72	15,47
	0.0	-0.7	55,44	14,99	54,53	15,30	53,62	15,61	53,17	15,77	52,70	15,92	51,50	15,77
	3.0	2.2	62,24	16,31	61,24	16,66	60,22	17,01	59,72	17,18	59,21	17,34	57,11	16,09
	5.0	4.1	67,79	17,42	66,71	17,80	65,62	18,16	65,07	18,36	64,03	17,84	61,59	16,39
	7.0	6.0	76,38	19,25	75,58	19,77	74,25	20,16	73,30	19,74	71,97	18,98	66,95	16,82
	9.0	7.9	79,41	19,65	78,04	20,03	76,43	19,91	75,03	19,13	71,97	17,93	66,95	15,88
	11.0	9.8	81,93	19,90	80,51	20,30	78,14	19,26	77,00	18,55	71,97	16,92	66,95	14,92
	13.0	11.8	84,47	20,13	82,79	20,10	78,14	18,11	77,00	17,45	71,97	15,86	66,95	14,09
	15.0	13.7	86,98	20,39	84,49	19,37	78,14	17,10	77,00	16,40	71,97	14,92	66,95	13,33
	18.0	16,6	89,82	19,76	87,03	18,27	78,14	15,56	77,00	14,93	71,97	13,67	66,95	12,19
	20.0	19,6	93,48	18,80	87,03	16,64	78,14	14,18	77,00	13,66	71,97	12,50	66,95	11,13
	23.0	22,4	93,70	17,16	87,03	15,11	78,14	12,95	77,00	12,49	71,97	11,39	66,95	10,05
	26.0	25,3	93,70	15,57	87,03	13,74	78,14	11,78	77,00	11,32	71,97	10,28	66,95	10,56
	30.0	28,1	93,70	14,13	87,03	12,50	80,47	11,04	77,00	10,26	73,72	9,51	66,95	11,10
100%	-29.8	-30.0	46,16	14,00	45,27	14,43	44,38	14,84	43,94	15,05	43,50	15,24	42,61	15,64
	-25.0	-25.4	46,16	14,09	45,27	14,46	44,38	14,81	43,94	14,99	43,50	15,16	42,61	15,52
	-19.8	-20.0	46,16	14,19	45,27	14,48	44,38	14,79	43,94	14,94	43,50	15,09	42,61	15,39
	-18.8	-19.0	46,16	14,18	45,27	14,46	44,38	14,77	43,94	14,91	43,50	15,06	43,02	15,51
	-16.7	-17.0	46,16	14,13	45,66	14,55	44,87	14,86	44,48	15,02	44,09	15,19	43,99	15,76
	-13.7	-15.0	46,76	14,37	46,66	14,90	45,94	15,24	45,58	15,42	45,22	15,58	44,51	15,95
	-11.8	-13.0	47,97	14,63	47,22	14,96	46,49	15,31	46,11	15,46	45,74	15,63	45,00	15,99
	-9.8	-11.0	48,52	14,69	47,76	15,02	47,00	15,35	46,61	15,53	46,23	15,68	45,47	16,01
	-9.5	-10.0	48,78	14,64	48,01	14,96	47,24	15,28	46,85	15,45	46,46	15,62	45,69	15,94
	-8.5	-9.1	49,01	14,68	48,23	14,98	47,45	15,30	47,06	15,47	46,67	15,63	45,89	15,97
	-7.0	-7.6	49,38	14,70	48,59	15,01	47,79	15,32	47,39	15,48	47,00	15,66	46,20	15,96
	-5.0	-5.6	49,00	14,47	48,20	14,77	47,39	15,09	46,99	15,23	46,59	15,40	45,65	15,47
	-3.0	-3.7	50,77	14,70	49,94	15,00	49,10	15,31	48,68	15,47	48,26	15,63	46,93	15,09
	0.0	-0.7	55,08	15,46	54,17	15,79	53,27	16,10	52,82	16,27	52,11	16,01	50,26	14,83
	3.0	2.2	61,82	16,87	60,83	17,21	59,82	17,55	58,80	16,93	57,76	16,32	55,55	15,04
	5.0	4.1	67,33	18,03	66,26	18,40	64,61	17,95	63,44	17,30	61,38	16,38	59,29	15,15
	7.0	6.0	75,92	19,96	75,09	20,47	73,00	19,20	70,15	18,09	66,96	16,86	59,29	14,26
	9.0	7.9	78,35	20,25	76,84	19,89	73,00	18,13	70,15	17,05	66,96	15,92	59,29	13,54
	11.0	9.8	81,38	20,68	76,84	18,78	73,00	17,10	70,15	16,07	66,96	14,98	59,29	12,82
	13.0	11.8	83,21	19,97	76,84	17,67	73,00	16,07	70,15	15,09	66,96	14,13	59,29	12,10
	15.0	13.7	83,21	18,84	76,84	16,66	73,00	15,11	70,15	14,24	66,96	13,36	59,29	11,43
	18.0	16,6	83,21	17,21	79,14	15,65	73,04	13,83	70,15	13,04	66,96	12,24	62,04	11,30
	20.0	19,6	83,21	15,68	79,14	14,26	73,04	12,66	70,15	11,92	66,96	11,13	62,04	9,84
	23.0	22,4	83,21	14,21	79,14	13,01	73,04	11,50	70,15	10,80	66,96	10,09	62,04	10,32
	26.0	25,3	83,21	12,99	79,14	11,80	73,04	10,38	70,15	9,73	66,96	10,57	62,04	9,43
	30.0	28,1	85,29	12,17	79,14	10,71	73,04	9,36	70,15	8,76	66,96	11,07	62,04	8,61

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
90%	-29.8	-30.0	41,54	13,04	40,75	13,41	39,95	13,78	39,55	13,96	39,14	14,18	38,35	14,50
	-25.0	-25.4	41,54	13,11	40,75	13,44	39,95	13,76	39,55	13,92	39,14	14,10	38,35	14,41
	-19.8	-20.0	41,96	13,33	41,26	13,64	40,54	13,96	40,83	14,33	40,51	14,52	39,89	14,90
	-18.8	-19.0	42,11	13,36	42,03	13,89	41,39	14,23	41,08	14,41	40,75	14,57	40,13	14,94
	-16.7	-17.0	43,20	13,68	42,55	14,01	41,89	14,35	41,56	14,53	41,23	14,67	40,58	15,04
	-13.7	-15.0	43,71	13,88	43,04	14,20	42,36	14,53	42,02	14,70	41,68	14,86	41,00	15,20
	-11.8	-13.0	44,19	13,96	43,50	14,26	42,81	14,58	42,45	14,74	42,10	14,90	41,40	15,22
	-9.8	-11.0	44,64	14,02	43,93	14,32	43,21	14,62	42,85	14,79	42,49	14,94	41,78	15,26
	-9.5	-10.0	44,85	13,98	44,12	14,27	43,40	14,57	43,04	14,73	42,67	14,87	41,79	14,93
	-8.5	-9.1	45,03	14,00	44,30	14,30	43,57	14,60	43,20	14,74	42,83	14,90	41,79	14,69
	-7.0	-7.6	45,32	14,03	44,58	14,33	43,84	14,63	43,47	14,77	43,09	14,92	41,79	14,26
	-5.0	-5.6	44,90	13,83	44,15	14,11	43,41	14,39	43,03	14,54	42,50	14,38	41,08	13,45
	-3.0	-3.7	46,51	14,05	45,74	14,34	44,96	14,63	44,44	14,50	43,72	14,04	42,23	13,10
	0.0	-0.7	50,49	14,81	49,65	15,12	48,46	14,79	47,70	14,31	46,90	13,82	45,22	12,83
	3.0	2.2	56,76	16,22	55,61	16,14	53,84	15,11	52,91	14,58	51,98	14,05	50,01	13,01
	5.0	4.1	61,91	17,39	60,16	16,54	58,14	15,41	57,11	14,85	55,25	14,08	53,36	13,17
	7.0	6.0	70,55	18,99	67,60	17,58	65,70	16,45	63,03	15,45	61,41	14,77	53,36	12,48
	9.0	7.9	71,36	18,16	69,16	16,97	65,70	15,48	63,03	14,55	61,41	14,00	53,36	11,82
	11.0	9.8	73,27	17,62	71,31	16,50	65,70	14,58	63,03	13,79	61,41	13,26	53,36	11,18
	13.0	11.8	74,89	16,92	71,31	15,46	65,70	13,76	63,03	13,01	61,41	12,50	53,36	10,54
	15.0	13.7	74,89	15,94	71,31	14,55	65,70	13,01	63,03	12,30	61,41	11,80	53,36	9,91
	18.0	16,6	74,89	14,50	71,31	13,36	65,76	11,94	63,03	11,23	61,41	11,18	53,36	10,25
	20.0	19,6	74,89	13,24	71,31	12,20	65,76	10,86	63,03	10,19	61,41	9,73	53,36	9,38
	23.0	22,4	74,89	12,09	71,31	11,08	65,76	9,79	63,03	10,62	61,41	10,20	53,36	8,56
	26.0	25,3	76,73	11,22	71,31	9,97	65,76	10,28	63,03	9,71	61,41	9,30	53,36	7,79
	30.0	28,1	76,73	10,17	71,31	8,97	65,76	10,81	63,03	8,88	61,41	8,48	54,87	7,29
80%	-29.8	-30.0	36,93	12,03	36,21	12,39	35,51	12,69	35,16	12,88	34,80	13,05	34,09	13,24
	-25.0	-25.4	36,93	12,11	36,58	12,53	35,96	12,86	35,65	13,03	35,89	13,41	35,24	13,68
	-19.8	-20.0	38,78	12,79	38,19	13,11	37,60	13,44	37,31	13,61	37,02	13,78	36,43	14,13
	-18.8	-19.0	39,00	12,87	38,40	13,17	37,81	13,50	37,50	13,68	37,21	13,83	36,62	14,16
	-16.7	-17.0	39,43	12,99	38,81	13,30	38,20	13,61	37,89	13,76	37,58	13,92	36,97	14,25
	-13.7	-15.0	39,82	13,18	39,19	13,48	38,56	13,78	38,24	13,94	37,92	14,10	37,14	14,17
	-11.8	-13.0	40,19	13,26	39,55	13,54	38,89	13,84	38,57	13,99	38,25	14,14	37,14	13,68
	-9.8	-11.0	40,54	13,30	39,88	13,60	39,21	13,88	38,88	14,04	38,45	14,00	37,15	13,18
	-9.5	-10.0	40,70	13,27	40,04	13,56	39,37	13,83	39,03	13,98	38,44	13,68	37,15	12,86
	-8.5	-9.1	40,84	13,31	40,17	13,59	39,50	13,87	39,08	13,85	38,44	13,44	37,15	12,63
	-7.0	-7.6	41,08	13,35	40,40	13,61	39,68	13,83	39,07	13,44	38,44	13,04	37,14	12,24
	-5.0	-5.6	40,64	13,14	39,96	13,40	38,98	13,06	38,39	12,67	37,78	12,30	36,52	11,51
	-3.0	-3.7	42,10	13,37	41,32	13,51	40,12	12,75	39,50	12,35	38,87	11,98	37,55	11,18
	0.0	-0.7	45,69	14,11	44,41	13,34	43,07	12,55	42,38	12,14	41,69	11,75	40,21	11,02
	3.0	2.2	50,93	14,50	49,42	13,63	47,86	12,76	47,04	12,32	46,21	11,96	44,45	11,26
	5.0	4.1	55,17	14,84	53,46	13,92	51,70	13,00	50,78	12,60	49,11	12,05	47,43	11,39
	7.0	6.0	62,71	15,94	60,09	14,75	58,40	13,90	57,07	13,44	53,59	12,46	48,73	11,08
	9.0	7.9	63,43	15,21	61,47	14,20	58,40	13,18	57,07	12,74	53,59	11,80	48,73	10,45
	11.0	9.8	65,13	14,69	61,47	13,44	58,40	12,48	57,07	12,06	53,59	11,17	48,73	9,87
	13.0	11.8	66,57	14,09	61,47	12,68	58,40	11,76	57,07	11,32	53,59	10,49	48,73	10,28
	15.0	13.7	66,57	13,33	63,34	12,35	58,40	11,08	57,07	10,67	53,59	9,88	48,73	9,77
	18.0	16,6	68,17	12,51	63,34	11,30	59,55	10,70	57,07	10,09	53,59	10,23	48,73	9,03
	20.0	19,6	68,17	11,39	63,34	10,25	59,55	10,69	57,07	10,09	53,59	9,34	48,73	8,25
	23.0	22,4	68,17	10,29	63,34	9,21	59,55	9,75	57,07	9,21	53,59	8,53	48,73	7,53
	26.0	25,3	68,17	9,23	63,34	9,73	59,55	8,90	57,07	8,40	53,59	7,76	48,73	6,68
	30.0	28,1	68,17	8,27	63,34	10,27	59,55	8,12	57,07	7,65	53,59	7,06	48,73	5,94

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
70%	-29.8	-30.0	32,31	11,01	32,02	11,41	31,48	11,75	31,69	12,10	30,84	11,93	29,83	11,48
	-25.0	-25.4	33,91	11,65	33,42	11,98	32,92	12,32	32,68	12,50	32,33	12,57	31,15	12,13
	-19.8	-20.0	34,90	12,08	34,36	12,38	33,81	12,70	33,54	12,87	33,28	13,01	32,36	12,74
	-18.8	-19.0	35,07	12,15	34,52	12,44	33,97	12,75	33,70	12,90	33,42	13,06	32,51	12,78
	-16.7	-17.0	35,39	12,28	34,83	12,56	34,26	12,85	33,97	13,00	33,64	13,07	32,51	12,37
	-13.7	-15.0	35,68	12,46	35,11	12,74	34,53	13,02	34,19	13,08	33,64	12,74	32,51	12,04
	-11.8	-13.0	35,97	12,53	35,38	12,80	34,72	12,93	34,19	12,62	33,64	12,28	32,51	11,59
	-9.8	-11.0	36,24	12,59	35,64	12,86	34,72	12,48	34,19	12,15	33,64	11,82	32,51	11,13
	-9.5	-10.0	36,37	12,56	35,76	12,82	34,73	12,17	34,19	11,86	33,64	11,52	32,51	10,84
	-8.5	-9.1	36,47	12,60	35,76	12,61	34,73	11,98	34,19	11,65	33,64	11,31	32,51	10,61
	-7.0	-7.6	36,65	12,62	35,76	12,26	34,73	11,61	34,19	11,28	33,65	10,95	32,51	10,32
	-5.0	-5.6	36,09	12,14	35,12	11,54	34,11	10,93	33,59	10,60	33,06	10,28	31,95	9,75
	-3.0	-3.7	37,16	11,87	36,15	11,26	35,10	10,63	34,57	10,31	34,01	10,03	32,85	9,53
	0.0	-0.7	39,98	11,71	38,86	11,07	37,70	10,43	37,09	10,18	36,47	9,93	35,18	9,40
	3.0	2.2	44,56	11,96	43,24	11,26	41,87	10,70	41,17	10,44	40,42	10,15	38,90	9,59
	5.0	4.1	48,27	12,22	46,79	11,56	45,24	10,98	44,42	10,67	42,98	10,22	41,50	9,67
	7.0	6.0	54,88	13,11	52,58	12,30	51,10	11,74	49,02	11,13	46,88	10,56	42,64	10,31
	9.0	7.9	55,50	12,55	53,79	11,92	51,18	11,13	49,02	10,52	46,88	9,88	42,64	9,62
	11.0	9.8	56,99	12,21	55,44	11,63	51,18	10,49	49,02	9,93	46,88	10,38	42,64	9,08
	13.0	11.8	58,25	11,74	55,44	10,93	51,18	9,85	49,02	10,38	46,88	9,76	42,64	8,51
	15.0	13.7	58,25	11,06	55,44	10,30	51,18	10,50	49,02	9,85	46,88	9,20	42,64	8,00
	18.0	16.6	59,70	10,35	55,44	10,65	51,18	9,62	49,02	9,08	46,88	8,49	42,64	7,40
	20.0	19.6	59,70	9,34	55,44	9,73	51,18	8,77	49,02	8,29	46,88	7,84	42,64	6,76
	23.0	22.4	59,70	9,80	55,44	8,89	51,18	7,99	49,02	7,55	46,88	7,17	42,64	6,20
	26.0	25.3	59,70	8,92	55,44	8,08	51,18	7,29	49,02	6,73	46,88	6,29	42,64	5,39
	30.0	28,1	59,70	8,11	55,44	7,34	51,18	6,65	49,02	6,00	46,88	5,52	42,64	4,69
60%	-29.8	-30.0	29,24	10,54	28,82	10,86	28,01	10,70	27,47	10,50	26,96	10,40	25,79	10,09
	-25.0	-25.4	30,04	10,96	29,59	11,27	28,89	11,22	28,44	11,06	27,97	10,91	27,01	10,53
	-19.8	-20.0	30,75	11,37	30,27	11,64	29,66	11,71	29,26	11,58	28,84	11,37	27,87	10,83
	-18.8	-19.0	30,87	11,42	30,38	11,69	29,76	11,74	29,31	11,47	28,83	11,19	27,87	10,65
	-16.7	-17.0	31,11	11,54	30,61	11,80	29,76	11,39	29,31	11,13	28,83	10,84	27,87	10,29
	-13.7	-15.0	31,33	11,71	30,65	11,60	29,76	11,08	29,31	10,81	28,83	10,54	27,87	9,97
	-11.8	-13.0	31,50	11,69	30,65	11,19	29,76	10,67	29,31	10,40	28,84	10,13	27,87	9,62
	-9.8	-11.0	31,50	11,28	30,64	10,77	29,76	10,24	29,31	9,98	28,84	9,71	27,87	9,30
	-9.5	-10.0	31,50	11,00	30,64	10,50	29,76	9,99	29,31	9,71	28,84	9,47	27,87	9,08
	-8.5	-9.1	31,50	10,83	30,65	10,32	29,76	9,80	29,31	9,53	28,84	9,33	27,87	8,93
	-7.0	-7.6	31,50	10,49	30,65	9,99	29,76	9,47	29,31	9,28	28,84	9,08	27,87	8,66
	-5.0	-5.6	30,94	9,88	30,10	9,38	29,24	8,96	28,80	8,76	28,34	8,56	27,39	8,17
	-3.0	-3.7	31,85	9,60	30,98	9,12	30,09	8,75	29,63	8,56	29,15	8,36	28,17	7,97
	0.0	-0.7	34,65	9,64	33,70	9,25	32,71	8,85	32,21	8,65	31,68	8,44	30,61	8,94
	3.0	2.2	38,69	9,94	37,58	9,53	36,43	9,08	35,82	8,86	35,21	8,63	33,91	9,12
	5.0	4.1	41,98	10,24	40,73	9,77	39,42	9,31	38,75	9,08	38,02	9,86	36,07	9,17
	7.0	6.0	47,87	11,04	46,32	10,50	44,26	9,88	43,36	10,51	42,92	10,32	39,24	8,97
	9.0	7.9	49,02	10,68	46,79	10,05	45,20	10,38	44,75	10,12	42,92	9,56	39,24	8,42
	11.0	9.8	50,17	10,33	48,02	9,73	46,60	10,09	44,75	9,55	42,92	8,99	39,24	7,89
	13.0	11.8	50,61	9,79	48,97	10,30	46,60	9,60	44,75	8,97	42,92	8,41	39,24	7,41
	15.0	13.7	51,88	10,68	50,39	10,03	46,60	9,01	44,75	8,40	42,92	7,94	39,24	7,00
	18.0	16.6	53,57	10,10	50,39	9,21	46,60	8,18	44,75	7,79	42,92	7,27	39,24	6,37
	20.0	19.6	53,57	9,22	50,39	8,48	46,60	7,54	44,75	7,12	42,92	6,75	39,24	5,79
	23.0	22.4	53,57	8,38	50,39	7,75	46,60	6,93	44,75	6,44	42,92	6,11	39,24	5,24
	26.0	25.3	53,57	7,64	50,39	6,81	46,60	6,17	44,75	5,66	42,92	5,26	39,24	4,56
	30.0	28,1	54,97	7,14	50,39	5,99	47,48	5,59	45,17	5,02	42,92	4,53	39,24	3,97

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
50%	-29.8	-30.0	25,52	9,91	24,82	9,76	24,11	9,61	23,75	9,51	23,39	9,43	22,65	9,23
	-25.0	-25.4	26,05	10,26	25,35	9,99	24,62	9,72	24,26	9,57	23,88	9,42	23,11	9,14
	-19.8	-20.0	26,50	10,60	25,81	10,21	25,08	9,82	24,70	9,61	24,33	9,38	23,52	9,03
	-18.8	-19.0	26,50	10,44	25,81	10,06	25,08	9,65	24,70	9,44	24,32	9,23	23,52	8,92
	-16.7	-17.0	26,50	10,13	25,81	9,73	25,08	9,32	24,70	9,10	24,33	8,95	23,53	8,67
	-13.7	-15.0	26,51	9,86	25,81	9,45	25,08	9,04	24,70	8,87	24,33	8,73	23,53	8,44
	-11.8	-13.0	26,50	9,47	25,81	9,08	25,08	8,73	24,70	8,58	24,32	8,42	23,52	8,12
	-9.8	-11.0	26,50	9,10	25,81	8,72	25,08	8,42	24,70	8,26	24,32	8,11	23,53	7,79
	-9.5	-10.0	26,51	8,87	25,81	8,51	25,08	8,21	24,70	8,07	24,32	7,91	23,53	7,60
	-8.5	-9.1	26,51	8,69	25,81	8,39	25,08	8,08	24,70	7,92	24,33	7,78	23,53	7,46
	-7.0	-7.6	26,50	8,43	25,81	8,15	25,08	7,84	24,71	7,70	24,33	7,54	23,52	7,99
	-5.0	-5.6	26,02	7,96	25,34	7,68	24,63	7,40	24,26	7,24	23,89	7,09	23,12	7,52
	-3.0	-3.7	26,81	7,78	26,10	7,51	25,37	7,22	24,98	7,07	24,59	7,68	23,78	7,33
	0.0	-0.7	28,87	7,72	28,08	7,42	27,27	7,93	26,84	7,76	26,41	7,58	25,50	7,21
	3.0	2.2	32,25	7,94	31,31	8,49	30,36	8,12	29,85	7,93	29,34	7,75	28,26	7,36
	5.0	4.1	34,99	8,16	33,94	8,72	32,84	8,31	32,27	8,10	31,69	7,89	30,06	7,29
	7.0	6.0	39,89	9,63	38,60	9,03	36,88	8,39	36,13	8,08	35,77	7,86	30,06	6,43
	9.0	7.9	40,89	9,27	38,96	8,58	37,66	8,06	37,29	7,84	35,77	7,42	30,06	6,09
	11.0	9.8	41,80	8,90	40,01	8,27	38,84	7,77	37,29	7,38	35,77	7,01	30,06	5,74
	13.0	11.8	42,17	8,41	40,81	7,88	38,84	7,30	37,61	6,99	35,97	6,61	32,76	5,87
	15.0	13.7	43,23	8,21	42,00	7,70	38,84	6,90	37,61	6,58	35,97	6,20	32,76	5,48
	18.0	16,6	44,64	7,73	42,00	7,01	38,84	6,26	37,61	5,99	35,97	5,61	32,76	4,92
	20.0	19,6	44,64	7,03	42,81	6,71	38,84	5,66	37,61	5,37	35,97	5,02	32,76	4,46
	23.0	22,4	44,64	6,44	42,81	5,99	38,84	5,14	37,61	4,83	35,97	4,58	32,76	4,09
	26.0	25,3	44,64	5,59	42,81	5,14	39,27	4,53	37,61	4,28	35,97	4,07	32,76	3,63
	30.0	28,1	44,64	4,85	42,81	4,42	39,27	3,94	37,61	3,79	35,97	3,63	32,76	3,24

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

Tabella di capacità

Sistema VRF Serie IV8-730WV2RN1E(PRO)

Tabella della capacità di riscaldamento

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	-29.8	-30.0	57,41	20,96	56,30	21,60	55,20	22,18	54,65	22,60	54,10	22,88	52,99	23,47
	-25.0	-25.4	57,41	21,13	56,30	21,69	55,20	22,23	54,65	22,54	54,10	22,79	52,99	23,31
	-19.8	-20.0	57,41	21,31	56,30	21,78	55,20	22,28	54,65	22,48	54,10	22,70	52,99	23,16
	-18.8	-19.0	57,41	21,29	56,30	21,76	55,20	22,19	54,65	22,43	54,10	22,65	52,99	23,07
	-16.7	-17.0	57,41	21,22	56,30	21,66	55,20	22,10	54,65	22,33	54,10	22,52	52,99	22,95
	-13.7	-15.0	57,41	21,27	56,30	21,70	55,20	22,11	54,65	22,32	54,53	22,71	53,54	23,18
	-11.8	-13.0	57,85	21,25	56,86	21,72	55,87	22,19	55,37	22,42	54,87	22,65	54,76	23,47
	-9.8	-11.0	58,22	21,20	58,13	21,99	57,22	22,51	56,77	22,76	56,31	23,01	55,39	23,50
	-9.5	-10.0	59,40	21,44	58,48	21,93	57,55	22,42	57,09	22,66	56,62	22,89	55,69	23,40
	-8.5	-9.1	59,70	21,48	58,77	21,97	57,83	22,45	57,37	22,67	56,90	22,94	55,95	23,41
	-7.0	-7.6	60,20	21,49	59,25	21,97	58,30	22,43	57,82	22,68	57,34	22,92	56,38	23,40
	-5.0	-5.6	59,83	21,15	58,87	21,59	57,90	22,06	57,42	22,29	56,93	22,53	55,96	22,98
	-3.0	-3.7	62,02	21,41	61,02	21,88	60,02	22,32	59,51	22,57	59,01	22,79	57,99	23,25
	0.0	-0.7	67,28	22,38	66,20	22,87	65,11	23,34	64,56	23,60	64,01	23,82	62,91	24,32
	3.0	2.2	75,43	24,21	74,24	24,76	73,03	25,30	72,43	25,56	71,82	25,83	70,60	26,35
	5.0	4.1	80,96	25,43	80,77	26,33	79,48	26,93	78,83	27,21	78,19	27,49	76,88	28,07
	7.0	6.0	94,42	29,02	92,61	29,57	90,79	30,11	89,88	30,38	88,98	30,63	87,16	30,91
	9.0	7.9	97,44	29,32	95,57	29,90	93,70	30,43	92,76	30,71	91,82	30,99	87,16	29,21
	11.0	9.8	100,47	29,63	98,53	30,20	96,60	30,75	95,64	31,02	94,67	31,29	87,16	27,62
	13.0	11.8	103,49	29,87	101,50	30,45	99,51	31,03	98,51	31,31	94,67	29,88	88,35	26,36
	15.0	13.7	106,51	30,14	104,46	30,73	102,41	31,35	101,39	31,08	94,67	28,22	88,35	24,81
	18.0	16,6	111,04	30,56	108,91	31,20	105,99	30,62	101,39	28,43	94,67	25,79	88,35	22,65
	20.0	19,6	115,57	30,94	113,35	31,60	105,99	28,00	101,56	26,04	94,67	23,55	88,35	20,67
	23.0	22,4	120,11	31,39	114,76	29,32	105,99	25,55	101,56	23,72	94,67	21,36	88,35	18,90
	26.0	25,3	124,64	30,79	114,76	26,78	105,99	23,23	101,56	21,48	94,67	19,49	88,35	17,17
	30.0	28,1	126,51	29,54	114,76	24,46	105,99	21,12	101,56	19,46	97,25	18,27	88,35	15,59
120%	-29.8	-30.0	54,88	20,54	53,83	21,18	52,77	21,81	52,25	22,13	51,72	22,43	50,66	23,01
	-25.0	-25.4	54,88	20,70	53,83	21,24	52,77	21,79	52,25	22,06	51,72	22,32	50,66	22,84
	-19.8	-20.0	54,88	20,87	53,83	21,30	52,77	21,78	52,25	21,98	51,72	22,22	50,66	22,67
	-18.8	-19.0	54,88	20,85	53,83	21,32	52,77	21,73	52,25	21,97	51,72	22,17	50,66	22,60
	-16.7	-17.0	54,88	20,81	53,83	21,22	52,77	21,64	52,25	21,85	51,72	22,06	51,13	22,67
	-13.7	-15.0	54,88	20,84	54,29	21,42	53,34	21,87	52,87	22,11	52,40	22,34	52,24	23,16
	-11.8	-13.0	55,59	20,91	55,45	21,69	54,59	22,19	54,15	22,44	53,72	22,68	52,85	23,19
	-9.8	-11.0	56,99	21,28	56,11	21,79	55,22	22,26	54,77	22,51	54,33	22,74	53,43	23,22
	-9.5	-10.0	57,32	21,22	56,42	21,68	55,52	22,16	55,07	22,41	54,62	22,64	53,71	23,10
	-8.5	-9.1	57,61	21,26	56,70	21,70	55,79	22,19	55,33	22,43	54,87	22,66	53,96	23,13
	-7.0	-7.6	58,07	21,26	57,14	21,72	56,22	22,20	55,75	22,42	55,28	22,65	54,35	23,13
	-5.0	-5.6	57,68	20,92	56,74	21,35	55,80	21,80	55,33	22,02	54,86	22,25	53,91	22,72
	-3.0	-3.7	59,78	21,19	58,81	21,63	57,83	22,09	57,34	22,31	56,85	22,53	55,87	23,00
	0.0	-0.7	64,87	22,19	63,81	22,66	62,75	23,15	62,22	23,36	61,69	23,61	60,62	24,06
	3.0	2.2	72,76	24,08	71,60	24,60	70,43	25,11	69,84	25,37	69,26	25,63	67,95	25,92
	5.0	4.1	79,18	25,65	77,94	26,22	76,68	26,78	76,05	27,05	75,42	27,35	73,34	26,50
	7.0	6.0	90,27	28,68	88,53	29,19	86,80	29,71	85,93	29,98	85,06	30,22	81,72	27,91
	9.0	7.9	93,16	28,98	91,37	29,53	89,58	30,06	88,68	30,34	87,78	29,80	81,72	26,39
	11.0	9.8	96,05	29,31	94,20	29,87	92,35	30,41	91,43	30,09	87,78	28,18	81,72	24,89
	13.0	11.8	98,94	29,61	97,03	30,17	95,13	30,25	91,43	28,35	87,78	26,53	81,72	23,36
	15.0	13.7	101,82	29,89	99,87	30,50	97,91	29,41	91,43	26,75	87,78	25,01	81,72	21,97
	18.0	16,6	106,16	30,37	104,12	30,12	97,91	26,92	93,76	25,06	87,78	22,81	81,72	20,14
	20.0	19,6	110,49	30,80	104,12	27,56	97,91	24,52	93,76	22,84	87,78	20,74	81,72	18,43
	23.0	22,4	114,16	29,10	104,12	25,13	97,91	22,28	93,76	20,78	87,78	18,99	81,72	16,76
	26.0	25,3	114,16	26,57	105,95	23,25	97,91	20,29	93,76	18,94	87,78	17,27	81,72	15,15
	30.0	28,1	114,16	24,25	105,95	21,15	97,93	18,49	93,76	17,26	89,82	16,07	81,72	13,70

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
110%	-29.8	-30.0	51,84	19,95	50,85	20,58	49,85	21,17	49,35	21,45	48,85	21,75	47,86	22,29
	-25.0	-25.4	51,84	20,09	50,85	20,61	49,85	21,13	49,35	21,38	48,85	21,64	47,86	22,13
	-19.8	-20.0	51,84	20,23	50,85	20,65	49,85	21,10	49,35	21,30	48,85	21,53	47,86	21,97
	-18.8	-19.0	51,84	20,22	50,85	20,64	49,85	21,06	49,35	21,27	48,85	21,48	48,32	22,12
	-16.7	-17.0	51,84	20,17	51,29	20,75	50,40	21,21	49,96	21,45	49,52	21,66	49,39	22,47
	-13.7	-15.0	52,53	20,47	52,41	21,22	51,60	21,74	51,20	21,98	50,79	22,23	49,98	22,74
	-11.8	-13.0	53,88	20,85	53,05	21,30	52,21	21,79	51,79	22,04	51,38	22,29	50,54	22,77
	-9.8	-11.0	54,50	20,93	53,64	21,39	52,78	21,86	52,35	22,07	51,92	22,32	51,06	22,81
	-9.5	-10.0	54,79	20,85	53,92	21,30	53,05	21,76	52,62	22,00	52,18	22,22	51,30	22,69
	-8.5	-9.1	55,05	20,87	54,17	21,32	53,29	21,78	52,85	22,01	52,41	22,24	51,53	22,70
	-7.0	-7.6	55,47	20,89	54,57	21,34	53,68	21,78	53,23	22,00	52,78	22,23	51,88	22,70
	-5.0	-5.6	55,05	20,56	54,14	20,98	53,24	21,41	52,79	21,63	52,33	21,84	51,42	22,28
	-3.0	-3.7	57,05	20,83	56,12	21,28	55,18	21,69	54,70	21,91	54,23	22,12	53,28	22,57
	0.0	-0.7	61,89	21,87	60,88	22,32	59,86	22,78	59,36	23,01	58,84	23,23	57,50	23,01
	3.0	2.2	69,49	23,79	68,37	24,30	67,23	24,82	66,67	25,06	66,10	25,30	63,76	23,48
	5.0	4.1	75,68	25,41	74,48	25,97	73,26	26,50	72,65	26,78	71,49	26,03	68,76	23,91
	7.0	6.0	85,27	28,09	84,38	28,84	82,89	29,41	81,83	28,80	80,35	27,69	74,75	24,54
	9.0	7.9	88,66	28,67	87,13	29,22	85,33	29,05	83,77	27,91	80,35	26,16	74,75	23,16
	11.0	9.8	91,47	29,03	89,88	29,62	87,24	28,10	85,97	27,06	80,35	24,69	74,75	21,77
	13.0	11.8	94,30	29,37	92,43	29,32	87,24	26,42	85,97	25,45	80,35	23,14	74,75	20,56
	15.0	13.7	97,11	29,74	94,33	28,26	87,24	24,94	85,97	23,93	80,35	21,77	74,75	19,44
	18.0	16,6	100,28	28,82	97,16	26,65	87,24	22,70	85,97	21,78	80,35	19,94	74,75	17,78
	20.0	19,6	104,37	27,42	97,16	24,27	87,24	20,68	85,97	19,93	80,35	18,24	74,75	16,23
	23.0	22,4	104,61	25,04	97,16	22,04	87,24	18,89	85,97	18,22	80,35	16,61	74,75	14,66
	26.0	25,3	104,61	22,72	97,16	20,05	87,24	17,19	85,97	16,52	80,35	15,00	74,75	15,41
	30.0	28,1	104,61	20,62	97,16	18,23	89,84	16,11	85,97	14,97	82,30	13,88	74,75	16,19
100%	-29.8	-30.0	51,53	20,42	50,54	21,05	49,55	21,65	49,06	21,96	48,56	22,23	47,57	22,82
	-25.0	-25.4	51,53	20,56	50,54	21,09	49,55	21,61	49,06	21,87	48,56	22,12	47,57	22,64
	-19.8	-20.0	51,53	20,70	50,54	21,12	49,55	21,57	49,06	21,79	48,56	22,01	47,57	22,45
	-18.8	-19.0	51,53	20,69	50,54	21,09	49,55	21,54	49,06	21,75	48,56	21,97	48,03	22,62
	-16.7	-17.0	51,53	20,62	50,98	21,23	50,10	21,68	49,66	21,91	49,22	22,16	49,11	22,99
	-13.7	-15.0	52,21	20,96	52,09	21,73	51,29	22,24	50,89	22,49	50,49	22,73	49,69	23,27
	-11.8	-13.0	53,55	21,35	52,72	21,83	51,90	22,33	51,48	22,56	51,07	22,80	50,24	23,33
	-9.8	-11.0	54,17	21,43	53,32	21,91	52,47	22,40	52,04	22,65	51,61	22,87	50,76	23,35
	-9.5	-10.0	54,46	21,36	53,60	21,82	52,74	22,29	52,31	22,54	51,87	22,79	51,01	23,26
	-8.5	-9.1	54,72	21,41	53,85	21,86	52,98	22,32	52,54	22,57	52,10	22,80	51,23	23,30
	-7.0	-7.6	55,13	21,45	54,25	21,90	53,36	22,35	52,91	22,59	52,47	22,84	51,58	23,29
	-5.0	-5.6	54,70	21,11	53,81	21,55	52,91	22,01	52,46	22,22	52,01	22,46	50,96	22,57
	-3.0	-3.7	56,68	21,45	55,75	21,89	54,82	22,34	54,35	22,57	53,88	22,80	52,39	22,01
	0.0	-0.7	61,49	22,56	60,48	23,03	59,47	23,49	58,97	23,73	58,18	23,35	56,11	21,64
	3.0	2.2	69,02	24,61	67,91	25,11	66,79	25,61	65,65	24,70	64,48	23,81	62,02	21,94
	5.0	4.1	75,17	26,30	73,97	26,85	72,13	26,19	70,83	25,24	68,53	23,90	66,19	22,10
	7.0	6.0	84,76	29,12	83,83	29,87	81,50	28,01	78,32	26,39	74,76	24,60	66,19	20,80
	9.0	7.9	87,47	29,54	85,79	29,01	81,50	26,45	78,32	24,88	74,76	23,23	66,19	19,75
	11.0	9.8	90,86	30,17	85,79	27,40	81,50	24,94	78,32	23,45	74,76	21,86	66,19	18,70
	13.0	11.8	92,90	29,13	85,79	25,78	81,50	23,44	78,32	22,01	74,76	20,61	66,19	17,65
	15.0	13.7	92,90	27,48	85,79	24,30	81,50	22,04	78,32	20,77	74,76	19,49	66,19	16,67
	18.0	16,6	92,90	25,10	88,36	22,83	81,55	20,18	78,32	19,03	74,76	17,85	69,26	16,49
	20.0	19,6	92,90	22,87	88,36	20,80	81,55	18,47	78,32	17,39	74,76	16,24	69,26	14,36
	23.0	22,4	92,90	20,73	88,36	18,98	81,55	16,78	78,32	15,75	74,76	14,72	69,26	15,06
	26.0	25,3	92,90	18,95	88,36	17,22	81,55	15,14	78,32	14,19	74,76	15,42	69,26	13,76
	30.0	28,1	95,22	17,75	88,36	15,63	81,55	13,66	78,32	12,78	74,76	16,15	69,26	12,56

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
90%	-29.8	-30.0	46,38	19,02	45,49	19,56	44,60	20,11	44,15	20,37	43,70	20,68	42,81	21,15
	-25.0	-25.4	46,38	19,13	45,49	19,61	44,60	20,08	44,15	20,31	43,70	20,57	42,81	21,02
	-19.8	-20.0	46,85	19,44	46,06	19,90	45,26	20,36	45,58	20,91	45,23	21,18	44,54	21,74
	-18.8	-19.0	47,01	19,49	46,92	20,27	46,21	20,76	45,86	21,02	45,50	21,25	44,80	21,80
	-16.7	-17.0	48,23	19,95	47,50	20,44	46,77	20,94	46,40	21,19	46,03	21,40	45,30	21,94
	-13.7	-15.0	48,80	20,25	48,05	20,71	47,29	21,20	46,91	21,44	46,53	21,68	45,77	22,18
	-11.8	-13.0	49,34	20,36	48,56	20,81	47,79	21,27	47,39	21,51	47,00	21,73	46,22	22,21
	-9.8	-11.0	49,84	20,45	49,04	20,89	48,24	21,33	47,84	21,57	47,44	21,79	46,64	22,26
	-9.5	-10.0	50,07	20,39	49,26	20,82	48,45	21,26	48,05	21,49	47,64	21,70	46,66	21,78
	-8.5	-9.1	50,27	20,42	49,46	20,86	48,64	21,30	48,23	21,51	47,82	21,74	46,66	21,43
	-7.0	-7.6	50,60	20,47	49,77	20,90	48,94	21,35	48,53	21,55	48,11	21,77	46,66	20,81
	-5.0	-5.6	50,13	20,17	49,29	20,58	48,46	20,99	48,04	21,21	47,45	20,98	45,86	19,62
	-3.0	-3.7	51,93	20,50	51,07	20,92	50,20	21,34	49,61	21,16	48,81	20,48	47,15	19,11
	0.0	-0.7	56,37	21,61	55,43	22,06	54,10	21,57	53,25	20,88	52,36	20,16	50,49	18,72
	3.0	2.2	63,37	23,66	62,08	23,55	60,11	22,05	59,07	21,27	58,03	20,49	55,83	18,98
	5.0	4.1	69,12	25,37	67,16	24,13	64,91	22,48	63,76	21,66	61,68	20,54	59,57	19,22
	7.0	6.0	78,77	27,70	75,47	25,64	73,35	24,00	70,37	22,54	68,56	21,54	59,57	18,21
	9.0	7.9	79,67	26,49	77,21	24,76	73,35	22,58	70,37	21,23	68,56	20,42	59,57	17,24
	11.0	9.8	81,80	25,71	79,61	24,07	73,35	21,27	70,37	20,12	68,56	19,34	59,57	16,31
	13.0	11.8	83,61	24,68	79,61	22,56	73,35	20,08	70,37	18,98	68,56	18,24	59,57	15,37
	15.0	13.7	83,61	23,26	79,61	21,22	73,35	18,98	70,37	17,95	68,56	17,21	59,57	14,45
	18.0	16,6	83,61	21,16	79,61	19,49	73,42	17,42	70,37	16,38	68,56	16,31	59,57	14,95
	20.0	19,6	83,61	19,32	79,61	17,80	73,42	15,84	70,37	14,86	68,56	14,19	59,57	13,68
	23.0	22,4	83,61	17,64	79,61	16,16	73,42	14,28	70,37	15,50	68,56	14,88	59,57	12,49
	26.0	25,3	85,66	16,37	79,61	14,54	73,42	15,00	70,37	14,17	68,56	13,57	59,57	11,36
	30.0	28,1	85,66	14,83	79,61	13,08	73,42	15,77	70,37	12,95	68,56	12,37	61,26	10,63
80%	-29.8	-30.0	41,23	17,55	40,43	18,07	39,64	18,52	39,25	18,79	38,85	19,04	38,06	19,32
	-25.0	-25.4	41,23	17,66	40,84	18,28	40,15	18,76	39,80	19,01	40,07	19,57	39,34	19,96
	-19.8	-20.0	43,29	18,66	42,64	19,13	41,98	19,61	41,65	19,85	41,33	20,11	40,67	20,61
	-18.8	-19.0	43,54	18,77	42,87	19,22	42,21	19,69	41,87	19,95	41,54	20,18	40,88	20,66
	-16.7	-17.0	44,02	18,95	43,33	19,40	42,65	19,85	42,30	20,08	41,96	20,30	41,27	20,79
	-13.7	-15.0	44,46	19,23	43,75	19,66	43,05	20,11	42,69	20,34	42,34	20,57	41,47	20,67
	-11.8	-13.0	44,87	19,34	44,15	19,76	43,42	20,19	43,06	20,41	42,70	20,63	41,47	19,95
	-9.8	-11.0	45,26	19,41	44,52	19,84	43,78	20,25	43,41	20,48	42,93	20,43	41,48	19,23
	-9.5	-10.0	45,44	19,36	44,70	19,78	43,95	20,18	43,58	20,39	42,92	19,95	41,48	18,76
	-8.5	-9.1	45,60	19,42	44,85	19,82	44,10	20,23	43,63	20,20	42,92	19,60	41,48	18,42
	-7.0	-7.6	45,86	19,47	45,10	19,86	44,30	20,17	43,62	19,60	42,92	19,03	41,47	17,85
	-5.0	-5.6	45,37	19,17	44,61	19,55	43,52	19,05	42,86	18,49	42,18	17,94	40,77	16,79
	-3.0	-3.7	47,00	19,51	46,13	19,71	44,79	18,60	44,10	18,02	43,40	17,47	41,92	16,31
	0.0	-0.7	51,01	20,59	49,58	19,46	48,09	18,31	47,32	17,71	46,54	17,14	44,89	16,08
	3.0	2.2	56,86	21,15	55,17	19,89	53,43	18,62	52,52	17,98	51,59	17,45	49,63	16,42
	5.0	4.1	61,59	21,65	59,69	20,31	57,72	18,96	56,69	18,38	54,83	17,58	52,95	16,62
	7.0	6.0	70,01	23,26	67,09	21,52	65,20	20,28	63,72	19,61	59,83	18,18	54,40	16,16
	9.0	7.9	70,82	22,19	68,63	20,72	65,20	19,23	63,72	18,58	59,83	17,22	54,40	15,25
	11.0	9.8	72,71	21,43	68,63	19,60	65,20	18,21	63,72	17,60	59,83	16,29	54,40	14,40
	13.0	11.8	74,32	20,55	68,63	18,50	65,20	17,15	63,72	16,52	59,83	15,30	54,40	15,00
	15.0	13.7	74,32	19,44	70,71	18,02	65,20	16,17	63,72	15,57	59,83	14,41	54,40	14,26
	18.0	16,6	76,11	18,25	70,71	16,49	66,48	15,61	63,72	14,72	59,83	14,93	54,40	13,17
	20.0	19,6	76,11	16,61	70,71	14,95	66,48	15,59	63,72	14,72	59,83	13,63	54,40	12,03
	23.0	22,4	76,11	15,01	70,71	13,44	66,48	14,23	63,72	13,44	59,83	12,44	54,40	10,98
	26.0	25,3	76,11	13,46	70,71	14,19	66,48	12,98	63,72	12,25	59,83	11,32	54,40	9,75
	30.0	28,1	76,11	12,07	70,71	14,98	66,48	11,84	63,72	11,16	59,83	10,30	54,40	8,66

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
70%	-29.8	-30.0	36,07	16,06	35,75	16,64	35,15	17,14	35,38	17,65	34,43	17,41	33,30	16,75
	-25.0	-25.4	37,86	16,99	37,31	17,47	36,75	17,98	36,48	18,24	36,09	18,34	34,78	17,69
	-19.8	-20.0	38,96	17,63	38,36	18,06	37,75	18,53	37,45	18,77	37,15	18,98	36,13	18,59
	-18.8	-19.0	39,15	17,73	38,54	18,15	37,92	18,60	37,62	18,82	37,31	19,05	36,30	18,65
	-16.7	-17.0	39,51	17,92	38,88	18,32	38,25	18,75	37,93	18,97	37,56	19,06	36,29	18,05
	-13.7	-15.0	39,84	18,18	39,20	18,58	38,55	19,00	38,17	19,08	37,56	18,58	36,29	17,57
	-11.8	-13.0	40,16	18,28	39,50	18,67	38,76	18,86	38,17	18,41	37,56	17,92	36,30	16,91
	-9.8	-11.0	40,46	18,36	39,79	18,76	38,76	18,21	38,17	17,73	37,56	17,24	36,29	16,23
	-9.5	-10.0	40,60	18,32	39,92	18,70	38,77	17,76	38,17	17,30	37,56	16,80	36,30	15,81
	-8.5	-9.1	40,72	18,38	39,92	18,39	38,77	17,48	38,17	17,00	37,56	16,50	36,29	15,48
	-7.0	-7.6	40,92	18,41	39,92	17,88	38,77	16,94	38,17	16,46	37,57	15,98	36,29	15,06
	-5.0	-5.6	40,29	17,71	39,21	16,84	38,08	15,94	37,50	15,46	36,91	15,00	35,67	14,23
	-3.0	-3.7	41,49	17,31	40,36	16,42	39,19	15,51	38,59	15,04	37,97	14,63	36,68	13,90
	0.0	-0.7	44,64	17,09	43,39	16,15	42,09	15,22	41,41	14,85	40,72	14,48	39,28	13,71
	3.0	2.2	49,75	17,45	48,28	16,43	46,74	15,61	45,96	15,23	45,13	14,81	43,43	13,99
	5.0	4.1	53,89	17,82	52,24	16,86	50,51	16,02	49,59	15,57	47,98	14,91	46,33	14,10
	7.0	6.0	61,27	19,12	58,70	17,95	57,05	17,12	54,73	16,24	52,34	15,41	47,61	15,04
	9.0	7.9	61,96	18,31	60,05	17,39	57,14	16,24	54,73	15,35	52,34	14,42	47,61	14,03
	11.0	9.8	63,63	17,81	61,90	16,97	57,14	15,31	54,73	14,49	52,34	15,15	47,61	13,24
	13.0	11.8	65,03	17,13	61,90	15,95	57,14	14,37	54,73	15,15	52,34	14,24	47,61	12,42
	15.0	13.7	65,03	16,14	61,90	15,03	57,14	15,32	54,73	14,37	52,34	13,42	47,61	11,67
	18.0	16,6	66,65	15,10	61,90	15,54	57,14	14,03	54,73	13,25	52,34	12,38	47,61	10,80
	20.0	19,6	66,65	13,62	61,90	14,20	57,14	12,80	54,73	12,09	52,34	11,44	47,61	9,86
	23.0	22,4	66,65	14,30	61,90	12,97	57,14	11,65	54,73	11,02	52,34	10,46	47,61	9,04
	26.0	25,3	66,65	13,01	61,90	11,79	57,14	10,63	54,73	9,82	52,34	9,18	47,61	7,86
	30.0	28,1	66,65	11,83	61,90	10,71	57,14	9,70	54,73	8,75	52,34	8,06	47,61	6,84
60%	-29.8	-30.0	32,64	15,37	32,18	15,85	31,27	15,61	30,67	15,32	30,10	15,17	28,79	14,72
	-25.0	-25.4	33,54	15,99	33,03	16,44	32,25	16,37	31,75	16,13	31,23	15,91	30,15	15,36
	-19.8	-20.0	34,33	16,58	33,79	16,98	33,11	17,09	32,67	16,89	32,20	16,58	31,11	15,80
	-18.8	-19.0	34,47	16,66	33,92	17,06	33,23	17,13	32,72	16,74	32,19	16,33	31,11	15,54
	-16.7	-17.0	34,73	16,83	34,17	17,22	33,23	16,61	32,72	16,24	32,19	15,82	31,11	15,01
	-13.7	-15.0	34,98	17,08	34,22	16,93	33,23	16,17	32,72	15,77	32,19	15,37	31,11	14,55
	-11.8	-13.0	35,17	17,05	34,22	16,33	33,23	15,56	32,72	15,17	32,20	14,78	31,11	14,04
	-9.8	-11.0	35,17	16,45	34,21	15,71	33,23	14,94	32,72	14,56	32,20	14,17	31,11	13,57
	-9.5	-10.0	35,17	16,05	34,21	15,32	33,23	14,57	32,72	14,17	32,20	13,82	31,11	13,24
	-8.5	-9.1	35,17	15,80	34,22	15,05	33,23	14,29	32,72	13,90	32,20	13,61	31,11	13,03
	-7.0	-7.6	35,17	15,31	34,22	14,58	33,23	13,81	32,72	13,54	32,20	13,25	31,11	12,63
	-5.0	-5.6	34,54	14,41	33,60	13,68	32,64	13,07	32,15	12,78	31,64	12,49	30,58	11,92
	-3.0	-3.7	35,56	14,01	34,59	13,31	33,59	12,77	33,08	12,49	32,54	12,19	31,45	11,63
	0.0	-0.7	38,68	14,06	37,62	13,50	36,52	12,91	35,96	12,62	35,37	12,32	34,17	13,04
	3.0	2.2	43,19	14,50	41,96	13,90	40,67	13,25	39,99	12,92	39,31	12,59	37,86	13,30
	5.0	4.1	46,87	14,94	45,47	14,26	44,01	13,58	43,26	13,24	42,45	14,38	40,27	13,38
	7.0	6.0	53,44	16,10	51,71	15,32	49,41	14,42	48,41	15,33	47,92	15,05	43,81	13,08
	9.0	7.9	54,73	15,58	52,24	14,66	50,46	15,15	49,96	14,76	47,92	13,94	43,81	12,28
	11.0	9.8	56,01	15,07	53,61	14,20	52,03	14,72	49,96	13,93	47,92	13,11	43,81	11,51
	13.0	11.8	56,50	14,28	54,67	15,03	52,03	14,00	49,96	13,08	47,92	12,27	43,81	10,81
	15.0	13.7	57,92	15,58	56,26	14,63	52,03	13,14	49,96	12,26	47,92	11,58	43,81	10,21
	18.0	16,6	59,81	14,73	56,26	13,43	52,03	11,94	49,96	11,36	47,92	10,60	43,81	9,29
	20.0	19,6	59,81	13,45	56,26	12,37	52,03	11,00	49,96	10,38	47,92	9,84	43,81	8,44
	23.0	22,4	59,81	12,22	56,26	11,30	52,03	10,11	49,96	9,39	47,92	8,91	43,81	7,64
	26.0	25,3	59,81	11,14	56,26	9,94	52,03	9,00	49,96	8,25	47,92	7,67	43,81	6,65
	30.0	28,1	61,37	10,42	56,26	8,74	53,01	8,16	50,43	7,32	47,92	6,61	43,81	5,79

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)

CR	Temperatura esterna		Temperatura interna (°C BS)											
			16.0		18.0		20.0		21.0		22.0		24.0	
	(°C BS)	(°C BU)	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
50%	-29.8	-30.0	28,49	14,46	27,71	14,24	26,92	14,02	26,52	13,87	26,11	13,76	25,29	13,46
	-25.0	-25.4	29,08	14,97	28,30	14,58	27,49	14,18	27,08	13,96	26,66	13,74	25,80	13,33
	-19.8	-20.0	29,59	15,46	28,81	14,89	28,00	14,32	27,58	14,02	27,16	13,69	26,26	13,17
	-18.8	-19.0	29,59	15,23	28,81	14,67	28,00	14,08	27,58	13,77	27,15	13,46	26,26	13,01
	-16.7	-17.0	29,59	14,78	28,81	14,19	28,00	13,59	27,58	13,28	27,16	13,05	26,27	12,65
	-13.7	-15.0	29,60	14,38	28,81	13,78	28,00	13,19	27,58	12,94	27,16	12,74	26,27	12,31
	-11.8	-13.0	29,59	13,82	28,81	13,24	28,00	12,73	27,58	12,51	27,15	12,28	26,26	11,84
	-9.8	-11.0	29,59	13,27	28,81	12,72	28,00	12,28	27,58	12,05	27,15	11,83	26,27	11,37
	-9.5	-10.0	29,60	12,94	28,81	12,42	28,00	11,98	27,58	11,77	27,15	11,54	26,27	11,09
	-8.5	-9.1	29,60	12,68	28,82	12,24	28,00	11,79	27,58	11,56	27,16	11,35	26,27	10,88
	-7.0	-7.6	29,59	12,30	28,82	11,89	28,00	11,44	27,59	11,23	27,16	11,00	26,26	11,65
	-5.0	-5.6	29,05	11,61	28,29	11,21	27,50	10,79	27,09	10,56	26,67	10,35	25,81	10,97
	-3.0	-3.7	29,93	11,35	29,14	10,96	28,32	10,54	27,89	10,31	27,45	11,21	26,55	10,70
	0.0	-0.7	32,23	11,26	31,35	10,83	30,44	11,57	29,97	11,32	29,48	11,06	28,47	10,52
	3.0	2.2	36,00	11,58	34,96	12,39	33,89	11,85	33,33	11,57	32,76	11,30	31,55	10,73
	5.0	4.1	39,06	11,90	37,89	12,72	36,66	12,13	36,03	11,81	35,38	11,51	33,56	10,64
	7.0	6.0	44,54	14,05	43,09	13,18	41,17	12,24	40,34	11,79	39,94	11,47	33,56	9,38
	9.0	7.9	45,65	13,52	43,50	12,51	42,05	11,76	41,63	11,44	39,94	10,83	33,56	8,89
	11.0	9.8	46,67	12,98	44,67	12,07	43,36	11,34	41,63	10,76	39,94	10,23	33,56	8,38
	13.0	11.8	47,08	12,27	45,56	11,50	43,36	10,65	41,99	10,20	40,16	9,64	36,57	8,57
	15.0	13.7	48,26	11,97	46,89	11,23	43,36	10,06	41,99	9,60	40,16	9,04	36,57	8,00
	18.0	16.6	49,84	11,28	46,89	10,22	43,36	9,13	41,99	8,74	40,16	8,19	36,57	7,18
	20.0	19.6	49,84	10,26	47,80	9,79	43,36	8,26	41,99	7,84	40,16	7,33	36,57	6,51
	23.0	22.4	49,84	9,39	47,80	8,74	43,36	7,50	41,99	7,04	40,16	6,68	36,57	5,96
	26.0	25.3	49,84	8,15	47,80	7,50	43,84	6,61	41,99	6,24	40,16	5,94	36,57	5,30
	30.0	28,1	49,84	7,08	47,80	6,45	43,84	5,75	41,99	5,53	40,16	5,29	36,57	4,72

Abbreviazioni:

CR: Rapporto di combinazione

TC: Capacità totale (kW)

PI: Potenza assorbita (compressore + motore ventilatore esterno) (kW)